



## GRIZZLY SECURITY SAFE INSTRUCTION SHEET

Congratulations on your purchase of one of the best values in home security safes. You can sleep better knowing your valuables are secured in a Grizzly safe.

After unpacking the box, consider carefully where you want to place the safe. Choose a location which is not obvious to an intruder and a place where the safe can be firmly secured. Refer to the mounting instructions below.

Be sure to advise your insurance company you have invested in a safe. Many companies offer discounts for the installation and use of these types of security devices.

### **WARNING**

**This safe is extremely heavy and great care should be taken when moving it into place. The safe can tip forward when the door is opened which can cause a pinch point or crushing injury. Once the final location for the safe has been determined, it should be permanently mounted to the building structure to avoid inadvertent tipping or movement. Serious personal injury may occur.**

## MOUNTING INSTRUCTIONS

There are two holes through the back wall of the safe designed to allow bolting of the safe to a structural component such as a concrete wall or a wall stud. Do not attempt to bolt the safe to plaster or wall board as these can be easily broken out.

There are two concrete wall anchors included with the safe for installation against a concrete wall. First mark the hole locations, then move the safe out of the way. Use a drill bit suitable for drilling into concrete, drill a ½" diameter hole no more than 2" deep. Insert the bulbous end of the anchor into the hole, with the nut positioned at the very end of the threaded stud. Use a hammer to pound the anchor into the hole, it will be an interference fit so it will require some force. Take care, however to not deform the threaded end of the anchor. Once the anchor is fully seated, remove the nut, lockwasher and flat washer. Move the safe back into position and push it onto the anchors. Install the washers and nut from the inside of the safe.

If you are putting the safe in a building which has plaster or sheetrocked walls, be sure to locate the safe in a position where the mounting holes will line up with a wall stud. Locate the stud by tapping on the wall or by using one of the several different devices to locate studs. Mark and drill two holes into the stud, making sure you are centered on the stud. Two lag bolts (not supplied) should be used to secure the safe through the inside back of wall of the safe into the drilled holes.

Permanently mounting the safe also provides an extra measure of security in that it makes it very difficult for a thief to take the entire unit. It also provides stability for the heavy weight of the safe and will eliminate any tipping hazard.

# OPENING INSTRUCTIONS

The combination for your safe is shown below. Please be sure to record this number in several different places. For your safety and security, Grizzly does not retain a master record of the combination numbers. In the event the combination is lost, you will need to contact a locksmith or safe expert to open the safe. There is also a special key included which is needed for opening the safe. Three copies of the key are included with your safe, be sure to safely store away at least one of these keys.

To open the safe:

1. Turn the Dial Left (counterclockwise) at least four (4) turns, then line the first number (#1) up with the index mark at the top of the Dial.
2. Turn the dial Right (clockwise) until the first number has gone past the index mark two times, then line up the second number (#2) with the index mark when it comes around.
3. Turn the Dial Left (counterclockwise) one full revolution, then line up the third number (#3) with the index mark on the next revolution.
4. Turn the Dial Right (clockwise) until the fourth number (#4) lines up with the index mark. Do not go past the third number on this revolution.
5. Insert the key into the lock and turn the key Right (clockwise).
6. Turn the handle lever to the Right and pull on the door.

---

**MODEL #:** \_\_\_\_\_  
**SERIAL #:** \_\_\_\_\_  
**Combination:**  
#1 Left \_\_\_\_\_  
#2 Right \_\_\_\_\_  
#3 Left \_\_\_\_\_  
#4 Right \_\_\_\_\_

Cut these out  
and store in  
two different  
secure places.

**MODEL #:** \_\_\_\_\_  
**SERIAL #:** \_\_\_\_\_  
**Combination:**  
#1 Left \_\_\_\_\_  
#2 Right \_\_\_\_\_  
#3 Left \_\_\_\_\_  
#4 Right \_\_\_\_\_