MSDS Name: GOOD STUFF MSDS Number: #V-17 Version Number

MSDS Date: Page Number:

JAN-23-2002

1 of 8

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name:

GOOD STUFF

CAS Number

MIXTURE

Hazard Rating:

Health: 2 Fire: 2 Reactivity: 0 PPI: H

Company Identification:

COATING DEVELOPMENT GROUP, INC

P.O. BOX 14817

SCHILLER & ALLEN STREETS PHILADELPHIA PA 19134-4817

Contact:

MICHAEL A. BARNISIN

Telephone/Fax:

(215) 426-6216 (215) 426-6219

Emergency Phone (24 Hour): MICHAEL A. BARNISIN

(610) 369-7988

Preparer

MARK R. KOCHANOWICZ

COATINGS TECHNOLOGIST

Product Class

TOPCOATS

Trade Name

GOOD STUFF

Product Code

#V-17

SECTION II - INGREDIENT AND HAZARD INFORMATION

| Ingredient Name | CAS Number | Percent | TSCA |
|---|------------------------------------|---------|------|
| MINERAL SPIRITS HMIS Health: 1 Fire: | 8052-41-3 2 Reactivity:0 PPI:H | 52.20 | |
| PSEUDOCUMENE HMIS Health: 2 Fire: | 95-63-6 2 Reactivity:0 PPI:H | 0.94 | |
| XYLENE HMIS Health: 2 Fire: | 1330-20-7 Reactivity:0 PPI:H | 0.70 | |
| MANGANESE COMPOUNDS HMIS Health: 2 Fire: | 15339-36-3 2 Reactivity:0 PPI:H | 0.26 | ~ |
| COLBALT COMPOUNDS HMIS Health: 2 Fire: | COMPOUND 0 Reactivity:0 PPI:H | 0.25 | |
| | | | |

MSDS Name: GOOD STUFF MSDS Number: #V-17

Version Number

MSDS Date: JAN-23-200
Page Number: 2 of 8 JAN-23-2002

YLETHYL KETOXIME (MEKO) 96-29-7
HMIS Health: 2 Fire:2 Reactivity:0 PPI:H_____ 0.22 METHYLETHYL KETOXIME (MEKO) 100-41-4 ETHYLBENZENE HMIS Health: 2 Fire:3 Reactivity:0 PPI:H____

MESITYLENE 108-67-8 0.11

HMIS Health: 2 Fire:2 Reactivity:0 PPI:H_ *** ALL Ingredients in this product are listed in the T.S.C.A. Inventory

SECTION III - HAZARDS IDENTIFICATION

EYE CONTACT - Exposure may cause eye irritation. Symptoms may include stinging, tearing and redness.

INGESTION - Harmful or fatal if swallowed. Pulmonary aspiration hazard if swallowed and/or vomiting occurs - can enter lungs and cause damage.

INHALATION - Excessive exposures may cause irritation to eyes, nose, throat, lungs; respiratory tract; central nervous system (brain) effects; headaches, nausea; dizziness, loss of balance and coordination; unconsciousness, coma; respiratory failure and death. Repeated excessive exposures may cause liver effects or damage; kidney effects or damage.

SKIN - Skin absorption of material may produce systemic toxicity. May cause irritation with prolonged or repeated contact. Removes natural oil and fats from skin.

CANCER HAZARDS

CONTAINS COBALT - Cobalt and its compounds are confirmed animal carcinogens and are suspected human carcinogens.

CONTAINS ETHYLBENZENE - The International Agency for Research on Cancer (IARC) has listed ethylbenzene as a possible cancer causing agent to animals.

Prolonged or repeated overexposure to ethylbenzene may cause the following: - kidney effects - liver effects - lung effects - pituitary effects - thyroid effects - testicular effects.

MSDS Name: GOOD STUFF MSDS Number: #V-17

Version Number

MSDS Date: JAN-23-2002

Page Number: 3 of 8

CONTAINS METHYLETHYL KETOXIME (MEKO) - WARNING -Causes severe eye irratation and may cause eye damage. May cause skin sensitization. Harmful if inhaled. May be harmful if swallowed or absorbed through the skin. May inhibit alcohol metabolism. Chronic inhalation toxicity studies in animals indicate MEKO has the potential to cause methemoglobin, cataract formation and histopathological changes in the upper respiratory tract. A rodent liver carcinogen; relevance to humans is questionable.

SECTION IV - FIRST AID MEASURES

KYE CONTACT - Flush immediately with large amounts of water for at least 15 minutes. Take to a physician for medical treatment.

INGESTION - DO NOT INDUCK VOMITING! This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with head down. Seek medical attention. If possible, do not leave individual unattended.

INHALATION - Remove to fresh air. Restore breathing. Treat symptomatically. Consult a physician.

SKIN CONTACT - Wash affected areas with soap and water. Remove contaminated clothing and shoes. Obtain medical attention if irritation persists. Do not reuse contaminated clothing without laundering. Destroy or thoroughly clean shoes before reuse.

SECTION V - FIRE-FIGHTING MEASURES

Flammability Class IB
Flash Range: 100.oF (37.78oC)
Setaflash

Explosive Range:

Not Available

Use foam, carbon dioxide (CO2) or dry chemical. Water may not be effective to extinguish fire. Use water spray to cool fire-exposed containers and to protect personnel.

Keep personnel removed from and upwind of fire. Wear full fire-fighting turn-out gear (full bunker gear), and respiratory protection (SCBA). Cool container with water spray.

MSDS Name: GOOD STUFF MSDS Number: #V-17

Version Number

MSDS Date: MSDS Date: JAN-23-2002 Page Number: 4 of 8

SECTION VI - ACCIDENTAL RELEASE MRASURES

Contain spilled liquid with sand or earth. DO NOT use combustible materials, such as sawdust.

Eliminate all ignition sources, use explosion-proof equipment. The very fine particles can cause fire or explosion. Vacuum or sweep material and place in a disposal container. Obey all local, state and federal laws regarding chemical spills.

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN - Closed containers may explode when exposed to extreme heat. Store away from high temperatures, sparks and flames. Avoid prolonged skin contact. Do not breath spray mist. Ground containers while pouring and limit free fall to a few inches to prevent static sparks. Avoid spontaneous combustion of contaminated rags and other easily ignitable organic accumalations (such as spray booth residues) by immediate immersion in water. Emptied containers may retain hazardous properties. Do not cut, puncture or weld on or near the container. Store large quantities only in buildings designed to comply with OSHA 1910.106.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

| Occupational Exposure : ACGIH TLV | Limits ACGIH TLV-C | ACGIH STEL | OSHA STEL | OSHA PEL |
|-----------------------------------|-----------------------|------------|-----------|------------|
| MINERAL SPIRITS | | | | |
| 100.00 PPM | N/est | N/est | N/est | 100.00 PPM |
| PSEUDOCUMENE | | | | |
| 25.00 PPM | N/est | N/est | N/est | N/est |
| XYLENE | | | | |
| 100.00 PPM | N/est | N/est | N/est | 100.00 PPM |
| MANGANESE COMPOUNDS | | | | |
| N/est | N/est | N/est | N/est | N/est |
| | | | | |

MSDS Name: GOOD STUFF MSDS Number: #V-17

Version Number

MSDS Date: MSDS Date: JAN-23-2002 Page Number: 5 of 8

COLBALT COMPOUNDS

0.02 mg/M3 N/est N/est N/est $0.05 \, \text{mg/M3}$

METHYLETHYL KETOXIME (MEKO)

N/est N/est N/est N/est N/est

ETHYLBENZENE

100.00 PPM N/est 125.00 PPM 125.00 PPM 100.00 PPM

MESITYLENE

N/est N/est N/est N/est N/est

RESPIRATORY PROTECTION - Provide adequate ventilation. If TLV of the product is exceded, a NIOSH/MSHA jointly approved self-contained breathing apparatus with a full facepiece operated in pressure demand or other positive pressure mode is advised.

VENTILATION - Provide sufficient mechanical and/or local exhaust ventilation to maintain exposure below TLV.

PROTECTIVE GLOVES - Wear resistant gloves such as Buna-N (nitrile rubber).

EYE PROTECTION - Chemical splash goggles in compliance with OSHA regulations are advised.

OTHER PROTECTIVE EQUIPMENT - To prevent prolonged skin contact, wear impervious clothing and boots. Maintain an eyewash facility and an emergency shower.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Form:

LIQUID GEL

Appearance/Color:

AMBER

Odor:

LIGHT PETROLEUM

Solubility (in water):

INSOLUBLE

pH Value:

Not Available

Rvaporation Rate:

Boiling Range: 277.oF - 398.oF (136.11oC - 203.33oC)
Vapor Pressure (mmHg): Not Available
Melting Point: Not Available
Rvaporation Rate: 0.07 **Time Point** 0.07 times Slower than n-Butyl Acetate

Vapor Density:

Heavier than air

MSDS Name: GOOD STUFF MSDS Number: #V-17

Version Number

MSDS Date: JAN-23-2 Page Number: 6 of 8

JAN-23-2002

Partition Coefficient

Not Available

% Volatile Weight

53.85%

% Volatile

BY VOLUME 61.01% 0.87666 1.17 VOC/NV LBS N/A

Specific Gravity:

VOC

Molecular Weight: Heavy Elements (ppm)

0.

SECTION X - STABILITY AND REACTIVITY

Stability:

This product is stable

Hazardous Polymerization: Hazardous polymerization will not occur

SECTION XI - TOXICOLOGICAL INFORMATION

Route

Species

Exposure and Dose

PSEUDOCUMENE

Inhalation Oral

Rat, adult Rat, adult

LC50 18. PPM LD50 5. PPM

ETHYLBENZENE

Oral

Rat, adult

LD50 3500. PPM

THIS PRODUCT CONTAINS ETHYLBENZENE.

A study conducted by the National Toxicology Program states that lifetime inhalation exposure of rats and mice to high concentrations of ethylbenzene (750 ppm) resulted in increases in certain types of cancer, including kidney tumors in rats and lung and liver tumors in mice. Incidences of testicular adenoma were increased along with increased incidences of thyroid effects in rats at 750 ppm; pituitary effects were observed in female mice at 250 ppm. These effects were not observed in animals exposed to lower concentrations of ethylbenzene (75 ppm). The study does not address the relevance of these results to humans.

SECTION XII - ECOLOGICAL INFORMATION

No data available.

MSDS Name: GOOD STUFF MSDS Number: #V-17

Version Number

MSDS Date: JAN-23-2002 Page Number: 7 of 8 MSDS Date:

SECTION XIII - DISPOSAL CONSIDERATIONS

Empty containers should be washed and discarded.

Empty containers should not be used for other purposes. Disposal should be in accordance with local, state or national legislation.

SECTION XIV - TRANSPORT INFORMATION

| UN Number | NA1993 |
|-------------------|--------|
| UN Pack Group | 3 |
| UN Class | III |
| Emergency Storage | N/A |
| MPAG Table Number | N/A |
| Kemmler Code | N/A |
| ICAO/IATA Class | N/A |
| IMDG Class | N/A |

Shipping Name COMBUSTIBLE LIQUIDS NOS (MINERAL

SPIRITS), 3, NA 1993, III

DOT Hazard Class Technical Name

SECTION XV - REGULATORY INFORMATION

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

| Ingredient Name | CAS Number | Percent |
|---------------------|------------|---------|
| PSEUDOCUMENE | 95-63-6 | 0.94 |
| XYLENE | 1330-20-7 | 0.70 |
| MANGANESE COMPOUNDS | 15339-36-3 | 0.26 |
| COLBALT COMPOUNDS | COMPOUND | 0.25 |
| ETHYLBENZENE | 100-41-4 | 0.17 |

MSDS Name: GOOD STUFF MSDS Number: #V-17

Version Number

MSDS Date: JAN-23-2002

Page Number:

8 of 8

-PROP 65 (CARCINOGEN)

WARNING: This product contains a chemical known to the state of

California to cause cancer.

Ingredient Name

CAS Number

Percent

COLBALT COMPOUNDS

COMPOUND

0.25

SECTION XVI - OTHER INFORMATION

NOTICE - Reports have associated repeated and prolonged occupational exposures with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

DISCLAIMER:

The information contained herein applies only to the material identified on this MSDS. The data presented in these sheets are based on information provided by the suppliers of the raw materials and chemicals used in the manufacture of this product and is accurate to the best of our knowledge at the date of issue of this MSDS. Coating Development Group, Inc. makes no warranty with respect to the accuracy of the information provided by its suppliers and disclaims all liability of reliance thereon. Coating Development Group, Inc. warrants only that its products conform to their published specifications. We do not guarantee favorable results and we assume no liability in connection with the use of this product. Final determination of the use of this product is the sole responsibility of the user. Although certain hazards are described herein, it cannot be guaranteed that these are the only hazards that exist. All chemicals may present unknown health hazards and should be used with caution. Read all labels.