



BANDSAW COMPARISON CHART

	G0580	G0555/ G0555P	G0555X	G0457	G0513/ G0513P	G0513X2	G0513X2B	G0513X2F	G0513X2BF	G0636X	G0636XB
BANDSAW SIZE	14"	14"	14"	14"	17"	17"	17"	17"	17"	17"	17"
THROAT CAPACITY (Left of Blade)	13½"	13½"	13½"	13½"	16¼"	16¼"	16¼"	16¼"	16¼"	16½"	16½"
MAX. RESAW HEIGHT	6¼"	6"	6"	10"	vz12"	12"	12"	12"	12"	16"	16"
MOTOR SIZE	¾ HP	1 HP	1½ HP	2 HP	2 HP	2 HP	2 HP	2 HP	2 HP	5 HP	5 HP
MOTOR VOLTAGE	110V/220V Single-Phase	110V/220V Single-Phase	110V/220V Single-Phase	110V/220V Single-Phase	110V/220V Single-Phase	110V/220V Single-Phase	220V Single-Phase	110V/220V Single-Phase	220V Single-Phase	220V Single-Phase	220V Single-Phase
PREWIRED VOLTAGE	110V	110V	110V	220V	220V	220V	220V	220V	220V	220V	220V
RECOMMENDED CIRCUIT SIZE	15/15 Amp	15/15 Amp	15/15 Amp	20/15 Amp	30/15 Amp	30/15 Amp	15 Amp	20/15 Amp	15 Amp	30 Amp	30 Amp
SWITCH TYPE	ON/OFF Paddle	ON/OFF Push Button	ON/OFF Push Button	ON/OFF Push Button	ON/OFF Push Button	ON/OFF Push Button	Magnetic Switch	Magnetic Switch	Magnetic Switch	Magnetic Switch	Magnetic Switch
BLADE CAPACITY	½"-¾"	½"-¾"	½"-¾"	½"-¾"	½"-1"	½"-1"	½"-1"	½"-1"	½"-1"	½"-1¾"	½"-1¾"
BLADE LENGTH	92½"-93½"	92½"-93½"	92½"-93½"	105¾"-107¼"	131½"	131½"	131½"	131½"	131½"	162"	160"-162"
BLADE SPEED (FPM)	3000	1500, 3200	3000	3000	1700, 3500	1700, 3500	1700, 3500	1700, 3500	1700, 3500	4500	4500
BLADE GUIDES	Guide Blocks	Ball Bearings	Ball Bearings	Ball Bearings	Euro-Style Roller Disc	Double Ball Bearings	Double Ball Bearings	Double Ball Bearings	Double Ball Bearings	Double Ball Bearings	Double Ball Bearings
BLADE RELEASE	Knob	Quick Release	Quick Release	Quick Release	Quick Release	Quick Release	Quick Release	Quick Release	Quick Release	Quick Release	Quick Release
TABLE SIZE	14" D x 14" W	14" D x 14" W	20½" D x 14" W	19¾" D x 14¾" W	17" D x 17" W	23⅝" D x 17¼" W	23⅝" D x 17¼" W	23⅝" D x 17¼" W	23⅝" D x 17¼" W	21" D x 25½" W	21" D x 25½" W
TABLE TYPE	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
GEARED TABLE RACK & PINION TILT	No	No	No	No	No	No	No	No	No	Yes	Yes
TABLE TILT	15° Left 45° Right	15° Left 45° Right	10° Left 45° Right	8° Left 45° Right	10° Left 45° Right	5° Left 45° Right	5° Left 45° Right	5° Left 45° Right	5° Left 45° Right	5° Left 45° Right	5° Left 45° Right
TABLE TRUNNIONS	Aluminum	Aluminum	Cast Iron	Aluminum	Steel	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
FENCE TYPE	Extruded Aluminum	Extruded Aluminum	Cast Iron	Cast Iron	Extruded Aluminum	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Extruded Aluminum	Cast Iron
RESAW FENCE	Not Included	Not Included	Included	Included	Not Included	Included	Included	Included	Included	Included	Included
MITER GAUGE	Included	Included	Included	Included	Included	Included	Included	Included	Included	Included	Included
WHEELS	Balanced Aluminum	Balanced Aluminum	Balanced Cast Iron	Balanced Cast Iron	Balanced Aluminum	Balanced Cast Iron	Balanced Cast Iron	Balanced Cast Iron	Balanced Cast Iron	Balanced Cast Iron	Balanced Cast Iron
DUST PORT(S)	1 x 4"	1 x 4"	1 x 4"	1 x 4"	2 x 4"	2 x 4"	2 x 4"	2 x 4"	2 x 4"	2 x 4"	2 x 4"
FOOT BRAKE	No	No	No	No	No	No	Motor Brake	Yes	Foot Brake w/ Micro Switch	Yes	Motor Brake
FRAME TYPE	Cast Iron	Cast Iron	Cast Iron	Reinforced Steel	Reinforced Steel	Reinforced Steel	Reinforced Steel	Reinforced Steel	Reinforced Steel	Reinforced Steel	Reinforced Steel
FLOOR-TO-TABLE HEIGHT	43⅝"	43⅝"	44"	42¼"	37½"	37½"	37½"	37½"	37½"	35½"	35½"
OVERALL HEIGHT	67¼"	66⅝"	67¼"	73"	73"	73"	73"	73"	73"	78½"	78½"
FOOTPRINT	24" x 22"	24⅝" x 17½"	17¼" x 16"	21½" x 18¼"	27" x 17¾"	27" x 17¾"	27" x 17¾"	27" x 17¾"	27" x 17¾"	29½" x 23½"	29½" x 23½"
MACHINE WEIGHT	154 lbs.	167 lbs.	236 lbs.	251 lbs.	266 lbs.	325 lbs.	352 lbs.	335 lbs.	357 lbs.	620 lbs.	620 lbs.
SHIPPING WEIGHT	165 lbs.	198 lbs.	262 lbs.	284 lbs.	342 lbs.	418 lbs.	446 lbs.	434 lbs.	460 lbs.	784 lbs.	675 lbs.
CSA CERTIFIED	No	Yes	Yes	Yes	No	No	Yes	No	No	No	No
COUNTRY OF ORIGIN	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan
2012 CATALOG PRICING	\$425 ⁰⁰	\$525 ⁰⁰ / \$495 ⁰⁰	\$795 ⁰⁰	\$950 ⁰⁰	\$950 ⁰⁰ / \$895 ⁰⁰	\$1095 ⁰⁰	\$1295 ⁰⁰	\$1195 ⁰⁰	\$1225 ⁰⁰	\$2395 ⁰⁰	\$2695 ⁰⁰

CHECK OUR WEBSITE FOR CURRENT PRICING



BANDSAW COMPARISON CHART

	G0514X	G0514XF	G0514X2	G0514X3	G0514X2B	G0701	G0566B	G0531B	G0568	G0569
BANDSAW SIZE	19"	19"	19"	19"	19"	19"	21"	21"	24"	24"
THROAT CAPACITY (Left of Blade)	18¼"	18¼"	18¼"	18¼"	18¼"	18¾"	20"	20"	24½"	24½"
MAX. RESAW HEIGHT	12"	12"	12"	12"	12"	19½"	14¼"	14¼"	16¼"	16¼"
MOTOR SIZE	3 HP	3 HP	3 HP	3 HP	3 HP	5 HP	3 HP	5 HP	5 HP	7½ HP
MOTOR VOLTAGE	220V Single-Phase	220V Single-Phase	220V Single-Phase	220V/440V 3-Phase	220V Single-Phase	220V Single-Phase	220V Single-Phase	220V Single-Phase	220V Single-Phase	220V/440V 3-Phase
PREWIRED VOLTAGE	220V	220V	220V	220V	220V	220V	220V	220V	220V	220V
RECOMMENDED CIRCUIT SIZE	15 Amp	20 Amp	15 Amp	15/10 Amp	15 Amp	30 Amp	20 Amp	30 Amp	40 Amp	40/20 Amp
SWITCH TYPE	Magnetic Switch	Magnetic Switch	Magnetic Switch	Magnetic Switch	Magnetic Switch	Magnetic Switch	Magnetic Switch	Magnetic Switch	Magnetic Switch	Magnetic Switch
BLADE CAPACITY	½"-1¼"	½"-1¼"	½"-1¼"	½"-1¼"	½"-1¼"	¾"-1¾"	¼"-1¾"	¼"-1¾"	¼"-1½"	¼"-1½"
BLADE LENGTH	143"	143"	143"	143"	143"	166"-168"	165"	165"	180"-181½"	180"-181½"
BLADE SPEED (FPM)	1700, 3500	1700, 3500	1700, 3500	1700, 3500	1700, 3500	4975	4600	4600	5300	5300
BLADE GUIDES	Double Ball Bearings	Double Ball Bearings	Double Ball Bearings	Double Ball Bearings	Double Ball Bearings	Double Ball Bearings	Double Ball Bearings	Double Ball Bearings	Double Ball Bearings	Double Ball Bearings
BLADE RELEASE	Quick Release	Quick Release	Quick Release	Quick Release	Quick Release	Quick Release	Quick Release	Quick Release	Quick Release	Quick Release
TABLE SIZE	26¾" D x 19" W	26¾" D x 19" W	26¾" D x 19" W	26¾" D x 19" W	26¾" D x 19" W	24" D x 28" W	20¾" D x 29½" W	20¾" D x 29½" W	23¾" D x 33½" W	23¾" D x 33½" W
TABLE TYPE	Ground Cast Iron	Ground Cast Iron	Ground Cast Iron	Ground Cast Iron	Ground Cast Iron	Ground Cast Iron	Ground Cast Iron	Ground Cast Iron	Ground Cast Iron	Ground Cast Iron
GEARED TABLE RACK & PINION TILT	No	No	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes
TABLE TILT	5° Left 45° Right	5° Left 45° Right	5° Left 45° Right	5° Left 45° Right	5° Left 45° Right	5° Left 45° Right	5° Left 45° Right	5° Left 45° Right	45° Right	45° Right
TABLE TRUNNIONS	Steel	Steel	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
FENCE TYPE	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
RESAW FENCE	Included	Included	Included	Included	Included	Included	Not Included	Not Included	Not Included	Not Included
MITER GAUGE	Included	Included	Included	Included	Included	Included	Included	Included	Included	Included
WHEELS	Balanced Cast Iron	Balanced Cast Iron	Balanced Cast Iron	Balanced Cast Iron	Balanced Cast Iron	Balanced Cast Iron	Balanced Cast Iron	Balanced Cast Iron	Balanced Cast Iron	Balanced Cast Iron
DUST PORT(S)	2 x 4"	2 x 4"	2 x 4"	2 x 4"	2 x 4"	2 x 4"	2 x 4"	2 x 4"	2 x 4"	2 x 4"
FOOT BRAKE	No	Yes	Yes	Yes	Motor Brake	Yes	Motor Brake	Motor Brake	Yes	Yes
FRAME TYPE	Reinforced Steel	Reinforced Steel	Reinforced Steel	Reinforced Steel	Reinforced Steel	Reinforced Steel	Reinforced Steel	Reinforced Steel	Reinforced Steel	Reinforced Steel
FLOOR-TO-TABLE HEIGHT	37½"	37½"	37½"	37½"	37½"	35¼"	35½"	35½"	34½"	34½"
OVERALL HEIGHT	76"	76"	76"	76"	76"	86½"	78"	78"	83½"	83½"
FOOTPRINT	29½" x 17¾"	29½" x 17¾"	29½" x 17¾"	29½" x 17¾"	29½" x 17¾"	31" x 23½"	21½" x 33½"	21½" x 33½"	41¾" x 23½"	41¾" x 23½"
MACHINE WEIGHT	383 lbs.	390 lbs.	427 lbs.	421 lbs.	427 lbs.	717 lbs.	581 lbs.	594 lbs.	836 lbs.	847 lbs.
SHIPPING WEIGHT	460 lbs.	496 lbs.	480 lbs.	456 lbs.	512 lbs.	810 lbs.	680 lbs.	684 lbs.	951 lbs.	962 lbs.
CSA CERTIFIED	Yes	No	Yes	Yes	Yes	No	No	No	No	No
COUNTRY OF ORIGIN	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan
2012 CATALOG PRICING	\$1495 ⁰⁰	\$1325 ⁰⁰	\$1495 ⁰⁰	\$1450 ⁰⁰	\$1595 ⁰⁰	\$2995 ⁰⁰	\$2095 ⁰⁰	\$2095 ⁰⁰	\$2995 ⁰⁰	\$2995 ⁰⁰

CHECK OUR WEBSITE FOR CURRENT PRICING