

Grizzly[®] Industrial

CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G0700 10" Sliding Table Saw

"A Powerful Slider with a Compact Footprint"



MACHINE HIGHLIGHTS (see Machine Data Sheet for full specifications)

- 5 HP, 220V, single-phase motor.
- Compact 25½" x 27½" foot print.
- Crosscuts up to 34" long with sliding table, or rips up to 34" wide with traditional fence.
- Cuts up to 3⅛" deep at 90° and up to 2¼" deep at 45°.
- Cuts dados up to 1⅜" thick.
- Adjustable scoring blade for tear-out free cuts.
- Miter fence features single lever lock and adjustable flip stop for repeat angle cutting.

The Model G0700 10" Sliding Table Saw is available for \$2,595.00. As with all Grizzly products, the Model G0700 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0700 10" SLIDING TABLESAW WITH SCORING

Product Dimensions:

Weight..... 473 lbs.
 Length/Width/Height..... 47 x 71 x 48 in.
 Foot Print (Length/Width)..... 27-1/2 x 25-1/2 in.

Shipping Dimensions:

Type..... Wood
 Content..... Machine
 Weight..... 572 lbs.
 Length/Width/Height..... 46 x 42 x 44 in.

Electrical:

Power Requirement..... 220V, Single-Phase, 60 Hz
 Minimum Circuit Size..... 30A
 Switch..... Magnetic Switch w/Thermal Overload
 Switch Voltage..... 220V
 Plug Included..... No
 Recommended Plug/Outlet Type..... NEMA L6-30

Motors:

Main

Type..... TEFC Capacitor Start Induction
 Horsepower..... 5 HP
 Voltage..... 220V
 Phase..... Single-Phase
 Amps..... 22A
 Speed..... 3450 RPM
 Cycle..... 60 Hz
 Number Of Speeds..... 1
 Power Transfer V-Belt
 Bearings..... Shielded and Permanently Sealed

Main Specifications:

Operation Information

Main Blade Size..... 10 in.
 Main Arbor Size..... 5/8 in.
 Scoring Blade Size..... 3-1/8 in.
 Scoring Blade Arbor Size..... 22 mm
 Maximum Width of Dado..... 13/16 in.
 Main Blade Tilt..... 0-45 deg.
 Main Blade Speed..... 4000 RPM
 Scoring Blade Tilt..... 0-45 deg.
 Scoring Blade Speed..... 8000 RPM

Cutting Capacities

Max Depth Of Cut At 90D.....	3-1/8 in.
Max Depth Of Cut At 45D.....	2-1/4 in.
Table With Rip Fence Max Cut Width.....	34 in.
Sliding Table With Cross Fence Max Cut Width.....	27-1/2 in.
Sliding Table With Cross Fence Max Cut Length.....	39-3/8 in.
Miter Fence Cut Width At 45D.....	38 in.

Table Information

Table Size Length.....	27 in.
Table Size Width.....	14-3/4 in.
Table Size With Ext Wings Length.....	27 in.
Table Size With Ext Wings Width.....	39-3/4 in.
Sliding Table Length.....	39-3/8 in.
Sliding Table Width.....	12-1/4 in.

Construction Materials

Table Construction.....	Cast Iron
Sliding Table Construction.....	Aluminum
Base Construction.....	Cast Iron
Cabinet Construction.....	Steel
Trunnions Construction.....	Cast Iron
Rollers Construction.....	Steel
Fence Assembly Construction.....	Extruded Aluminum & Cast Iron
Rails Construction.....	Hardened Steel
Guard Construction.....	Plastic
Spindle Bearing Type.....	Lubricated & Permanently Sealed Ball Bearings
Paint.....	Powder Coated

Other Related Information

No Of Dust Ports.....	2
Dust Port Size.....	2-1/2, 4 in.

Other Specifications:

Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	Machine ID Label on Side of Machine
Assembly Time	1 Hour
Sound Rating	80 dB

Features:

- Blade guard with 2-1/2" dust port
- 4" main dust port
- Adjustable scoring blade
- Adjustable riving knife
- Single-lever locking miter fence