



CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

## Introducing the Grizzly Model G0702 12" Disc Sander with Built-In Brake



### **MACHINE HIGHLIGHTS** (see *Machine Data Sheet* for full specifications)

- 1 HP, 110V, 12A, 1725 RPM, single-phase motor.
- Motor brake stops disc within four seconds after power is switched off for added safety.
- Large precision-ground cast iron table tilts from +15° to -45°, and includes X and Y-axis miter slots.
- 12" cast iron disc accepts PSA sanding discs.
- Adjustable miter gauge for angle sanding.
- Steel base easily mounts to workbenches.
- Built-in 2½" dust port allows for dust collection.

The Model G0702 is available for \$395. As with all Grizzly products, the Model G0702 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit [www.grizzly.com](http://www.grizzly.com).



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0702 12" DISC SANDER WITH BRAKE

### Product Dimensions:

Weight..... 103 lbs.  
 Width (side-to-side) x Depth (front-to-back) x Height..... 26-1/2 x 17-1/8 x 16-3/8 in.  
 Footprint (Length x Width)..... 16-1/2 x 16-1/2 in.

### Shipping Dimensions:

Type..... Cardboard  
 Content..... Machine  
 Weight..... 113 lbs.  
 Length x Width x Height..... 26 x 18 x 17 in.

### Electrical:

Power Requirement..... 110V, Single-Phase, 60 Hz  
 Minimum Circuit Size..... 15 Amp  
 Switch..... Keyed Safety Switch  
 Switch Voltage..... 110V  
 Cord Length..... 5 ft.  
 Cord Gauge..... 16 AWG  
 Plug Included..... Yes  
 Recommended Plug/Outlet Type..... NEMA 5-15

### Motors:

#### Main

Type..... TEFC Capacitor Start w/Brake  
 Horsepower..... 1 HP  
 Voltage..... 110V  
 Phase..... Single-Phase  
 Amps..... 12A  
 Speed..... 1725 RPM  
 Cycle..... 60 Hz  
 Power Transfer ..... Direct Drive  
 Bearings..... Sealed and Permanently Lubricated

### Main Specifications:

#### Table Info

Table Width..... 15 in.  
 Table Length..... 15-1/2 in.  
 Table Tilt..... +15 to -45 Degrees  
 Miter Gauge Slot Width..... 5/8 in.  
 Miter Gauge Slot Height..... 3/16 in.  
 Disc Table Length..... 12 in.

#### Disc Info

Sanding Disc Speed..... 1725 RPM

**Construction**

Base..... Steel  
Table..... Cast Iron  
Disc..... Cast Iron  
Miter Gauge..... Plastic/Aluminum

**Features:**

Automatic Internal Motor Braking System  
Table Tilt Range +15 to -45 Deg.  
Accepts 12 In. PSA Discs  
Large Tilting Precision-Ground Cast Iron Table  
X- and Y-Axis Slots  
Steel Base