

Grizzly[®] Industrial

CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G0702 12" Disc Sander with Built-In Brake



MACHINE HIGHLIGHTS (see *Machine Data Sheet* for full specifications)

- 1 HP, 110V, single-phase motor.
- Motor brake stops disc within four seconds after power is switched off for added safety.
- Large precision-ground cast iron table tilts from -15° to $+45^{\circ}$, and includes two-axis miter gauge support.
- 12" cast iron disc accepts pressure sensitive adhesive sanding discs.
- Adjustable miter gauge for angle sanding.
- Steel base easily mounts to workbenches.
- Built-in 2½" OD dust port allows for dust collection.

The Model G0702 12" Disc Sander with Built-In Brake is available for \$395.00. As with all Grizzly products, the Model G0702 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0702 12" DISC SANDER WITH BRAKE

Product Dimensions:

Weight..... 103 lbs.
 Length/Width/Height.....26-1/2 x 17-1/8 x 16-3/8 in.
 Foot Print (Length/Width)..... 16-1/2 x 16-1/2 in.

Shipping Dimensions:

Type..... Cardboard
 Content..... Machine
 Weight..... 113 lbs.
 Length/Width/Height..... 26 x 18 x 17 in.

Electrical:

Power Requirement..... 110V, Single-Phase, 60 Hz
 Minimum Circuit Size..... 15 Amp
 Switch..... Keyed Safety Switch
 Switch Voltage..... 110V
 Cord Length..... 5 ft.
 Cord Gauge..... 16 AWG
 Plug Included..... Yes
 Recommended Plug/Outlet Type..... NEMA 5-15

Motors:

Main

Type..... TEFC Capacitor Start w/Brake
 Horsepower.....1 HP
 Voltage.....110V
 Phase.....Single-Phase
 Amps.....12A
 Speed.....1725 RPM
 Cycle.....60 Hz
 Power Transfer Direct Drive
 Bearings..... Sealed and Permanently Lubricated

Main Specifications:

Table Info

Table Width..... 15 in.
 Table Length..... 15-1/2 in.
 Table Tilt..... -15 to +45 Degrees
 Miter Gauge Slot Width..... 5/8 in.
 Miter Gauge Slot Height..... 3/16 in.
 Disc Table Length..... 12 in.

Disc Info

Sanding Disc Speed.....1725 RPM

Construction

Base Construction.....	Steel
Table Construction.....	Cast Iron
Disc Construction.....	Cast Iron
Miter Gauge Construction.....	Plastic/Aluminum

Features:

- Automatic Internal Motor Braking System
- Table Tilt Range -15 to +45 Deg.
- Accepts 12 In. PSA Discs
- Large Tilting Precision-Ground Cast Iron Table
- X- and Y-Axis Slots
- Steel Base