

# Grizzly<sup>®</sup> Industrial

CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

## Introducing the Grizzly Model G0713 10" Left-Tilting Contractor-Style Table Saw w/Riving Knife



CSA Approved  
to UL987 Standards!

### **MACHINE HIGHLIGHTS** (see *Machine Data Sheet* for full specifications)

- 1 $\frac{3}{4}$  HP, 110V/220V, single-phase motor (prewired 110V) drives the blade at 4200 RPM.
- Precision-ground cast iron table with wings measures 27" x 44" with a rip capacity of 36" right and 12" left.
- Blade tilt features cast iron trunnions.
- Quick release blade guard and riving knife.
- Lower half of blade is encapsulated in a dust shroud for optimum dust collection from the 2 $\frac{1}{2}$ " dust port.

The Model G0713 10" Contractor-Style Table Saw is available for \$850.00. As with all Grizzly products, the Model G0713 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit [www.grizzly.com](http://www.grizzly.com).



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 • To Order Call: (800) 523-4777 • Fax #: (800) 438-5901

## MODEL G0713 10" 1-3/4 HP CONTRACTOR STYLE TABLE SAW WITH RIVING KNIFE

### Product Dimensions:

Weight ..... 292 lbs.  
 Length/Width/Height ..... 66" x 40" x 40 1/2"  
 Foot Print (Length/Width)..... 26 1/4" x 26"

### Shipping Dimensions:

#### Carton #1

Type..... Cardboard  
 Content..... Machine  
 Weight ..... 288 lbs.  
 Length/Width/Height ..... 33" x 31" x 22"

#### Carton #2

Type..... Cardboard  
 Content..... Fence  
 Weight ..... 18 lbs.  
 Length/Width/Height ..... 38" x 17" x 8"

#### Carton #3

Type..... Cardboard  
 Content..... Rail  
 Weight ..... 36 lbs.  
 Length/Width/Height ..... 71" x 4" x 4"

### Electrical:

Power Requirement ..... 110V or 220V, Single-Phase, 60 Hz  
 Switch..... ON/OFF Push Button with Lockout Pin  
 Switch Voltage ..... 110V/220V  
 Recommended Cord Type ..... 14 Gauge, 3 Wire, 300VAC  
 Minimum Circuit Size ..... 15A@110V/15A@220V  
 Recommended Plug Type ..... 6-15 for 220V  
 Included Plug Type ..... 5-15 for 110V

### Motors:

#### Main

Type..... TEFC Capacitor Start Induction  
 Horsepower ..... 1 3/4 HP  
 Voltage ..... 110V/220V  
 Prewired ..... 110V  
 Phase ..... Single  
 Amps ..... 14/7A  
 Speed ..... 3450 RPM  
 Cycle..... 60 Hz  
 Number Of Speeds..... 1  
 Power Transfer..... Belt Drive  
 Bearings ..... Shielded and Permanently Sealed

**Main Specifications:**

**Blade Information**

Maximum Blade Diameter .....	10"
Riving Knife/Spreader Thickness .....	0.09" (2.3mm)
Required Blade Body Thickness .....	0.074"-0.082" (1.9-2.1mm)
Required Blade Kerf Thickness .....	0.114"-0.122" (2.9-3.1mm)
Maximum Diameter of Dado .....	8"
Maximum Width of Dado .....	3/4"
Blade Tilt .....	Left 0-45°
Arbor Size .....	5/8"
Arbor Speed .....	4200 RPM
Arbor Bearings .....	Sealed and Permanently Lubricated
Rim Speed .....	1904 FPM

**Cutting Capacities**

Maximum Depth of Cut at 90 Degrees .....	3 1/8"
Maximum Depth of Cut at 45 Degrees .....	2 1/4"
Maximum Rip to Right of Blade-Standard .....	36"
Maximum Rip to Right of Blade-Optional .....	36"
Maximum Rip to Left of Blade .....	12"

**Table Information**

Floor to Table Height .....	35 3/8"
Table Size Length .....	27"
Table Size Width .....	20"
Table Size Thickness .....	1 1/2"
Table Size with Extension Wings Length .....	27"
Table Size with Extension Wings Width .....	44"
Table Size with Extension Wings Thickness .....	1 1/2"
Distance Front of Table to Center of Blade .....	16"
Distance Front of Table to Blade at Maximum Cut .....	11 1/8"

**Fence Information**

Fence Type .....	Camlock T-Shaped Fence with Aluminum Face
Fence Size Length .....	33 1/4"
Fence Size Width .....	3 1/8"
Fence Size Height .....	2 9/16"
Fence Rail Type .....	Angle Iron/Square Tubing
Fence Rail Length .....	66"
Fence Rail Width .....	2"
Fence Rail Height .....	2"

**Miter Gauge Information**

Miter Gauge Slot Type .....	T-Slot
Miter Gauge Slot Size Width .....	3/4"
Miter Gauge Slot Size Height .....	3/8"

**Construction**

Table Construction .....	Precision Ground Cast Iron
Wings Construction .....	Precision Ground Cast Iron
Trunnions Construction .....	Cast Iron
Base Construction .....	Pre-Formed Steel
Body Assembly Construction .....	Pre-Formed Steel
Fence Assembly Construction .....	Steel with Aluminum Side Plates
Rails Construction .....	Angle Iron
Miter Gauge Construction .....	Cast Iron with Steel Bar
Guard Construction .....	Steel and Clear Plastic

**Other Related Information:**

Paint ..... Powder Coated  
Number of Dust Ports ..... 1  
Dust Port Size ..... 2 1/2"  
Mobile Base ..... G7314Z

**Other Specifications:**

ISO Factory ..... ISO 9001  
Country of Origin ..... Taiwan  
Warranty ..... 1 Year  
Serial Number Location ..... ID Label on Cabinet  
Assembly Time ..... 1 Hour

**Features:**

- Quick Release Riving Knife and Blade Guard Assembly
- Camlock T-Shaped Fence with Aluminum Face
- Extension Rails Available to Rip 36" Wide
- Includes Regular as well as Dado Blade Inserts
- Precision Ground Cast Iron Table with Beveled Edge
- All Machined Cast Iron Internal Structure
- Precision Ground Cast Iron Wings
- Clear Plastic Guard with Steel Splitter
- Inboard and Outboard Arbor Bearings
- Powder Coated Paint