

Grizzly[®] Industrial

CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G0718 Hinge Boring Machine



New!

MACHINE HIGHLIGHTS (see *Machine Data Sheet* for full specifications)

- 1 HP, 110V/220V, 10A/5A, single-phase motor, pre-wired 110V.
- Quickly and precisely produces hinge mounting holes for cabinets using Euro-style hinges.
- Head features depth stop adjustment, lateral adjustment, and swing arm for aligning hinge position.
- Interchangeable boring heads and bits available to accommodate a variety of hinge brands.
- Fence equipped with flip stops, hold-down clamps, extensions, and interchangeable scales.
- Also features manual downfeed handle, see-through guard, and 4" rear dust port.

The Model G0718 is available for \$2,395. As with all Grizzly products, the Model G0718 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

© Grizzly Industrial, Inc. • Customer Service: (800) 523-4777 • Website: www.grizzly.com

MODEL G0718 HINGE BORING MACHINE

Product Dimensions:

Weight 163 lbs.
 Length/Width/Height 32-3/4 x 22-1/2 x 37 in.
 Foot Print (Length/Width)..... 15-1/2 x 22-1/2 in.

Shipping Dimensions:

Type Wood Slat Crate
 Content..... Machine
 Weight..... 211 lbs.
 Length/Width/Height..... 32 x 29 x 34 in.

Electrical:

Power Requirement 110V/220V, Single-Phase, 60 Hz
 Minimum Circuit Size 15 Amp
 Switch..... ON/OFF Switch w/Emergency Stop Paddle & Anti-Start Pin
 Switch Voltage 110V/220V
 Cord Length 9 ft.
 Cord Gauge 14 gauge
 Plug Included Yes
 Included Plug Type 5-15
 Recommended Plug Type for 220V..... 6-15

Motors:

Main

Type..... TEFC
 Horsepower 1 HP
 Voltage 110V/220V
 Prewired 110V
 Phase Single-Phase
 Amps 10/5A
 Speed 3450 RPM
 Cycle..... 60 Hz
 Number Of Speeds..... 1
 Power Transfer..... Direct Drive
 Bearings Shielded and Permanently Sealed

Main Specifications:

Operation Information

Maximum Depth of Stroke..... 4 in.
 Maximum Boring Depth from Edge..... 4 in.

Other Information

Boring Bit Shaft Thread.....10mm
Rear Fence..... 12 in. Right, 12 in. Left
Extension Fence.....28 in.
Back Fence Stop2 Piece
Number of Spindles on Boring Head3 Spindles (2 Left, 1 Right)

Construction

Rail Shaft Construction.....SUJ-2 High Carbon Anti-Friction Steel
Boring Head ConstructionAluminum
Headstock Construction Sheet Metal
Guard.....Clear PVC
Head CarriageAluminum
Motor SeatAluminum
Table..... Laminated MDF
Paint Powder Coated

Other Related Information

Swing Boring Head Tolerance +/- 0.2mm
Number of Dust Ports..... 1
Dust Port Size4 in.

Other Specifications:

Country Of Origin.....Taiwan
Warranty..... 1 Year
Serial Number LocationID Label on Center of the Stand
Customer Cleanup and Assembly Time 30 Minutes

Features:

Swing boring head tolerance +/- 0.2mm
Downfeed stroke scale position indicator
Rear fence scale position indicator
28" extension fence
Manual stroke operation