



CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

## Introducing the Grizzly Model G0719 15" Disc Sander with Stand



### **MACHINE HIGHLIGHTS** (see *Machine Data Sheet* for full specifications)

- 1½ HP, 220V, 12A, 1725 RPM, single-phase motor with internal brake.
- 12" x 20" precision-ground cast iron table tilts from +15° to -45°, and includes two-axis miter gauge support.
- Uses 15" pressure sensitive adhesive (PSA) sanding discs.
- Steel powder coated cabinet serves as a solid sanding platform, and provides extra storage space.
- Features built-in 2½" dust port for dust collection and switch with disabling key.

The Model G0719 is available for \$795. As with all Grizzly products, the Model G0719 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit [www.grizzly.com](http://www.grizzly.com).



# MACHINE DATA SHEET

© Grizzly Industrial, Inc. • Customer Service: (800) 523-4777 • Website: www.grizzly.com

## MODEL G0719 15" DISC SANDER w/STAND

### Product Dimensions:

Weight ..... 201 lbs.  
Length/Width/Height ..... 20-1/2 x 26 x 46 in.  
Foot Print (Length/Width)..... 20-1/2 x 26 in.

### Shipping Dimensions:

#### Carton 1

Type..... Carboard  
Content ..... Machine  
Weight ..... 149 lbs.  
Length/Width/Height ..... 25 x 22 x 20 in.

#### Carton 2

Type..... Carboard  
Content ..... Cabinet Stand  
Weight ..... 72 lbs.  
Length/Width/Height ..... 29 x 23 x 11 in.

### Electrical:

Power Requirement ..... 220V, Single-Phase, 60 Hz  
Switch..... Paddle Switch w/Disabling Key  
Switch Voltage ..... 220V  
Cord Length ..... 6 ft.  
Cord Gauge ..... 14 gauge  
Minimum Circuit Size ..... 15 Amp  
Plug Included ..... Yes  
Included Plug Type ..... NEMA 6-15

### Motors:

#### Main

Type..... TEFC Capacitor Start w/Brake  
Horsepower ..... 1-1/2 HP  
Voltage ..... 220V  
Phase ..... Single  
Amps ..... 12A  
Speed ..... 1725 RPM  
Cycle..... 60 Hz  
Number Of Speeds..... 1  
Power Transfer..... Direct Drive  
Bearings ..... Sealed, Permanently Lubricated

**Main Specifications:**

**Table & Disc Information**

Table Tilt Range .....	+15° to -45°
Sanding Disc Diameter.....	15 in.
Sanding Disc Speed.....	1725 RPM
Disc Table Length .....	20 in.
Disc Table Width .....	12 in.
Disc Table Thickness .....	9/16 in.
Miter Gauge Slot Width.....	3/4 in.
Miter Gauge Slot Height.....	5/16 in.
Floor to Table Height.....	37 in.

**Construction**

Base .....	Steel
Disc.....	Cast Iron
Miter Gauge.....	Aluminum
Cabinet Stand.....	Steel
Table.....	Precision Ground Cast Iron
Paint .....	Powder Coated

**Other**

Number of Dust Ports.....	1
Dust Port Size .....	2-1/2 in.

**Other Specifications:**

Customer Cleaning and Setup Time.....	Approximately 30 Minutes
Sound Rating .....	75 dB
ISO Factory.....	ISO 9001
Warranty.....	1 Year
Country of Origin.....	Taiwan
Serial Number Location .....	ID Label on Cabinet

**Features:**

- Automatic internal motor braking system
- Table tilt range +15° to -45°
- Accepts 15" PSA discs
- Large tilting precision-ground cast iron table
- X and Y-axis miter slots
- Steel base