

Grizzly[®] Industrial

CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G1030Z2 3HP Dust Collector



MADE IN AN
ISO 9001
FACTORY

MACHINE HIGHLIGHTS (see *Machine Data Sheet* for full specifications)

- 3 HP, 220V, single-phase motor.
- Maximum air suction capacity of 2,300 CFM with a maximum static pressure of 16.7".
- Improved 12³/₄" balanced steel impeller with radial fins.
- Features two 2.5 micron upper filtration bags and two 11.4 cu. ft. disposable collection bags.
- 7" main inlet has removable Y-fitting with three 4" openings for capturing dust from multiple machines.
- Powder-coated steel stand with four plastic casters ensures full mobility—weighs 170 lbs.

The Model G1030Z2 is available for \$395.00. As with all Grizzly products, the Model G1030Z2 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G1030Z2 3 HP DUST COLLECTOR WITH NEW IMPELLER

Product Dimensions:

Weight..... 156 lbs.
 Length/Width/Height..... 49-1/2 x 21-1/2 x 78 in.
 Foot Print (Length/Width)..... 49-1/2 x 21-1/2 in.

Shipping Dimensions:

Type..... Cardboard
 Content..... Machine
 Weight..... 170 lbs.
 Length/Width/Height..... 51 x 22 x 23 in.

Electrical:

Minimum Circuit Size..... 30 amp
 Switch..... On/Off Push Button
 Switch Voltage..... 220V
 Cord Length..... 6 ft.
 Cord Gauge..... 14 gauge
 Plug Included..... No

Motors:

Main

Type..... TEFC Capacitor Start Induction
 Horsepower..... 3
 Voltage..... 220V
 Prewired..... 220V
 Phase..... Single
 Amps..... 18
 Speed..... 3450
 Cycle..... 60 Hz
 Number Of Speeds..... 1
 Power Transfer Direct Drive
 Bearings..... Sealed and Lubricated for Life

Main Specifications:

Operation

Air Suction Cap..... 2300 CFM
 Maximum Static Pressure..... 16.7 in.
 Main Inlet Size..... 7 in.
 Manifold Included..... Yes
 Manifold Inlets..... 3
 Manifold Inlet Size..... 4 in.
 Machine Collection Cap..... 3
 Maximum Material Collection Cap..... 11.4 cu. ft.
 Upper Bag Filtration..... 2.5 micron

Bag Information

| | |
|----------------------------|--------------|
| No Of Upper Bags..... | 2 |
| Upper Bag Cap..... | 5.7 cu. ft. |
| Lower Bag Cap..... | 5.7 cu. ft. |
| No Of Lower Bags..... | 2 |
| Upper Bags Total Area..... | 11.4 cu. ft. |
| Lower Bags Total Area..... | 11.4 cu. ft. |
| Upper Bag Diameter..... | 19-1/2 in. |
| Upper Bag Length..... | 33 in. |
| Lower Bag Diameter..... | 19-1/2 in. |
| Lower Bag Length..... | 33 in. |

Impeller Information

| | |
|-------------------------------|------------|
| Impeller Type..... | Radial Fin |
| Impeller Size..... | 12-3/4 in. |
| Impeller Blade Thickness..... | 1/8 in. |

Construction

| | |
|----------------------------|-------------------------------------|
| Upper Bag Material..... | Fabric |
| Lower Bag Material..... | Plastic |
| Base Construction..... | Fabricated Sheet Metal with Casters |
| Frame Construction..... | Formed Steel |
| Caster Construction..... | High Density Plastic |
| Impeller Construction..... | Balanced Steel, Riveted Fins |
| Paint..... | Powder Coated |

Other

| | |
|--------------------------------|--------|
| Height With Bags Inflated..... | 78 in. |
|--------------------------------|--------|

Other Specifications:

| | |
|------------------------------|--|
| ISO Factory | ISO 9001 |
| Country Of Origin | Taiwan |
| Warranty | 1 Year |
| Serial Number Location | Machine Label Above Magnetic On/OFF Switch |
| Awards | Wood Magazine Top Value 1997 |
| Assembly Time | 1 Hour |

Features:

- Fully Mobile
- Powder Coated Paint
- Includes Steel Base with Casters