



CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

## Introducing the Grizzly Model G0438RLX 10" Left-Tilt Contractor Style Table Saw with Riving Knife and Cast Iron Wings



Interchangeable Riving Knife

### **MACHINE HIGHLIGHTS** (see *Machine Data Sheet* for full specifications)

- 2 HP, 115V/230V, single-phase motor (prewired 230V).
- Precision-ground cast iron table with T-slots, beveled edge, rail-mounted switch, and cast iron wings.
- Riving knife and quick-release splitter guard are easily interchangeable.
- Shop Fox® Aluma-Classic Fence lifts off easily.
- Features standard 30" rip capacity or optional 50" rip capacity, and rips stock up to 3" at 90° and 2" at 45°.
- Includes precision-machined cast iron motor pulley for reduced vibration, cast iron trunnions, free 10" carbide tipped blade, plus regular and dado blade table inserts.

The Model G0438RLX 10" is available for \$775.00. As with all Grizzly products, the Model G0438RLX is covered by a one-year warranty. For more information call 1-800-523-4777 or visit [www.grizzly.com](http://www.grizzly.com).



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0438RLX 10" 2 HP 220V CONTRACTOR LEFT-TILT TABLESAW

### Product Dimensions:

Weight..... 300 lbs.  
 Length/Width/Height..... 59-1/2 x 47 x 36 in.  
 Foot Print (Length/Width)..... 31-1/2 x 25-3/4 in.

### Shipping Dimensions:

#### Carton #1

Type..... Cardboard  
 Content..... Machine  
 Weight..... 273 lbs.  
 Length/Width/Height..... 40 x 25 x 21 in.

#### Carton #2

Type..... Cardboard  
 Content..... Fence & Rail  
 Weight..... 55 lbs.  
 Length/Width/Height..... 62 x 17 x 7 in.

### Electrical:

Power Requirement..... 115V/230V, Single-Phase, 60 Hz  
 Minimum Circuit Size..... 30 Amps @ 115V, 15 Amps @ 230V  
 Switch..... Rail-Mounted Star/Stop Push Button  
 Switch Voltage..... 220V  
 Cord Length..... 7-1/2 ft.  
 Cord Gauge..... 12 gauge  
 Plug Included..... No  
 Recommended Plug/Outlet Type..... NEMA 6-15 @ 230V, NEMA L5-30 @ 115V

### Motors:

#### Main

Type..... TEFC Capacitor Start Induction  
 Horsepower..... 2 HP  
 Voltage..... 115V/230V  
 Prewired..... 230V  
 Phase..... Single  
 Amps..... 18/9A  
 Speed..... 3450 RPM  
 Cycle..... 60 Hz  
 Number Of Speeds..... 1

**Main Specifications:**

**Blade Information**

Maximum Blade Diameter.....	10 in.
Maximum Width Of Dado.....	13/16 in.
Blade Tilt.....	Left 0-45 deg.
Arbor Size.....	5/8 in.
Arbor Speed.....	4200 RPM
Arbor Bearings.....	Sealed and Permanently Lubricated
Rim Speed.....	10,990 FPM

**Cutting Capacities**

Maximum Depth Of Cut At 90 Degrees.....	3 in.
Maximum Depth Of Cut At 45 Degrees.....	2 in.
Maximum Rip To Right Of Blade-Standard.....	30 in.
Maximum Rip To Right Of Blade-Optional.....	50 in. (Model H5744)
Maximum Rip To Left Of Blade.....	8 in.

**Table Information**

Floor To Table Height.....	36 in.
Table Size Length.....	44-1/8 in.
Table Size Width.....	27 in.
Table Size Thickness.....	1-1/2 in.
Distance Front Of Table To Center Of Blade.....	14-11/16 in.
Distance Front Of Table to Blade At Maximum Cut.....	10 in.

**Fence Information**

Fence Type.....	SHOP FOX® AlumaClassic™
Fence Size Length.....	41 in. (w/o Handle)
Fence Size Width.....	3-15/16 in.
Fence Size Height.....	2-7/16 in.
Fence Rail Type.....	Angle Iron Square Tubing
Fence Rail Length.....	57-1/4 in.
Fence Rail Width.....	2-3/8 in.
Fence Rail Height.....	1-9/16 in.

**Miter Gauge Information**

Miter Gauge Slot Type.....	T-Slot
Miter Gauge Slot Size Width.....	3/4 in.
Miter Gauge Slot Size Height.....	3/8 in.

**Construction**

Table Construction.....	Precision-Ground Cast Iron
Wings Construction.....	Precision-Ground Cast Iron
Cabinet Construction.....	Steel
Trunnions Construction.....	Cast Iron
Body Assembly Construction.....	Cast Iron
Fence Assembly Construction.....	Steel Tube and Aluminum Side Plates
Rails Construction.....	Steel
Miter Gauge Construction.....	Cast Iron with Steel Bar
Guard Construction.....	Steel and Clear Plastic

**Other Related Information**

Paint.....	Powder Coated
Number Of Dust Ports.....	1
Dust Port Size.....	4 in.
Long Rails.....	H5744
Mobile Base.....	Use G7315Z

**Other Specifications:**

ISO Factory ..... Yes, ISO 9001  
Country Of Origin ..... Taiwan  
Warranty ..... 1 Year  
Serial Number Location ..... ID Label on Center of the Stand  
Assembly Time ..... 2 Hours

**Features:**

- Quick release splitter guard
- Riving knife
- Aluma-Classic fence
- Extension rails available to rip 50 in. wide
- Includes regular as well as dado blade table inserts
- Precision-ground cast-iron table with beveled edge
- Precision-machined cast-iron motor pulley for reduced vibration
- All machined cast iron internal structure
- Inboard and outboard arbor bearings
- Powder coated paint