



CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G0477 15" Planer/Moulder



MACHINE HIGHLIGHTS (see *Machine Data Sheet* for full specifications)

- Powerful 2½ HP, 110V motor and high-speed cutterhead (5,500 RPM!) make quick and convenient work of any planing or moulding job.
- Preset depth stop, depth of cut gauge and extension tables make for quick and efficient work.
- Easy knife changes and an extensive line of moulding knives mean this machine is ready for anything!
- Designed with portability in mind – lightweight, yet rugged.
- A sturdy stand and built-in dust collection make this perfect for any shop or work site.

The Model G0477 15" Planer/Moulder is available for \$795.00. As with all Grizzly products, the Model G0477 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0477 15" PLANER / MOULDER

Product Dimensions:

Weight..... 168 lbs.
 Length/Width/Height..... 41 x 31 x 57-3/4 in.
 Foot Print (Length/Width)..... 31 x 25-1/3 in.

Shipping Dimensions:

Type..... Cardboard
 Content..... Machine
 Weight..... 181 lbs.
 Length/Width/Height..... 23 x 36 x 27 in.

Electrical:

Minimum Circuit Size..... 15 amp
 Switch..... Toggle On/Off with Safety Lock Tab
 Switch Voltage..... 110V
 Cord Length..... 7 ft.
 Cord Gauge..... 14 gauge
 Plug Included..... Yes

Motors:

Main

Type..... Carbon Brushes
 Horsepower..... 2-1/2 HP
 Voltage..... 110V
 Prewired..... 110V
 Phase..... Single
 Amps..... 12A
 Speed..... 16500 RPM
 Cycle..... 60 Hz
 Number Of Speeds..... 1
 Power Transfer V-Belt Drive
 Bearings..... Shielded and Lubricated

Main Specifications:

Operation Info

Max. Cut Width..... 15 in.
 Max. Cut Height..... 6 in.
 Min. Stock Length..... 17 in.
 Min. Stock Thickness..... 1/8 in.
 Max. Stock Thickness..... 6 in.
 No. Of Cuts Per Inch..... 42, 83
 No. Of Cuts Per Minute..... 11000
 Cutterhead Speed..... 5500 RPM
 Planing Feed Rate..... 11, 22 FPM
 Moulding Feed Rate..... 11 FPM
 Max. Cut Depth Planing Full Width..... 1/16 in.
 Max. Cut Depth Planing 6 Inch Wide Board..... 3/32 in.
 Max. Profile Depth Moulding..... 7/8 in.
 Max. Profile Width Moulding..... 4-9/16 in.

Cutterhead Info

Cutterhead Type.....	2 Knife
Cutterhead Dia.....	3-15/64 in.
No. Of Knives.....	2
Knife Type.....	Reversible
Knife Size Length.....	15-1/2 in.
Knife Size Width.....	5/8 in.
Knife Size Thickness.....	5/64 in.
Knife Adjustment.....	Bottom out on 2 Locating Collars

Table Info

Table Movement.....	6 in.
Table Bed Size Length.....	16 in.
Table Bed Size Width.....	15 in.
Table Bed Size Thickness.....	11/32 in.
Floor To Table Height.....	34 in.
Roller Ext Table Size Length.....	15 in.
Roller Ext Table Size Width.....	11-1/3 in.

Construction

Table Construction.....	Stainless Steel
Body Construction.....	Cast Aluminum
Stand Construction.....	Sheet Metal
Cutterhead Assembly Construction.....	Steel
Infeed Roller Construction.....	Rubber
Outfeed Roller Construction.....	Rubber
Paint.....	Powder Coated

Other

Measurement Scale.....	Inch and Metric
No. Of Dust Ports.....	1
Dust Port Size.....	2-1/2 in.
Mobile Base.....	G7315Z

Other Specifications:

Country Of Origin	China
Warranty	1 Year
Serial Number Location	Data Label on Left Housing
Assembly Time	1 hour

Features:

- Built-in Dust Collection
- Extra Large Return Rollers
- Large Top Mounted Hand Crank
- Four Heavy Duty Support Columns
- Anti-kickback Fingers Prevent Board from Backing Up
- Powered Height Adjustment
- Preset Thickness Stops at 1/8", 1/4", 1/2", 3/4", 1" & 1-1/4"