



CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G0566B 21" 3HP Heavy-Duty Bandsaw with Magnetic Motor Brake



Shown with optional
T10131 Extension Table

MACHINE HIGHLIGHTS (see *Machine Data Sheet* for full specifications)

- 3 HP, 220V, Single-Phase Motor.
- Built-in magnetic motor brake stops blade in less than 3 seconds!
- Optional Model T10131 extension table with support accommodates extra-long workpieces.
- Computer balanced cast iron wheels with Grizzly bear head cut-outs and lower wheel brush.
- Heavy-duty cast iron fence with removable 6" resaw fence attachment.
- Large 29½" x 20¾" precision ground cast iron table.
- Geared table tilting mechanism with positive lock for extra table stability.

The Model G0566B is available for \$1,895.00. The T10131 is available for \$249.95. As with all Grizzly products, the Model G0566B is covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0566B 21" SUPER HEAVY-DUTY 3 HP BANDSAW WITH MOTOR BRAKE

Product Dimensions:

Weight..... 581 lbs.
 Length/Width/Height..... 39-1/2 x 28-5/8 x 78 in.
 Foot Print (Length/Width)..... 21-5/8 x 33-1/2 in.

Shipping Dimensions:

Type..... Wood Slat
 Content..... Machine
 Weight..... 680 lbs.
 Length/Width/Height..... 38 x 30 x 84 in.

Electrical:

Power Requirement..... 220V, Single-Phase, 60 Hz
 Minimum Circuit Size..... 20 amp
 Switch..... Magnetic with Thermal Overload Protection
 Switch Voltage..... 220V
 Cord Gauge..... 14 gauge
 Plug Included..... No
 Recommended Plug/Outlet Type..... 6-20 or L6-20

Motors:

Main

Type..... TEFC Capacitor Start Induction
 Horsepower..... 3 HP
 Voltage..... 220V
 Phase..... Single
 Amps..... 15A
 Speed..... 1725 RPM
 Cycle..... 60 Hz
 Number Of Speeds..... 1
 Power Transfer V-Belt
 Bearings..... Shielded and Permanently Lubricated

Main Specifications:

Operation

Blade Speeds..... 4600 FPM
 Table Tilt..... Left 5, Right 45 deg.

Cutting Capacities

Maximum Cutting Height..... 14-1/4 in.
 Max Capacity Left of Blade..... 20 in.

Blade Information

Standard Blade Length.....	165 in.
Blade Length Range.....	164 - 165-1/2 in.
Blade Width Range.....	1/4 - 1-3/8 in.
Upper Blade Guides.....	Ball Bearing
Lower Blade Guides.....	Ball Bearing

Table Information

Table Length.....	29-1/2 in.
Table Width.....	20-3/4 in.
Table Thickness.....	1-7/8 in.
Floor to Table Height.....	35-1/2 in.

Fence Information

Locks in Front.....	Yes
Locks in Rear.....	No
Adjustable for Blade Lead.....	No

Construction

Table Construction.....	Precision Ground Cast Iron
Rip Fence	Precision Ground Cast Iron
Base Construction.....	Cast Iron
Body Construction.....	Pre-Formed Steel
Upper Wheel.....	Computer Balanced Cast Iron
Lower Wheel.....	Computer Balanced Cast Iron
Tire Material.....	Polyurethane
Wheel Cover	Pre-Formed Steel
Paint.....	Powder Coated

Other Related Information

Wheel Diameter.....	20-3/4 in.
Wheel Width.....	1-1/2 in.
Number of Dust Ports.....	2
Dust Port Size.....	4 in.
Mobile Base.....	G7315Z, G8685Z

Other Specifications:

ISO Factory	ISO 9001
Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	Data Plate on Upper Cover
Assembly Time	15 minutes

Features:

- Quick Change Blade Release/Tensioner
- Blade Tension Indicator
- Micro Adjusting Rack and Pinon Table Tilt
- Height Scale Measurement
- Included Miter Gauge
- Rack and Pinon Upper Guide Adjustment
- Hinged Wheel Covers with Safety Lock
- Motor Stops in Under 3 Seconds After Switch is Turned Off
- Brake is Built-in Magnetic Type 90 VDC