

Grizzly[®] Industrial

CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G0690/G0691 10" Table Saw with Riving Knife



G0690



G0691

MACHINE HIGHLIGHTS (see *Machine Data Sheet* for full specifications)

- 3 HP, 220V, single-phase Leeson motor.
- Quick-release blade guard with independent sides.
- Quick-release riving knife for added kickback safety during "non-through" cuts.
- Available with 30" rip capacity (G0690) or 50" rip capacity (G0691).
- Rock-solid T-fence clamps against 3 sides of rail and has right/left mounting scale window.

The Model G0690 is available for \$1,250.00. The Model G0691 is available for \$1,350.00. As with all Grizzly products, these saws are covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0690 10" 3HP 220V CABINET TABLE SAW WITH RIVING KNIFE

Product Dimensions:

Weight..... 550 lbs.
 Length/Width/Height..... 62 x 41 x 40 in.
 Foot Print (Length/Width)..... 20 x 20 in.

Shipping Dimensions:

Carton #1

Type..... Cardboard/Wood Skids
 Content..... Machine
 Weight..... 460 lbs.
 Length/Width/Height..... 24 x 30 x 43 in.

Carton #2

Type..... Cardboard
 Content..... Fence
 Weight..... 24 lbs.
 Length/Width/Height..... 42 x 17 x 7 in.

Carton #3

Type..... Cardboard
 Content..... Rails
 Weight..... 44 lbs.
 Length/Width/Height..... 66 x 7 x 5 in.

Carton #4

Type..... Cardboard
 Content..... Table Extension
 Weight..... 14 lbs.
 Length/Width/Height..... 29 x 15 x 4 in.

Electrical:

Minimum Circuit Size..... 20A
 Switch..... Magnetic with Thermal Overload Protection
 Switch Voltage..... 220V
 Cord Length..... 6 feet
 Cord Gauge..... 14 gauge
 Plug Included..... No
 Recommended Plug/Outlet Type..... 6-20

Motors:

Main

Type.....	TEFC Capacitor Start Induction
Horsepower.....	3 HP
Voltage.....	220V
Phase.....	Single
Amps.....	12.8A
Speed.....	3450 RPM
Cycle.....	60 Hz
Number Of Speeds.....	1
Power Transfer	Triple V-Belt Drive
Bearings.....	Shielded and Permanently Sealed

Main Specifications:

Blade Information

Maximum Blade Diameter.....	10 in.
Maximum Width Of Dado.....	13/16 in.
Blade Tilt.....	Left 0-45 deg.
Arbor Size.....	5/8 in.
Arbor Speed.....	4300 RPM
Arbor Bearings.....	Sealed and Permanently Lubricated

Cutting Capacities

Maximum Depth Of Cut At 90 Degrees.....	3-1/8 in.
Maximum Depth Of Cut At 45 Degrees.....	2-3/16 in.
Maximum Rip To Right Of Blade-Standard.....	29-1/2 in.
Maximum Rip To Left Of Blade.....	12 in.

Table Information

Floor To Table Height.....	34 in.
Table Size Length.....	20 in.
Table Size Width.....	27 in.
Table Size Thickness.....	1-1/2 in.
Table Size With Extension Wings Length.....	40 in.
Table Size With Extension Wings Width.....	27 in.
Table Size With Extension Wings Thickness.....	1-1/2 in.
Distance Front Of Table To Center Of Blade.....	17-1/4 in.
Distance Front Of Table to Blade At Maximum Cut.....	12-1/4 in.

Fence Information

Fence Type.....	Camlock T-Shaped Fence with HDPE Face
Fence Size Length.....	48 in.
Fence Size Width.....	4-1/8 in.
Fence Size Height.....	2-1/2 in.
Fence Rail Type.....	Square Steel Tubing
Fence Rail Length.....	62 in.
Fence Rail Width.....	2-3/4 in.
Fence Rail Height.....	2 in.

Miter Gauge Information

Miter Gauge Slot Type.....	T-Slot
Miter Gauge Slot Size Width.....	3/4 in.
Miter Gauge Slot Size Height.....	3/8 in.

Construction

Table Construction.....	Precision Ground Cast Iron
Wings Construction.....	Precision Ground Cast Iron
Trunnions Construction.....	Cast Iron
Base Construction.....	Pre-Formed Steel
Body Assembly Construction.....	Pre-Formed Steel
Fence Assembly Construction.....	Steel with HDPE Side Plates
Rails Construction.....	Steel
Miter Gauge Construction.....	Cast Iron with Steel Bar
Guard Construction.....	Steel and Plastic

Other Related Information

Paint.....	Powder Coated
Number Of Dust Ports.....	1
Dust Port Size.....	4 in.

Other Specifications:

ISO Factory	ISO 9001
Country Of Origin	China
Serial Number Location	ID Label on Cabinet
Assembly Time	1 Hour

Features:

- Leeson Motor
- Precision Ground Cast Iron Table
- Cast Iron Trunnions
- 4" Dust Port
- T-Slot Miter Gauge
- Riving Knife and Blade Guard
- Camlock T-Shaped Fence with HDPE Face
- Quick-Release Device for Changing Guard/Riving Knife
- Powder Coated Paint
- Standard and Dado Table Inserts
- Quick Release Riving Knife
- Quick Release Motor Guard
- Quick Release Splitter Assembly
- Easy Glide Fence System
- Knurled Knobs for Adjusting Fence
- Nylon Runners Inside Fence Head Assembly
- T-Square Type Fence System
- Recessed Screw Holding Table Insert



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0691 10" 3HP 220V CABINET TABLE SAW WITH LONG RAILS & RIVING KNIFE

Product Dimensions:

Weight..... 590 lbs.
Length/Width/Height..... 82 x 41 x 40 in.
Foot Print (Length/Width)..... 20 x 20 in.

Shipping Dimensions:

Carton #1

Type..... Cardboard/Wood Skids
Content..... Machine
Weight..... 450 lbs.
Length/Width/Height..... 24 x 30 x 42 in.

Carton #2

Type..... Cardboard
Content..... Fence
Weight..... 26 lbs.
Length/Width/Height..... 42 x 17 x 7 in.

Carton #3

Type..... Cardboard
Content..... Rails
Weight..... 66 lbs.
Length/Width/Height..... 67 x 7 x 5 in.

Carton #4

Type..... Cardboard
Content..... Table Extension
Weight..... 30 lbs.
Length/Width/Height..... 29 x 15 x 4 in.

Electrical:

Minimum Circuit Size..... 20A
Switch..... Magnetic with Thermal Overload Protection
Switch Voltage..... 220V
Cord Length..... 6 ft.
Cord Gauge..... 14 gauge
Plug Included..... No
Recommended Plug/Outlet Type..... 6-20

Motors:

Main

Type.....	TEFC Capacitor Start Induction
Horsepower.....	3 HP
Voltage.....	220V
Phase.....	Single
Amps.....	12.8A
Speed.....	3450 RPM
Cycle.....	60 Hz
Number Of Speeds.....	1
Power Transfer	Triple V-Belt Drive
Bearings.....	Shielded and Permanently Sealed

Main Specifications:

Blade Information

Maximum Blade Diameter.....	10 in.
Maximum Width Of Dado.....	13/16 in.
Blade Tilt.....	Left 0-45 deg.
Arbor Size.....	5/8 in.
Arbor Speed.....	4300 RPM
Arbor Bearings.....	Sealed and Permanently Lubricated

Cutting Capacities

Maximum Depth Of Cut At 90 Degrees.....	3-1/8 in.
Maximum Depth Of Cut At 45 Degrees.....	2-3/16 in.
Maximum Rip To Right Of Blade-Standard.....	50 in.
Maximum Rip To Left Of Blade.....	12 in.

Table Information

Floor To Table Height.....	34 in.
Table Size Length.....	20 in.
Table Size Width.....	27 in.
Table Size Thickness.....	1-1/2 in.
Table Size With Extension Wings Length.....	74-3/4 in.
Distance Front Of Table To Center Of Blade.....	17-1/4 in.
Distance Front Of Table to Blade At Maximum Cut.....	12-1/4 in.
Extension Table Size Length.....	34-3/4 in.

Fence Information

Fence Type.....	Camlock T-Shaped Fence with HDPE Face
Fence Size Length.....	48 in.
Fence Size Width.....	4-1/8 in.
Fence Size Height.....	2-1/2 in.
Fence Rail Type.....	Square Steel Tubing
Fence Rail Length.....	62 in.
Fence Rail Width.....	2-3/4 in.
Fence Rail Height.....	2 in.

Miter Gauge Information

Miter Gauge Slot Type.....	T-Slot
Miter Gauge Slot Size Width.....	3/4 in.
Miter Gauge Slot Size Height.....	3/8 in.

Construction

Table Construction.....	Precision Ground Cast Iron
Wings Construction.....	Precision Ground Cast Iron
Trunnions Construction.....	Cast Iron
Base Construction.....	Pre-Formed Steel
Body Assembly Construction.....	Pre-Formed Steel
Fence Assembly Construction.....	Steel with HDPE Side Plates
Rails Construction.....	Steel
Miter Guage Construction.....	Cast Iron with Steel Bar
Guard Construction.....	Steel and Plastic

Other Related Information

Paint.....	Powder Coated
Number Of Dust Ports.....	1
Dust Port Size.....	4 in.
Mobile Base.....	G7314Z

Other Specifications:

ISO Factory	ISO 9001
Country Of Origin	China
Warranty	1 Year
Serial Number Location	ID Label on Cabinet
Assembly Time	1 Hour

Features:

- Leeson Motor
- Precision Ground Cast Iron Table
- Cast Iron Trunnions
- 4" Dust Port
- T-Slot Miter Gauge
- Riving Knife and Blade Guard
- Camlock T-Shaped Fence with HDPE Face
- Quick-Release Device for Changing Guard/Riving Knife
- Powder Coated Paint
- Standard and Dado Table Inserts
- Quick Release Riving Knife
- Quick Release Motor Guard
- Quick Release Splitter Assembly
- Easy Glide Fence System
- Knurled Knobs for Adjusting Fence
- Nylon Runners Inside Fence Head Assembly
- T-Square Type Fence System
- Recessed Screw Holding Table Insert