



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0513X2B 17" 2 HP EXTREME-SERIES® BANDSAW W/ CAST IRON TRUNNION & BRAKE.

Product Dimensions:

Weight..... 352 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 32 x 32 x 73 in.
Footprint (Length x Width)..... 27 x 17-3/4 in.

Shipping Dimensions:

Type..... Wood Slat Crate
Content..... Machine
Weight..... 446 lbs.
Length x Width x Height..... 31 x 20 x 81 in.

Electrical:

Power Requirement..... 220V, Single-Phase, 60 Hz
Full-Load Current Rating..... 8.7A
Minimum Circuit Size..... 15A
Switch..... Magnetic with Thermal Overload Protection
Switch Voltage..... 220V
Cord Length..... 6 ft.
Plug Included..... Yes
Included Plug Type..... NEMA 6-15

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 2 HP
Voltage..... 220V
Phase..... Single
Amps..... 8.7A
Speed..... 1725 RPM
Cycle..... 60 Hz
Number of Speeds..... 1
Power Transfer Belt Drive
Bearings..... Shielded and Permanently Lubricated

Main Specifications:

Operation

Bandsaw Size..... 17 in.
Blade Speeds..... 1700, 3500 FPM
Table Tilt..... Left 5, Right 45 deg.

Cutting Capacities

Maximum Cutting Height..... 12 in.
Max Capacity Left of Blade..... 16-1/4 in.

Blade Information

Standard Blade Length.....	131-1/2 in.
Blade Width Range.....	1/8-1 in.
Upper Blade Guides.....	Ball Bearing
Lower Blade Guides.....	Ball Bearing

Table Information

Table Length.....	23-5/8 in.
Table Width.....	17-1/4 in.
Table Thickness.....	1-1/2 in.
Floor to Table Height.....	37-1/2 in.

Fence Information

Locks in Front.....	Yes
Locks in Rear.....	No
Adjustable for Blade Lead.....	Yes

Construction

Table.....	Precision Ground Cast Iron
Rip Fence	Cast Iron
Body.....	One Piece Reinforced Steel
Upper Wheel.....	Computer Balanced Cast Iron
Lower Wheel.....	Computer Balanced Cast Iron
Tire.....	Polyurethane
Wheel Cover	Pre-Formed Steel
Paint.....	Powder Coated

Other Related Information

Number of Dust Ports.....	2
Dust Port Size.....	4 in.

Other Specifications:

Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	Table
Customer Assembly & Setup Time	1 Hour

Features:

- Cast Iron Table Trunnion
- Ball Bearing Blade Guides
- Quick Change Blade Release/Tensioner
- Micro-Adjusting Gear Table Tilt
- Rack & Pinion Upper Blade Guide Height Adjustment
- Computer Balanced Cast Iron Wheels with Grizzly Bear Head Cut-Outs
- Blade Tension Indicator
- Height Scale for Upper Blade Guides
- Blade Tracking Window
- Hinged Wheel Covers
- Deluxe Cast Iron Fence with Extruded Aluminum Resaw Fence Attachment
- Included Miter Gauge
- Two 4 in. Dust Ports
- Motor Stops in Under 3 Seconds After Switch is Turned Off
- Included 1/2 in. Blade