



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0529 SPINDLE SANDER

Product Dimensions:

Weight..... 166 lbs.
 Length/Width/Height..... 32 x 18 x 47 in.
 Foot Print (Length/Width)..... 21-1/4 x 16-1/2 in.

Shipping Dimensions:

Type..... Cardboard
 Content..... Machine
 Weight..... 181 lbs.
 Length/Width/Height..... 34 x 30 x 21 in.

Electrical:

Switch..... ON/OFF Toggle with Safety Key
 Switch Voltage..... 110V
 Cord Length..... 6 ft.
 Cord Gauge..... 14 gauge
 Minimum Circuit Size..... 15 amp
 Plug Included..... Yes

Motors:

Main

Type..... TEFC Capacitor Start Induction
 Horsepower..... 1 HP
 Voltage..... 110V
 Prewired..... 110V
 Phase..... Single
 Amps..... 10A
 Speed..... 1725 RPM
 Cycle..... 60 Hz
 Number Of Speeds..... 1
 Power Transfer Direct/Gear Drive
 Bearings..... Sealed and Permanently Lubricated

Main Specifications:

Table Info

Table Width..... 14-1/2 in.
 Table Length..... 14-1/2 in.
 Table Thickness..... 1 in.
 Table Tilt..... 0 - 45 deg.
 Table Opening..... 5 in.
 Table Inserts..... 1-1/8, 1-1/8, 2, 2-1 in.
 Floor To Table Height..... Spindle Table:42, Di in.
 Miter Gauge Slot Width..... 3/4 in.
 Miter Gauge Slot Height..... 3/8 in.
 Disc Table Length..... 17-3/4 in.
 Disc Table Width..... 10 in.
 Disc Table Thickness..... 1 in.

Spindle Info

Spindle Diameters..... 1/4, 5/8, 1-1/2, 2 in.
Spindle Lengths..... 5-1/2 in.
Spindle Speed..... 1725 RPM
Spindle Oscillations..... 60 SPM
Stroke Length..... 1 in.

Disc Info

Sanding Disc Diameter..... 12 in.
Sanding Disc Speed..... 1725 RPM

Construction

Base Construction..... Preformed Steel
Stand Construction..... Preformed Steel
Table Construction..... Precision Ground Cast Iron
Frame Construction..... Cast Iron
Disc Construction..... Computer Balanced Aluminum
Miter Gauge Construction..... Plastic with Steel Bar
Paint..... Powder Coated

Other

No. Of Dust Ports..... 2
Dust Port Size..... 2 in.
Mobile Base..... G7314Z

Other Specifications:

ISO Factory ISO 9001
Country Of Origin Taiwan
Warranty 1 Year
Serial Number Location Front of Stand
Assembly Time 45 minutes

Features:

- Four Spindle Sizes
- Miter Gauge Included
- Includes Formed and Welded Steel Stand
- Both Tables Tilt
- Two Cast Iron Tables
- Safety Paddle Switch with Lock