



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0555 THE ULTIMATE 14" BANDSAW

Product Dimensions:

Weight..... 167 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 28 x 30-1/4 x 66-1/2 in.
Footprint (Length x Width)..... 24-1/2 x 17-1/2 in.

Shipping Dimensions:

Type..... Cardboard
Content..... Machine
Weight..... 198 lbs.
Length x Width x Height..... 44 x 21 x 20 in.

Electrical:

Power Requirement..... 110V/220V, Single-Phase, 60 Hz
Prewired Voltage..... 110V
Minimum Circuit Size..... 15A at 110V, 15A at 220V
Switch..... On/Off Push Button w/Disabling Padlock
Switch Voltage..... 110V/220V
Cord Length..... 6 ft.
Cord Gauge..... 16 Gauge
Plug Included..... Yes
Included Plug Type..... NEMA 5-15 for 110V
Recommended Plug/Outlet Type..... NEMA 6-15 for 220V

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 1 HP
Voltage..... 110V/220V
Prewired..... 110V
Phase..... Single
Amps..... 11A at 110V, 5.5A at 220V
Speed..... 1725 RPM
Cycle..... 60 Hz
Number of Speeds..... 1
Power Transfer Belt Drive
Bearings..... Shielded and Lubricated

Main Specifications:

Operation

Bandsaw Size..... 14 in.
Blade Speeds..... 1500, 3200 FPM
Table Tilt..... Left 15, Right 45 deg.

Cutting Capacities

Maximum Cutting Height..... 6 in.
Max Capacity Left of Blade..... 13-1/2 in.

Blade Information

Standard Blade Length..... 93-1/2 in.
Blade Length Range..... 92-1/2 - 93-1/2 in.
Blade Width Range..... 1/8 - 3/4 in.
Upper Blade Guides..... Ball Bearing
Lower Blade Guides..... Ball Bearing
Guide Post Size..... 0.865 in. (22mm)
Guide Post Type..... Solid Steel

Table Information

Table Length..... 14 in.
Table Width..... 14 in.
Table Thickness..... 1-1/2 in.
Floor to Table Height..... 43-5/16 in.

Fence Information

Locks in Front..... Yes
Locks in Rear..... No
Adjustable for Blade Lead..... Yes

Construction

Table..... Precision Ground Cast Iron
Rip Fence Deluxe Extruded Aluminum
Base..... Pre-Formed Steel
Body..... Cast Iron
Upper Wheel..... Computer Balanced Cast Aluminum
Lower Wheel..... Computer Balanced Cast Aluminum
Tire..... Rubber
Wheel Cover Pre-Formed Steel
Paint..... Powder Coated

Other Related Information

Wheel Diameter..... 13-3/4 in.
Wheel Width..... 1-3/16 in.
Number of Dust Ports..... 1
Dust Port Size..... 4 in.
Mobile Base..... G7314Z

Other Specifications:

ISO 9001 Factory Yes
Country Of Origin Taiwan
Warranty 1 Year
Serial Number Location Name Label on Top Cover
Awards Popular Woodworking Best New Tool 2003
Customer Assembly & Setup Time 1 Hours

Features:

Includes Fence and Miter Gauge
Upper and Lower Ball Bearing Blade Guides
Deluxe Heavy-Duty Stand
Magnifying Window Over Fence Scale
Hinged Wheel Covers
4" Dust Port
6" Riser Block Available
Powder Coated Paint