



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0564 OSCILLATING EDGE SANDER 3 HP

Product Dimensions:

Weight..... 495 lbs.
Length/Width/Height..... 60 x 28 x 49 in.
Foot Print (Length/Width)..... 32 x 19-1/2 in.

Shipping Dimensions:

Type..... Not Available
Content..... Not Available
Weight..... N/A
Length/Width/Height..... N/A x N/A x N/A

Electrical:

Switch..... Magnetic Contactor and Overload Relay
Switch Voltage..... 220V
Cord Length..... 10 ft.
Cord Gauge..... 12 gauge
Minimum Circuit Size..... 20 amp
Plug Included..... No

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 3 HP
Voltage..... 220V
Prewired..... 220V
Phase..... Single
Amps..... 18A
Speed..... 1725 RPM
Cycle..... 60 Hz
Number Of Speeds..... 1
Power Transfer Direct Drive
Bearings..... Shielded and Permanently Lubricated

Main Specifications:

Operation Information

Sanding Belt Speed..... 3150 FPM
Sanding Belt Oscillations..... 3/4 in.
Sanding Belt Length..... 108 in.
Sanding Belt Width..... 6 in.
Sanding Belt Tilt..... 0 - 90 deg.

Table Information

Table Length.....	35-1/2 in.
Table Width.....	12 in.
Table Thickness.....	1-1/2 in.
Table Travel.....	4 in.
Floor To Table Height.....	35-3/4 - 39-3/4 in.
End Table Length.....	11-1/2 in.
End Table Width.....	10 in.
End Table Thickness.....	3/4 in.
End Table Travel.....	10 in.

Platen Information

Platen Type.....	Steel wih Graphite Pad
Platen Length.....	39-3/4 in.
Platen Width.....	6-3/4 in.
Platen Travel.....	0 - 90 deg.

Construction

Table Construction.....	Precision Ground Cast Iron
Frame Construction.....	Sheet Metal
Base Construction.....	Sheet Metal
Drive Roller Construction.....	Aluminum
Idler Roller Construction.....	Rubber
Miter Block Construction.....	Aluminum
Paint.....	Powder Coated

Other Related Information

No Of Dust Ports.....	2
Dust Port Size.....	4 in.
Belt Release.....	Quick Release Lever
Drive Roller Size.....	7 in.
Idler Roller Size.....	3-7/8 in.

Other Specifications:

Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	On the Base
Assembly Time	10 minutes
Sound Rating	90 dB

Features:

- Sanding Surfaces Tilts Vertical and Horizontal
- T-Slot Table and Miter Gauge
- Quick Belt Release Lever
- Graphite Coated Platen
- Oscillating Sanding Surfaces
- Sanding Belt Oscillates at 52 Cycles per Minute
- Includes 3 Sanding Drums: 1 1/2", 2", 3" x 4 1/2"
- Platen Tilts 0 to 90 degrees (5 deg. Scale)