



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0574 RADIUSING SANDER

Product Dimensions:

Weight..... 172 lbs.
Length/Width/Height..... 42-1/2 x 32 x 74 in.
Foot Print (Length/Width)..... 21-3/4 x 14-3/4 in.

Shipping Dimensions:

Carton #1

Type..... Cardboard
Content..... Machine
Weight..... 190 lbs.
Length/Width/Height..... 46 x 45 x 16 in.

Carton #2

Type..... Cardboard
Content..... Attachment
Weight..... 62 lbs.
Length/Width/Height..... 39 x 18 x 11 in.

Electrical:

Switch..... Toggle Safety Switch w/ Safety Lock Tab
Switch Voltage..... 220V
Cord Length..... 10 ft.
Cord Gauge..... 16 gauge
Minimum Circuit Size..... 20 amps at 110V, 15 amps at 220V
Plug Included..... No

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 1-1/2 HP
Voltage..... 110/220V
Prewired..... 220V
Phase..... Single
Amps..... 20/10A
Speed..... 1725 RPM
Cycle..... 60 Hz
Number Of Speeds..... 1
Power Transfer Direct Drive
Bearings..... Shielded and Lubricated

Main Specifications:

Operation Information

Sanding Belt Speed..... 1800 FPM
Sanding Belt Length..... 80 in.
Sanding Belt Width..... 6 in.

Platen Information

Platen Type.....Milled Cast Iron, Graphite Coated
Platen Length..... 29-3/4 in.
Platen Width..... 6-3/4 in.

Construction

Frame Construction..... Welded Steel
Base Construction..... Welded Steel
Drive Roller Construction..... Cast Aluminum
Idler Roller Construction..... Rubber
Paint..... Powder Coated

Other Related Information

No Of Dust Ports..... 1
Dust Port Size..... 4 in.
Belt Release..... Quick Release
Drive Roller Size..... 4-1/4 in.
Idler Roller Size..... 3-1/2 in.
Mobile Base..... G8683Z

Other Specifications:

Country Of OriginTaiwan
Warranty 1 Year
Serial Number Location On the Stand
Assembly Time 30 minutes

Features:

- Quick Belt Release
- Micro Adjustment Knob for Sanding Height
- 30" Maximum Workpiece Length
- 15"-5 1/2" Maximum Workpiece Thickness
- 10"-16" Fretboard Radius