



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0576 10" TABLE SAW 2 HP SINGLE-PHASE 220V LEFT-TILT W/ CAST WINGS

Product Dimensions:

Weight..... 292 lbs.
Length/Width/Height..... 57 x 48-1/2 x 41 in.
Foot Print (Length/Width)..... 25-1/2 x 21 in.

Shipping Dimensions:

Carton #1

Type..... Not Available
Content..... Machine
Weight..... N/A
Length/Width/Height..... N/A x N/A x N/A

Carton #2

Type..... Not Available
Content..... Fence
Weight..... N/A
Length/Width/Height..... N/A x N/A x N/A

Electrical:

Switch..... On/Off Push Button
Switch Voltage..... 110/220V
Cord Length..... 10 ft.
Cord Gauge..... 12 gauge
Minimum Circuit Size..... 25 amps at 110V, 15 amps at 220V
Plug Included..... No

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 2 HP
Voltage..... 110/220V
Prewired..... 220V
Phase..... Single
Amps..... 24/12A
Speed..... 3450 RPM
Cycle..... 60 Hz
Number Of Speeds..... 1
Power Transfer Belt Drive
Bearings..... Shielded and Lubricated

Main Specifications:

Blade Information

Maximum Blade Diameter.....	10 in.
Maximum Width Of Dado.....	13/16 in.
Blade Tilt.....	Left 0-45 deg.
Arbor Size.....	5/8 in.
Arbor Speed.....	4250 RPM
Arbor Bearings.....	Sealed and Permanently Lubricated
Rim Speed.....	11000 FPM

Cutting Capacities

Maximum Depth Of Cut At 90 Degrees.....	3-1/8 in.
Maximum Depth Of Cut At 45 Degrees.....	2-1/8 in.
Maximum Rip To Right Of Blade-Standard.....	30 in.
Maximum Rip To Right Of Blade-Optional.....	50 in.
Maximum Rip To Left Of Blade.....	10-1/2 in.

Table Information

Floor To Table Height.....	35 in.
Table Size Length.....	27 in.
Table Size Width.....	20-1/8 in.
Table Size Thickness.....	1-9/16 in.
Table Size With Extension Wings Length.....	27 in.
Table Size With Extension Wings Width.....	39-5/8 in.
Table Size With Extension Wings Thickness.....	1-9/16 in.
Distance Front Of Table To Center Of Blade.....	16 in.
Distance Front Of Table to Blade At Maximum Cut.....	11 in.

Fence Information

Fence Type.....	SHOP FOX Aluma-Classic
Fence Size Length.....	42-1/2 in.
Fence Size Width.....	3-15/16 in.
Fence Size Height.....	2-7/16 in.
Fence Rail Type.....	Angle Iron/Square Tubing
Fence Rail Length.....	57 in.
Fence Rail Width.....	2 in.
Fence Rail Height.....	2 in.

Miter Gauge Information

Miter Gauge Slot Type.....	T-Slot
Miter Gauge Slot Size Width.....	3/4 in.
Mither Gauge Slot Size Height.....	3/8 in.

Construction

Table Construction.....	Precision Ground Cast Iron
Wings Construction.....	Precision Ground Cast Iron
Trunnions Construction.....	Cast Iron
Base Construction.....	Pre-Formed Steel
Body Assembly Construction.....	Pre-Formed Steel
Fence Assembly Construction.....	Steel with Aluminum Side Plates
Rails Construction.....	Angle Iron
Miter Gauge Construction.....	Cast Iron with Steel Bar
Guard Construction.....	Steel and Clear Plastic

Other Related Information

Paint.....	Powder Coated
Number Of Dust Ports.....	1
Dust Port Size.....	4 in.
Long Rails.....	H5744
Mobile Base.....	G7314Z

Other Specifications:

ISO Factory ISO 9001
Country Of Origin Taiwan
Warranty 1 Year
Serial Number Location Data Label on Front of Cabinet
Assembly Time 1-1/2 hours

Features:

- Aluma-Classic Fence Lifts Off Instantly
- Extension Rails Available to Rip 50" Wide
- Includes Regular as well as Dado Blade Inserts
- Precision Ground Cast Iron Table with Beveled Edge
- Precision Machined Cast Iron Motor Pulley for Reduced Vibration
- All Machined Cast Iron Internal Structure
- Precision Ground Cast Iron Wings
- Clear Plastic Guard with Steel Splitter
- Inboard and Outboard Arbor Bearings
- Powder Coated Paint