



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0606X 12" EXTREME SERIES TABLESAW - 3-PHASE

Product Dimensions:

Weight..... 715 lbs.
Length/Width/Height..... 93 x 91 x 42-1/2 in.
Foot Print (Length/Width)..... 66-1/2 x 58-1/2 in.

Shipping Dimensions:

Carton #1

Type..... Wood Crate
Content..... Machine
Weight..... 598 lbs.
Length/Width/Height..... 41-1/2 x 34 x 42 in.

Carton #2

Type..... Cardboard
Content..... Ext. Table/Legs
Weight..... 140 lbs.
Length/Width/Height..... 44 x 32 x 10-3/4 in.

Carton #3

Type..... Cardboard
Content..... Fence
Weight..... 26 lbs.
Length/Width/Height..... 44-1/2 x 18-1/4 x 8-1/4 in.

Carton #4

Type..... Wood Crate
Content..... Rails
Weight..... 92 lbs.
Length/Width/Height..... 96 x 6 x 8 in.

Electrical:

Power Requirement..... 220V or 440V, 3-Phase, 60Hz
Minimum Circuit Size..... 30A @ 220V; 15A @ 440V
Plug Included..... No
Recommended Plug/Outlet Type..... L15-30 @ 220V; Hardwire w/Locking Switch at 440V
Conversion To 440V..... G440VG0606X
Phase Converter..... G7978

Motors:

Main

Type.....	TEFC Induction
Horsepower.....	7.5 HP
Voltage.....	220V/440V
Prewired.....	220V
Phase.....	3-Phase
Amps.....	19/10A
Speed.....	3450 RPM
Cycle.....	60 Hz
Number Of Speeds.....	1
Power Transfer	Serpentine Belt Drive
Bearings.....	Shielded and Permanently Lubricated

Main Specifications:

Blade Information

Maximum Blade Diameter.....	12 in.
Maximum Width Of Dado.....	3/4 in.
Blade Tilt.....	Left 0-45 deg.
Arbor Size.....	1 in.
Arbor Speed.....	3600 RPM
Arbor Bearings.....	Sealed and Permanently Lubricated

Cutting Capacities

Maximum Depth Of Cut At 90 Degrees.....	4 in.
Maximum Depth Of Cut At 45 Degrees.....	2-3/4 in.
Maximum Rip To Right Of Blade-Standard.....	52 in.
Maximum Rip To Left Of Blade.....	12 in.

Table Information

Floor To Table Height.....	35-3/4 in.
Table Size Length.....	30-3/4 in.
Table Size Width.....	24-1/2 in.
Table Size Thickness.....	2 in.
Table Size With Extension Wings Length.....	78 in.
Table Size With Extension Wings Width.....	69-1/2 in.
Table Size With Extension Wings Thickness.....	3/4 in.
Distance Front Of Table To Center Of Blade.....	17-1/4 in.
Distance Front Of Table to Blade At Maximum Cut.....	13-1/2 in.

Fence Information

Fence Type.....	T-Shape, Front Locking, Extruded Aluminum Body
Fence Size Length.....	40-1/4 in.
Fence Size Width.....	4-1/8 in.
Fence Size Height.....	2-1/2 in.
Fence Rail Type.....	T-Shape
Fence Rail Length.....	40-1/4 in.
Fence Rail Width.....	5/8 in.
Fence Rail Height.....	2-1/2 in.

Miter Gauge Information

Miter Gauge Slot Type.....	T-Slot
Miter Gauge Slot Size Width.....	3/4 in.
Mither Gauge Slot Size Height.....	3/8 in.

Construction

Table Construction.....	Cast Iron
Wings Construction.....	Cast Iron
Cabinet Construction.....	Pre-Formed Steel
Trunnions Construction.....	Cast Iron
Base Construction.....	Pre-Formed Steel
Body Assembly Construction.....	Pre-Formed Steel
Fence Assembly Construction.....	T-Shape, Front Locking, Aluminum Extruded Body
Rails Construction.....	Steel
Miter Guage Construction.....	Aluminum Body with Steel Bar
Guard Construction.....	Aluminum

Other Related Information

Paint.....	Powder Coated
Number Of Dust Ports.....	1
Dust Port Size.....	4 in.

Features:

- Included Outfeed & Extension Tables with Storage Shelves
- Digital Tilt Guage
- Quick Release Riving Knife
- Quick Release Blade Guard
- Hinged Motor Cover
- 4" Dust Port
- Included 12" Blade