



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0630 80" X 20" DOWNDRAFT TABLE

### Product Dimensions:

Weight..... 304 lbs.  
Length/Width/Height..... 80 x 20 x 38 in.  
Foot Print (Length/Width)..... 81 x 22 in.

### Shipping Dimensions:

Type..... Skeleton Crate  
Content..... Machine  
Weight..... 404 lbs.  
Length/Width/Height..... 86 x 26 x 31 in.

### Electrical:

Switch..... Sealed Rocker  
Switch Voltage..... 110V  
Cord Length..... 10 ft.  
Cord Gauge..... 16 gauge  
Minimum Circuit Size..... 20 amp  
Plug Included..... Yes

### Motors:

#### Main #2

Type..... ODP Capacitor Running Induction  
Horsepower..... 1/2 HP  
Voltage..... 110V  
Prewired..... 110V  
Phase..... Single  
Amps..... 7A  
Speed..... 1175 RPM  
Cycle..... 60 Hz  
Number Of Speeds..... 1  
Power Transfer ..... Direct Drive  
Bearings..... Shielded and Lubricated

#### Main #1

Type..... ODP Capacitor Running Induction  
Horsepower..... 1/2 HP  
Voltage..... 110V  
Prewired..... 110V  
Phase..... Single  
Amps..... 7A  
Speed..... 1175 RPM  
Cycle..... 60 Hz  
Number Of Speeds..... 1  
Power Transfer ..... Direct Drive  
Bearings..... Shielded and Lubricated

**Main Specifications:**

**Operation Info**

Air Suction Cap.....	1300 CFM
Filter Micron.....	1
Filter Efficiency.....	96 Percent
Impeller Type.....	Squirrel Cage
Impeller Size.....	9-1/2 in.
Impeller Blade Thickness.....	0.030 in.

**Filter Info**

No. Of Filters.....	1
Filter Length.....	24 in.
Filter Width.....	12 in.
Filter Thickness.....	12 in.

**Table Info**

Table Size Length.....	80 in.
Table Size Width.....	20 in.
Floor To Table Height.....	38 in.

**Construction Info**

Frame Const.....	Pre-Formed Steel
Base Const.....	Pre-Formed Steel
Impeller Const.....	Zinc Plated Steel
Table Const.....	Pre-Formed Steel
Side Wall Const.....	Steel
Filter Const.....	Woven Fabric and Aluminum
Paint.....	Powder Coated

**Other Specifications:**

Country Of Origin .....	Taiwan
Warranty .....	1 Year
Serial Number Location .....	Machine ID Label
Assembly Time .....	15 minutes
Sound Rating .....	66 - 68 dB

**Features:**

- Non-marring Slip Resistant Table Top
- Convenient Access Filter Bay