



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 • To Order Call: (800) 523-4777 • Fax #: (800) 438-5901

MODEL G0633 JOINTER/PLANER COMBINATION MACHINE

Product Dimensions:

Weight672 lbs.
Length/Width/Height 41-1/4 x 59-5/8 x 45 in.
Foot Print (Length/Width)..... 19-1/2 x 26 in.

Shipping Dimensions:

Type Wood Crate
Content..... Machine
Weight.....767 lbs.
Length/Width/Height..... 34-1/4 x 62-1/2 x 44-3/8 in.

Electrical:

Switch..... Magnetic with Thermal Overload Protection
Switch Voltage 220V
Cord Length 10 ft.
Cord Gauge 12 gauge
Recommended Breaker Size 30 amp
Plug No

Motors:

Main

Type TEFC Capacitor Start Induction
Horsepower..... 5 HP
Voltage..... 220V
Phase..... Single
Amps 25A
Speed..... 3450 RPM
Cycle 60 Hz
Number Of Speeds 1
Power Transfer Twin V-Belts
Bearings Shielded and Lubricated

Main Specifications:

Fence Information

Fence Length 39-3/8 in.
Fence Height..... 5-7/8 in.
Fence Stops..... 45 and 90 deg.

Cutting Capacities (Jointer)

Bevel Jointing 0-45 deg.
Maximum Width of Cut 12 in.
Maximum Depth of Cut 1/8 in.
Number of Cuts Per Minute 15,102
Minimum Stock Length 5-5/8 in.

Cutting Capacities (Planer)

| | |
|-------------------------------------------------|----------|
| Maximum Width of Cut | 12 in. |
| Maximum Depth of Cut Planing Full Width..... | 1/8 in. |
| Maximum Depth of Cut Planing 6" Wide Board..... | 5/32 in. |
| Number of Cuts Per Minute | 15,102 |
| Number of Cuts Per Inch | 57 |
| Feed Speeds..... | 22 FPM |
| Minimum Stock Length | 12 in. |
| Maximum Stock Thickness | 8 in. |

Knife Information (Jointer)

| | |
|------------------------|-------------------------|
| Number of Knives | 3 |
| Knife Type..... | HSS |
| Knife Length..... | 12 in. |
| Knife Width..... | 1 in. |
| Knife Thickness..... | 1/8 in. |
| Knife Adjustment..... | Springs and Jack Screws |

Cutterhead Information

| | |
|--------------------------|--------------|
| Cutterhead Type | 3 HSS Knives |
| Cutterhead Diameter..... | 3-1/8 in. |
| Cutterhead Speed..... | 5034 RPM |

Table Information (Jointer)

| | |
|----------------------------|------------|
| Table Length..... | 59-1/2 in. |
| Table Width..... | 14 in. |
| Floor To Table Height..... | 35-1/2 in. |

Table Information (Planer)

| | |
|----------------------------|------------|
| Table Length..... | 23-1/8 in. |
| Table Width..... | 12-1/4 in. |
| Table Thickness..... | 1-5/8 in. |
| Floor To Table Height..... | 32-1/2 in. |

Construction

| | |
|----------------------------------------|-------------------------|
| Body Assembly Construction..... | Cast Iron |
| Cutterhead Assembly Construction | Steel |
| Infeed Roller Construction | Steel |
| Outfeed Roller Construction..... | Steel |
| Stand Construction | Heavy Gauge Sheet Metal |
| Table Construction..... | Cast Iron |
| Paint..... | Powder Coated |

Other Information

| | |
|----------------------------------|-------------|
| Dust Port Size..... | 4 in. |
| Number of Dust Ports | 2 |
| Measurement Scale (Jointer)..... | Inch |
| Measurement Scale (Planer) | Inch/Metric |

Other Specifications:

| | |
|------------------------------|--------------------------------|
| Country Of Origin | Taiwan |
| Warranty..... | 1 Year |
| Serial Number Location | ID Label on Front of the Stand |

Features:

- Quick Release Fence
- Flip Up Tables and Change Lever Simplify Jointer-Planer Conversion
- Jointer Tables Lock Into Raised Position for Planer Operation; Hand Knobs Release Tables
- Cast Iron Infeed and Outfeed Tables