



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0636XB 17" 5 HP 220V EXTREME-SERIES® BANDSAW WITH BRAKE

### Product Dimensions:

Weight..... 620 lbs.  
Width (side-to-side) x Depth (front-to-back) x Height..... 35-1/4 x 33-3/4 x 78-1/2 in.  
Footprint (Length x Width)..... 29-1/2 x 23-1/2 in.

### Shipping Dimensions:

Type..... Wood Slat Crate  
Content..... Machine  
Weight..... 675 lbs.  
Length x Width x Height..... 37 x 28 x 88 in.

### Electrical:

Minimum Circuit Size..... 30 amp  
Switch..... Magnetic w/Thermal Overload Protection  
Switch Voltage..... 220V  
Plug Included..... No  
Recommended Plug/Outlet Type..... L6-30

### Motors:

#### Main

Type..... TEFC Capacitor Start Induction  
Horsepower..... 5 HP  
Voltage..... 220V  
Phase..... Single  
Amps..... 22A  
Speed..... 1725 RPM  
Cycle..... 60 Hz  
Number of Speeds..... 1  
Power Transfer ..... Belt Drive  
Bearings..... Shielded and Permanently Lubricated

### Main Specifications:

#### Operation

Bandsaw Size..... 17 in.  
Blade Speeds..... 4500 FPM  
Table Tilt..... Left 5, Right 45 deg.

#### Cutting Capacities

Maximum Cutting Height..... 16 in.  
Max Capacity Left of Blade..... 16-1/2 in.

#### Blade Information

Blade Length Range..... 160-162 in.  
Blade Width Range..... 1/8 - 1-3/8 in.  
Upper Blade Guides..... Ball Bearing  
Lower Blade Guides..... Ball Bearing

**Table Information**

Table Length.....	21 in.
Table Width.....	25-1/2 in.
Table Thickness.....	2 in.
Floor to Table Height.....	35-1/2 in.

**Fence Information**

Locks in Front.....	Yes
Locks in Rear.....	No
Adjustable for Blade Lead.....	Yes

**Construction**

Table.....	Precision Ground Cast Iron
Rip Fence .....	Cast Iron
Body.....	One Piece Reinforced Steel
Upper Wheel.....	Computer Balanced Cast Iron
Lower Wheel.....	Computer Balanced Cast Iron
Tire.....	Rubber
Wheel Cover .....	Pre-Formed Steel
Paint.....	Powder Coated

**Other Related Information**

Number of Dust Ports.....	2
Dust Port Size.....	4 in.

**Other Specifications:**

Country Of Origin .....	Taiwan
Warranty .....	1 Year
Serial Number Location .....	ID Label on Upper Wheel Cover
Customer Assembly & Setup Time .....	1 Hour

**Features:**

- Cast Iron Table Trunnion
- Ball Bearing Blade Guides
- Quick Change Blade Release/Tensioner
- Micro-Adjusting Rack & Pinion Table Tilt
- Computer Balanced Cast Iron Wheels with Grizzly Bear Head Cut-Outs
- Blade Tension Indicator
- Height Scale for Upper Blade Guides
- Blade Tracking Window
- Hinged Wheel Covers with Safety Lock
- Deluxe Cast Iron Fence with Extruded Aluminum Resaw Fence Attachment
- Included Miter Gauge
- Included 1 in. Blade
- Two 4 in. Dust Ports
- Motor Stops in Under 3 Seconds After Switch is Turned Off
- Optional Extension Table with Support