



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0641 DOUBLE CUT-OFF MITER SAW

Product Dimensions:

Weight..... 1012 lbs.
Length/Width/Height..... 112-1/2 x 28-3/8 x 57-1/2 in.
Foot Print (Length/Width)..... 112-1/2 x 28-3/8 in.

Shipping Dimensions:

Type..... Not Available
Content..... Machine
Weight..... 1210 lbs.
Length/Width/Height..... 57 x 31 x 65 in.

Electrical:

Switch..... Magnetic with Thermal Overload Protection
Cord Length..... 98 in.
Cord Gauge..... 12 AWG
Minimum Circuit Size..... 30A

Motors:

Main

Type..... TEFC
Horsepower..... 2
Voltage..... 220
Phase..... Single
Amps..... 10
Speed..... 1725
Cycle..... 60
Bearings..... Shielded and Lubricated Ball Bearings

Main Specifications:

Operation Information

Main Blade Size..... 12 in.
Main Arbor Size..... 1 in.

Cutting Capacities

Max Cut Thickness..... 2-3/4 in.
Max Cut Cap Width..... 2-3/4 in.
Max Cut Length..... 61 in.

Table Information

Floor To Table Height..... 33-7/8 in.
Table Size Length..... 32-5/8 in.
Table Size Width..... 4 in.
Table Size With Ext Wings Length..... 112-1/2 in.

Construction Materials

| | |
|---------------------------|---------------------------------------|
| Table Construction..... | Sheet Metal |
| Base Construction..... | Sheet Metal |
| Guard Construction..... | Plastic |
| Spindle Bearing Type..... | Shielded and Lubricated Ball Bearings |
| Paint..... | Powder Coat |

Other Related Information

| | |
|-----------------------|-------|
| No Of Dust Ports..... | 1 |
| Dust Port Size..... | 4 in. |

Features:

- Creates Two Mitered Workpieces in One Cut for a Perfect 90 Degree Joint
- Foot Pedal Operated and Pneumatically Controlled
- Included Workpiece Support Stands with Stop Block System
- Adjustable Stroke Speed for Tear-Out Free Cuts
- Blade Swing Arm is Micro-Adjustable for Perfect Angles