



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0656 8" X 72" JOINTER WITH MOBILE BASE

Product Dimensions:

Weight..... 465 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 72-1/2 x 26 x 47-1/4 in.
Footprint (Length x Width)..... 26-3/4 x 16-1/2 in.

Shipping Dimensions:

Carton #1

Type..... Wood Crate
Content..... Machine
Weight..... 390 lbs.
Length x Width x Height..... 25 x 80-3/4 x 14-1/2 in.

Carton #2

Type..... Cardboard
Content..... Stand
Weight..... 132 lbs.
Length x Width x Height..... 18-3/4 x 29-1/4 x 26-5/8 in.

Electrical:

Power Requirement..... 220V, Single Phase, 60 Hz
Minimum Circuit Size..... 20 Amp
Switch..... ON/OFF Push Button with Large OFF Paddle
Switch Voltage..... 220V
Cord Length..... 6 ft.
Cord Gauge..... 14 guage
Plug Included..... No
Recommended Plug/Outlet Type..... NEMA 6-20

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 3 HP
Voltage..... 220V
Phase..... Single
Amps..... 15A
Speed..... 3450 RPM
Cycle..... 60 Hz
Number of Speeds..... 1
Power Transfer V-Belt Drive
Bearings..... Shielded and Lubricated

Main Specifications:

Cutting Capacities

Bevel Jointing..... Left & Right 45 deg.
Maximum Width of Cut..... 8 in.
Maximum Depth of Cut..... 1/8 in.
Maximum Rabbeting Depth..... 1/2 in.
Number of Cuts Per Minute..... 20000

Fence Information

Fence Length..... 35 in.
Fence Width..... 1-1/4 in.
Fence Height..... 5 in.
Fence Stops..... 45, 90 and 135 deg.

Cutterhead Information

Cutterhead Type..... 4 Knife
Cutterhead Diameter..... 3 in.
Cutterhead Speed..... 5000 RPM

Knife Information

Number of Knives..... 4
Knife Type..... HSS
Knife Length..... 8 in.
Knife Width..... 3/4 in.
Knife Thickness..... 1/8 in.
Knife Adjustment..... Jack Screws

Table Information

Table Length..... 72-1/2 in.
Table Width..... 9 in.
Floor to Table Height..... 33-1/2 in.
Table Adjustment Type..... Handwheel
Table Movement Type..... Dovetailed Ways

Construction

Base..... Cast Iron
Body Assembly..... Cast Iron
Cabinet..... One-Piece Steel Cabinet
Fence Assembly..... Cast Iron
Guard..... Die Cast Metal
Table..... Precision Ground Cast Iron
Paint..... Powder Coated

Other Information

Number of Dust Ports..... 1
Dust Port Size..... 4 in.

Other Specifications:

Country Of Origin China
Warranty 1 Year
Serial Number Location ID Label on Left Side of Stand
Customer Assembly & Setup Time 1 hour

Features:

- Built-In Easy-to-Use Mobile Base
- Included Push Blocks
- Top Mount Switch Controls
- Handwheel Controlled Fence Adjustment
- Rabbeting Table
- Super Long 72-1/2" Bed