



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0661 10" 2 HP CONTRACTOR STYLE TABLE SAW WITH RIVING KNIFE

### Product Dimensions:

Weight..... 292 lbs.  
Length/Width/Height..... 66 x 40 x 40-1/2 in.  
Foot Print (Length/Width)..... 26-1/4 x 26 in.

### Shipping Dimensions:

#### Carton #1

Type..... Cardboard  
Content..... Machine  
Weight..... 288 lbs.  
Length/Width/Height..... 33 x 31 x 22 in.

#### Carton #2

Type..... Cardboard  
Content..... Fence  
Weight..... 18 lbs.  
Length/Width/Height..... 38 x 17 x 8 in.

#### Carton #3

Type..... Cardboard  
Content..... Rails  
Weight..... 36 lbs.  
Length/Width/Height..... 71 x 4 x 4 in.

### Electrical:

Switch..... ON/OFF Push Button with Lockout Pin  
Switch Voltage..... 110/220V  
Cord Length..... 10 ft.  
Cord Gauge..... 12 guage  
Minimum Circuit Size..... 20A@110V; 15A@220V  
Plug Included..... Yes  
Recommended Plug/Outlet Type..... L5-30@110V; 6-15@220V

### Motors:

#### Main

Type..... TEFC Capacitor Start Induction  
Horsepower..... 2 HP  
Voltage..... 110/220V  
Prewired..... 110V  
Phase..... Single  
Amps..... 20/10A  
Speed..... 3450 RPM  
Cycle..... 60 Hz  
Number Of Speeds..... 1  
Power Transfer ..... Belt Drive  
Bearings..... Shielded and Permanently Sealed

**Main Specifications:**

**Blade Information**

Maximum Blade Diameter.....	10 in.
Maximum Width Of Dado.....	3/4 in.
Blade Tilt.....	Left 0-45 deg.
Arbor Size.....	5/8 in.
Arbor Speed.....	4200 RPM
Arbor Bearings.....	Sealed and Permanently Lubricated
Rim Speed.....	1904 FPM

**Cutting Capacities**

Maximum Depth Of Cut At 90 Degrees.....	3-1/8 in.
Maximum Depth Of Cut At 45 Degrees.....	2-1/4 in.
Maximum Rip To Right Of Blade-Standard.....	36 in.
Maximum Rip To Right Of Blade-Optional.....	36 in.
Maximum Rip To Left Of Blade.....	12 in.

**Table Information**

Floor To Table Height.....	35-3/8 in.
Table Size Length.....	27 in.
Table Size Width.....	20 in.
Table Size Thickness.....	1-1/2 in.
Table Size With Extension Wings Length.....	27 in.
Table Size With Extension Wings Width.....	44 in.
Table Size With Extension Wings Thickness.....	1-1/2 in.
Distance Front Of Table To Center Of Blade.....	16 in.
Distance Front Of Table to Blade At Maximum Cut.....	11-1/8 in.

**Fence Information**

Fence Type.....	Camlock T-Shaped, Aluminum Face
Fence Size Length.....	33-1/4 in.
Fence Size Width.....	3-1/8 in.
Fence Size Height.....	2-9/16 in.
Fence Rail Type.....	Angle Iron/Square Tubing
Fence Rail Length.....	66 in.
Fence Rail Width.....	2 in.
Fence Rail Height.....	2 in.

**Miter Gauge Information**

Miter Gauge Slot Type.....	T-Slot
Miter Gauge Slot Size Width.....	3/4 in.
Mither Gauge Slot Size Height.....	3/8 in.

**Construction**

Table Construction.....	Precision Ground Cast Iron
Wings Construction.....	Precision Ground Cast Iron
Trunnions Construction.....	Cast Iron
Base Construction.....	Pre-Formed Steel
Body Assembly Construction.....	Pre-Formed Steel
Fence Assembly Construction.....	Steel with Aluminum Side Plates
Rails Construction.....	Angle Iron
Miter Gauge Construction.....	Cast Iron with Steel Bar
Guard Construction.....	Steel and Clear Plastic

**Other Related Information**

Paint.....	Powder Coated
Number Of Dust Ports.....	1
Dust Port Size.....	2-1/2 in.
Mobile Base.....	G7314Z

**Other Specifications:**

ISO Factory ..... ISO 9001  
Country Of Origin ..... China  
Warranty ..... 1 Year  
Serial Number Location ..... ID Label on Cabinet  
Assembly Time ..... 1 hour

**Features:**

- Riving Knife
- Camlock T-Shaped Fence with Aluminum Fence
- Extension Rails Available to Rip 36" Wide
- Includes Regular as well as Dado Blade Inserts
- Precision Ground Cast Iron Table with Beveled Edge
- All Machined Cast Iron Internal Structure
- Precision Ground Cast Iron Wings
- Clear Plastic Guard with Steel Splitter
- Inboard and Outboard Arbor Bearings
- Powder Coated Paint