



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G1067Z 14" X 40" SWIVEL-HEAD WOOD LATHE - Z SERIES

Product Dimensions:

Weight..... 179 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 58-3/4 x 20-1/2 x 45-3/4 in.
Footprint (Length x Width)..... 51 x 20-1/2 in.

Shipping Dimensions:

Type..... Cardboard
Content..... Machine
Weight..... 197 lbs.
Length x Width x Height..... 61 x 18 x 14 in.

Electrical:

Minimum Circuit Size..... 15 amp
Switch..... Paddle
Switch Voltage..... 110V
Cord Length..... 6 ft.
Cord Gauge..... 18 gauge
Plug Included..... Yes

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 1/2 HP
Voltage..... 110V
Prewired..... 110V
Phase..... Single
Amps..... 8A
Speed..... 1725 RPM
Cycle..... 60 Hz
Number of Speeds..... 1
Power Transfer Belt Drive
Bearings..... Shielded and Lubricated

Main Specifications:

Operation Information

Swing Over Bed..... 14 in.
Dist Between Centers..... 40 in.
Swing Over Tool Rest..... 10 in.
No of Spindle Speeds..... 6
Spindle Speeds..... 510, 810, 1200, 1630, 2100, 2800 RPM
Floor to Center Height..... 42-1/2 in.
Headstock Rotation..... 0, 45, 90, 135, 180 deg.

Spindle Information

Spindle Type..... Right Hand
Spindle Taper..... MT#2
Spindle Size..... 1 in.
Spindle Bore..... 0.406 in.
Spindle Center..... Spur
Spindle TPI..... 12
Indexed Spindle..... 15 deg.
No of Indexes..... 12

Tailstock Information

Tailstock Taper..... MT#2
Tailstock Center..... Live

Construction

Bed..... Precision Ground Cast Iron
Frame..... Cast Iron
Stand..... Preformed Sheet Steel
Base..... Formed Steel
Headstock..... Cast Iron
Tailstock..... Cast Iron
Paint..... Powder Coated

Other Related Information

Bed Width..... 5 in.
Faceplate Size..... 6 in.

Other Specifications:

Country Of Origin Taiwan
Warranty 1 Year
Serial Number Location Model Number Label on Front of Base, Right Side of Grizzly Nameplate
Awards Popular Woodworking Tool Buying Guide Editor's Choice

Features:

Articulated Tool Rest Support
15 deg. Spindle Indexing
Headstock can be Locked at any Location on Bed
Cast Iron Bed
Variable Speed
Paddle Switch with Safety Key
All Ball Bearing
Headstock Rotates 180 Degrees

Accessories Included:

6" Face Plate
Live Center
Spur Center