



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G1073Z 16" BANDSAW (BEST ON THE MARKET) - CABINET STAND VERSION

Product Dimensions:

Weight..... 408 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 39 x 32 x 42 in.
Footprint (Length x Width)..... 26 x 29-1/2 in.

Shipping Dimensions:

Carton #1

Type..... Cardboard Box
Content..... Machine
Weight..... 516 lbs.
Length x Width x Height..... 0 x 0 x 0 in.

Carton #2

Type..... Cardboard Box
Content..... Stand
Weight..... 128 lbs.
Length x Width x Height..... 26 x 24 x 22 in.

Electrical:

Power Requirement..... 110V or 220V, Single-Phase, 60 Hz
Prewired Voltage..... 220V
Full-Load Current Rating..... 28A at 110V, 14A at 220V
Minimum Circuit Size..... 30A at 110V, 15A at 220V
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 5 ft.
Power Cord Gauge..... 14 AWG
Plug Included..... No
Switch Type..... On/Off Paddle with Safety Lock

Motors:

Main

Horsepower..... 2 HP
Phase..... Single-Phase
Amps..... 28A/14A
Speed..... 1720 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Belt Drive
Bearings..... Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type..... External

Main Specifications:

Main Specifications

Bandsaw Size..... 16 in.
Max Cutting Width (Left of Blade)..... 16-1/2 in.
Max Cutting Height (Resaw Height)..... 7-3/8 in.
Blade Speeds..... 2275, 2720, 3265 FPM

Blade Information

Standard Blade Length..... 113 in.
Blade Width Range..... 1/4 – 1 in.
Type of Blade Guides..... Steel Guide Blocks

Table Information

Table Length..... 17 in.
Table Width..... 17 in.
Table Thickness..... 1-5/16 in.
Table Tilt..... Left 10, Right 45 deg.
Floor-to-Table Height..... 42 in.
Fence Locking Position..... Front & Rear
Fence is Adjustable for Blade Lead..... Yes

Construction Materials

Table..... Precision Ground Cast Iron
Fence..... Extruded Aluminum
Base/Stand..... Pre-Formed Steel
Frame/Body..... Cast Iron
Wheels..... Computer-Balanced Cast Iron
Tire..... Rubber
Wheel Cover Pre-Formed Steel
Paint Type/Finish..... Powder Coated

Other Related Information

Wheel Diameter..... 16-7/8 in.
Wheel Width..... 1-1/4 in.
Number of Dust Ports..... 1
Dust Port Size..... 2-1/2 in.
Compatible Mobile Base..... D2058A

Other Specifications:

Country of Origin Taiwan
Warranty 1 Year
Approximate Assembly & Setup Time 1 Hour
Serial Number Location ID Label on Upper Cover
ISO 9001 Factory No
Certified by a Nationally Recognized Testing Laboratory (NRTL) No

Features:

- Heavy-Duty Stand to Prevent Vibration
- Includes Fence and Standard Miter Gauge
- Heavy-Duty Rip Fence
- Micro Adjustable Blade Guides
- Easy Blade Changes
- Hinged Wheel Covers
- Wheel Brush
- 2 1/4" Dust Port