



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G4173 BABY POWER FEEDER

### Product Dimensions:

Weight..... 20 lbs.  
Length/Width/Height..... 31 x 11 x 12 in.  
Foot Print (Length/Width)..... N/A x N/A

### Shipping Dimensions:

Type..... Cardboard  
Content..... Machine  
Weight..... 26.70 lbs.  
Length/Width/Height..... 11 x 22 x 9 in.

### Electrical:

Switch..... On/Off Variable Speed  
Switch Voltage..... 110V  
Cord Length..... 9 ft.  
Cord Gauge..... 18 gauge  
Minimum Circuit Size..... 10 amp  
Plug Included..... Yes

### Motors:

#### Main

Type..... Universal Variable Speed  
Horsepower..... 1/8 HP  
Voltage..... 110V  
Prewired..... 110V  
Phase..... Single  
Amps..... 1.2A  
Speed..... 550 - 3300 RPM  
Cycle..... 60 Hz  
Number Of Speeds..... Variable  
Power Transfer ..... Gear Box  
Bearings..... Lubricated for Life

### Main Specifications:

#### Workpiece Capacities

Min. WorkPiece Len..... 5 in.

#### Operation Info

No. Of Feed Speeds..... Variable  
Feed Speeds..... 6-1/2 - 39 FPM  
Swing..... 360 deg.  
Vertical Movement..... 13 in.  
Horizontal Movement..... 11 in.  
Rotation..... Forward, Reverse

**Roller Info**

No. Of Rollers.....3  
Roller Width..... 1-1/8 in.  
Roller Diameter..... 3 in.  
Roller Suspension..... 1/4 in.  
Max Hght Rollers Parallel Table Surface..... 13 in.  
Centers Between Rollers..... 3-3/4 in.

**Other**

Column Diameter..... 1-1/4 in.

**Construction Info**

Roller Construction..... Synthetic Rubber  
Housing Construction..... Cast Aluminum  
Supports Construction..... Cast Iron  
Column Construction..... Steel  
Paint..... Epoxy

**Other Specifications:**

ISO Factory ..... ISO 9001  
Country Of Origin ..... Taiwan  
Warranty ..... 1 Year  
Serial Number Location ..... Serial Number Sticker On Motor Specification Plate Outside The Motor  
Assembly Time ..... 20 minutes

**Features:**

Rollers are Spring Tensioned  
Heavy-Duty Gear Reduction with Hardened Gears  
Universal Positioning with Handle Locks