



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G5851Z 24" PLANER 5 HP SINGLE-PHASE

Product Dimensions:

Weight..... 1200 lbs.
Length/Width/Height..... 42 x 40-1/2 x 37 in.
Foot Print (Length/Width)..... 24-1/2 x 20-1/2 in.

Shipping Dimensions:

Type..... Wood Crate
Content..... Machine
Weight..... 1126 lbs.
Length/Width/Height..... 42 x 45 x 45 in.

Electrical:

Switch..... Magnetic with Thermal Overload Protector
Switch Voltage..... 220V
Cord Length..... 7 ft.
Cord Gauge..... 10 gauge
Minimum Circuit Size..... 30 amp
Plug Included..... No

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 5 HP
Voltage..... 220V
Prewired..... 220V
Phase..... Single
Amps..... 25A
Speed..... 3450 RPM
Cycle..... 60 Hz
Number Of Speeds..... 1
Power Transfer Twin V-Belt Drive
Bearings..... Shielded and Lubricated

Feed

Type..... TEFC Capacitor Start Induction
Horsepower..... 2 HP
Voltage..... 220V
Prewired..... 220V
Phase..... Single
Amps..... 12A
Speed..... 3450 RPM
Cycle..... 60 Hz
Number Of Speeds..... 1
Power Transfer Variable Split Pulley System
Bearings..... Shielded and Lubricated

Main Specifications:

Operation Info

Max. Cut Width.....	24 in.
Min. Stock Length.....	8 in.
Min. Stock Thickness.....	1/4 in.
Max. Stock Thickness.....	8 in.
No. Of Cuts Per Inch.....	67 - 102
No. Of Cuts Per Minute.....	20,800
Cutterhead Speed.....	5200 RPM
Planing Feed Rate.....	17 - 26 FPM
Max. Cut Depth Planing Full Width.....	1/16 in.
Max. Cut Depth Planing 6 Inch Wide Board.....	1/8 in.

Cutterhead Info

Cutterhead Type.....	4 Knife
Cutterhead Dia.....	3-1/8 in.
No. Of Knives.....	4
Knife Type.....	HSS
Knife Size Length.....	24 in.
Knife Size Width.....	1 in.
Knife Size Thickness.....	1/8 in.
Knife Adjustment.....	Gibs and Jack Screws

Table Info

Table Movement.....	8 in.
Table Bed Size Length.....	24-1/8 in.
Table Bed Size Width.....	31-1/8 in.
Table Bed Size Thickness.....	3-1/2 in.
No. Of Bed Rollers.....	2
Floor To Table Height.....	22-1/2 - 30 in.

Construction

Table Construction.....	Precision Ground Cast Iron
Body Construction.....	Cast Iron
Cutterhead Assembly Construction.....	One Piece Machined Shaft
Infeed Roller Construction.....	Segmented Steel
Outfeed Roller Construction.....	Fine Finished Steel
Paint.....	Epoxy

Other

Table Locks.....	Two Positive
Measurement Scale.....	Inch and Metric
No. Of Dust Ports.....	1
Dust Port Size.....	5 in.
Mobile Base.....	G7315Z

Other Specifications:

Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	Machine Data Plate on Top of Machine
Assembly Time	15 minutes

Features:

- Lever Controlled Bed Rollers
- Handwheel Depth Adjustment
- Segmented Chip Breaker
- Table Locks
- Board Return Rollers
- Dust Covers Protect Vertical Support Columns and Leadscrews
- Grease Fittings on Cutterhead