



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G9740 20" PLANER W/ 7-1/2 HP 3-PHASE MOTOR

Product Dimensions:

Weight..... 1678 lbs.
Length/Width/Height..... 38-1/2 x 35-3/8 x 42-1/2 in.
Foot Print (Length/Width)..... 38 x 28 in.

Shipping Dimensions:

Type..... Wood Crate
Content..... Machine
Weight..... 1765 lbs.
Length/Width/Height..... 40 x 43 x 48 in.

Electrical:

Switch..... Magnetic
Switch Voltage..... 220V
Cord Length..... 4 ft.
Cord Gauge..... 10 gauge
Minimum Circuit Size..... 30 amp at 220V, 15 amp at 440V
Plug Included..... No
Phase Converter..... G7979

Motors:

Table Lift

Type..... TEFC Induction
Horsepower..... 1/2 HP
Voltage..... 220V
Prewired..... 220V
Phase..... Three
Amps..... 2A
Speed..... 1725 RPM
Cycle..... 60 Hz
Number Of Speeds..... 1
Power Transfer Chain Drive
Bearings..... Shielded and Lubricated

Feed

Type..... TEFC Induction
Horsepower..... 1 HP
Voltage..... 220V
Prewired..... 220V
Phase..... Three
Amps..... 4A
Speed..... 1145 RPM
Cycle..... 60 Hz
Number Of Speeds..... 1
Power Transfer Chain Drive
Bearings..... Shielded and Lubricated

Cutterhead

Type.....	TEFC Induction
Horsepower.....	7-1/2 HP
Voltage.....	220/440V
Prewired.....	220V
Phase.....	Three
Amps.....	20A
Speed.....	3450 RPM
Cycle.....	60 Hz
Number Of Speeds.....	1
Power Transfer	Belt Drive
Bearings.....	Shielded and Lubricated

Main Specifications:

Operation Info

Max. Cut Width.....	20 in.
Max. Cut Height.....	9 in.
Min. Stock Length.....	10 in.
Min. Stock Thickness.....	1/4 in.
Max. Stock Thickness.....	9 in.
No. Of Cuts Per Inch.....	42 - 84
No. Of Cuts Per Minute.....	20000
Cutterhead Speed.....	5000 RPM
Planing Feed Rate.....	20 - 40 FPM
Max. Cut Depth Planing Full Width.....	3/16 in.
Max. Cut Depth Planing 6 Inch Wide Board.....	5/16 in.

Cutterhead Info

Cutterhead Type.....	4 Knife
Cutterhead Dia.....	4-5/8 in.
No. Of Knives.....	4
Knife Type.....	HSS
Knife Size Length.....	20-1/8 in.
Knife Size Width.....	1-3/16 in.
Knife Size Thickness.....	1/8 in.
Knife Adjustment.....	Gibs and Jack Screws

Table Info

Table Movement.....	1/4 - 9 in.
Table Bed Size Length.....	20-1/8 in.
Table Bed Size Width.....	35-3/8 in.
Table Bed Size Thickness.....	5 in.
No. Of Bed Rollers.....	2
Floor To Table Height.....	24 - 33 in.

Construction

Table Construction.....	Precision Ground Cast Iron
Body Construction.....	Cast Iron
Cutterhead Assembly Construction....	One Piece Machined Steel Shaft; 4 Knife Slots; Shielded Ball Bearings
Infeed Roller Construction.....	Serrated Steel
Outfeed Roller Construction.....	Polished Steel
Paint.....	Epoxy

Other

Table Locks.....	One Positive
Measurement Scale.....	Inch and Metric
No. Of Dust Ports.....	1
Dust Port Size.....	5 in.

Other Specifications:

ISO Factory ISO 9001
Country Of Origin Taiwan
Warranty 1 Year
Serial Number Location ID Label on Top of Machine
Assembly Time 15 minutes

Features:

Table Height Display
Micro Adjustment of Table Height
Segmented Chip Breaker
Variable Speed Feed
Convenient Control Panel