



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G9922 OSCILLATING SPINDLE SANDER

Product Dimensions:

Weight..... 86 lbs.
Length/Width/Height..... 26 x 26 x 39-1/2 in.
Foot Print (Length/Width)..... 25-1/2 x 25 in.

Shipping Dimensions:

Type..... Cardboard
Content..... Machine
Weight..... 102 lbs.
Length/Width/Height..... 18 x 17 x 23 in.

Electrical:

Switch..... Toggle On/Off with Safety Locking Tab
Switch Voltage..... 110V
Cord Length..... 6 ft.
Cord Gauge..... 18 gauge
Minimum Circuit Size..... 15 amp
Plug Included..... Yes

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 1/2 HP
Voltage..... 110V
Prewired..... 110V
Phase..... Single
Amps..... 4.6A
Speed..... 3450 RPM
Cycle..... 60 Hz
Number Of Speeds..... 1
Power Transfer Direct Drive
Bearings..... Sealed and Permanently Lubricated

Main Specifications:

Table Info

Table Width..... 14-1/2 in.
Table Length..... 14-1/2 in.
Table Thickness..... 1 in.
Table Tilt..... 45 deg.
Table Opening..... 5-1/2 in.
Table Inserts..... 2-3/8 in.
Floor To Table Height..... 39-1/2 in.
Miter Gauge Slot Width..... 5/8 in.
Miter Gauge Slot Height..... 1/4 in.

Spindle Info

Spindle Diameters..... 2 in.
 Spindle Lengths..... 5-1/2 in.
 Spindle Speed..... 3450 RPM
 Spindle Oscillations..... 64 SPM
 Stroke Length..... 1 in.
 Arbor Size..... 15 mm
 Total Arbor Length......5 in.

Construction

Base Construction..... Formed Steel
 Stand Construction..... Steel
 Table Construction..... Ground Cast Iron
 Frame Construction..... Steel
 Miter Gauge Construction..... Plastic
 Paint..... Epoxy

Other

No. Of Dust Ports..... 1
 Dust Port Size..... 2 in.
 Mobile Base..... G7314Z

Other Specifications:

Country Of Origin China
 Warranty 1 Year
 Serial Number Location Front Label
 Assembly Time 1 hour

Features:

Includes 80 Grit Sanding Sleeve, Miter Gauge and Wrench Set
 Table Tilts to 45 deg. for Bevel Sanding
 Steel Construction
 Cast Iron Table
 Paddle Safety Switch with Lock