



# Product Specifications

P.O. Box 2027, Bellingham, WA 98227 U.S.A.  
PHONE: (360) 734-1540 • © South Bend Tools  
[www.southbendtools.com](http://www.southbendtools.com)



## Model SB1055F 16" x 60" Gearhead Lathe with DRO

### Product Dimensions

Weight.....	3300 lbs.
Width (side-to-side) x Depth (front-to-back) x Height.....	105-1/2 x 32-3/4 x 49 in.
Footprint (Length x Width).....	102 x 19-1/2 in.

### Shipping Dimensions

Type.....	Wood Slat Crate
Content.....	Machine
Weight.....	3422 lbs.
Length x Width x Height.....	109 x 45 x 74 in.

### Electrical

Power Requirement.....	440V, 3-Phase, 60 Hz
Prewired Voltage.....	440V
Full-Load Current Rating.....	10.23A
Minimum Circuit Size.....	15A
Connection Type.....	Permanent (Hardwire to Shutoff Switch)
Switch Type.....	Control Panel w/Magnetic Switch Protection

### Motors

#### Main

Horsepower.....	7.5 HP
Phase.....	3-Phase
Amps.....	10A/9A
Speed.....	1720 / 850 RPM
Type.....	TEFC Induction
Power Transfer .....	V-Belt Drive
Bearings.....	Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type.....	N/A

#### Coolant Pump

Horsepower.....	1/8 HP
Phase.....	3-Phase
Amps.....	0.23A
Speed.....	3450 RPM
Type.....	TEFC Induction (Class F)
Power Transfer .....	Direct Drive
Bearings.....	Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type.....	N/A

## Main Specifications

### Operation Info

Swing Over Bed.....	16 in.
Distance Between Centers.....	60 in.
Max Weight Between Centers.....	660 lbs.
Swing Over Cross Slide.....	10-3/8 in.
Swing Over Saddle.....	15-3/4 in.
Swing Over Gap.....	22.95 in.
Maximum Tool Bit Size.....	3/4 in.
Compound Travel.....	5.1 in.
Carriage Travel.....	54 in.
Cross Slide Travel.....	9 in.

### Headstock Info

Spindle Bore.....	2.0625 in.
Spindle Taper.....	MT#6
Number of Spindle Speeds.....	16
Spindle Speeds.....	40 – 2000 RPM
Spindle Type.....	D1-6 Camlock
Spindle Bearings.....	NTN Tapered Roller
Spindle Length.....	24-1/4 in.
Spindle Length with 3-Jaw Chuck.....	30-7/8 in.
Spindle Length with 4-Jaw Chuck.....	28-3/4 in.
Spindle Length with Faceplate.....	26-1/4 in.

### Tailstock Info

Tailstock Quill Travel.....	6 in.
Tailstock Taper.....	MT#4
Tailstock Barrel Diameter.....	2.047 in.

### Threading Info

Number of Longitudinal Feeds.....	17
Range of Longitudinal Feeds.....	0.002 – 0.067 in./rev.
Number of Cross Feeds.....	17
Range of Cross Feeds.....	0.001 – 0.034 in./rev
Number of Inch Threads.....	45
Range of Inch Threads.....	2 – 72 TPI
Number of Metric Threads.....	39
Range of Metric Threads.....	0.2 – 14.0 mm
Number of Modular Pitches.....	18
Range of Modular Pitches.....	0.3 – 3.5 MP
Number of Diametral Pitches.....	21
Range of Diametral Pitches.....	8 – 44 DP

### Dimensions

Bed Width.....	10-1/4 in.
Carriage Leadscrew Diameter.....	1-1/8 in.
Leadscrew TPI.....	4 TPI
Carriage Leadscrew Length.....	83-9/16 in.
Steady Rest Capacity.....	5/16 – 4-5/16 in.
Follow Rest Capacity.....	5/8 – 3-1/8 in.
Faceplate Size.....	12 in.
Feed Rod Diameter.....	3/4 in.
Floor to Center Height.....	43-1/2 in.
Height With Leveling Jacks.....	44-1/2 in.

## **Construction**

Base.....	Cast Iron
Headstock.....	Cast Iron
End Gears.....	Flame-Hardened Steel
Bed.....	Induction-Hardened, Precision-Ground Meehanite Cast Iron
Body.....	Cast Iron
Stand.....	Cast Iron
Paint Type/Finish.....	Urethane

## **Fluid Capacities**

Headstock Capacity.....	7.4 qt.
Headstock Fluid Type.....	ISO 32 (eg. Grizzly T23963, Mobil DTE Light)
Gearbox Capacity.....	1.4 qt.
Gearbox Fluid Type.....	ISO 68 (eg. Grizzly T23962, Mobil Vactra 2)
Apron Capacity.....	1.2 qt.
Apron Fluid Type.....	ISO 68 (eg. Grizzly T23962, Mobil Vactra 2)
Coolant Capacity.....	11.1 qt.

## **Other**

Country of Origin .....	Taiwan
Warranty .....	2 Years
Approximate Assembly & Setup Time .....	1 Hour
Serial Number Location .....	ID Label on Rear Side of Left Stand
ISO 9001 Factory .....	No
Certified by a Nationally Recognized Testing Laboratory (NRTL) .....	No

## **Features**

Allen Bradley Electrical Components  
Signature South Bend 3 V-Way Bed  
Meehanite Castings with Induction-Hardened Ways  
Safety Chuck Guard with Micro-Switch Shut-Off  
Halogen Work Light (24V/70W)  
4-Way Tool Post  
Complete Coolant System  
Micrometer Carriage Stop  
NTN Japanese Spindle Bearings  
Full Length Splash Guard  
Front Removable Sliding Chip Tray  
Completely Enclosed Universal Gearbox for Cutting Inch, Metric, Modular and Diametral Pitches  
Jog Button and Emergency Stop  
Headstock Gears Run in an Oil Bath

## **Included Accessories**

10" 4-Jaw Independent Chuck D1-6  
12" Faceplate D1-6  
9" 3-Jaw Scroll Chuck (Mounted to 9" D1-6 Back Plate)  
Eight Leveling Pads  
Follow Rest  
MT#6 to MT#4 Spindle Sleeve  
Service Tools  
Steady Rest with Ball Bearing Tips  
Tool Box  
Two MT #4 Dead Centers (1 Carbon Steel and 1 Carbide-Tipped)  
USA-Written Manual