


THE KIT/SET CONTAINS FOUR DIFFERENT GRADES OF BUFFING COMPOUNDS. ALL GRADES ARE FORMULATED WITH AN ABRASIVE THAT SERVES TO BUFF/SHINE THE WORK SURFACE AND THE GREASE BINDERS SERVE TO ADHERE THE ABRASIVE TO THE BUFFING WHEEL FACE. THE TYPE OF ABRASIVE AND GREASE BINDER PERCENTAGES CAN BE, AND ARE VARIED TO SUIT THE INDIVIDUAL REQUIREMENTS TO BUFF AND SHINE DIFFERENT CLASSES OF METALS AND PLASTICS.



MSDS NO. 29-F
DATE 2-3-92
SECTION 1

PRODUCT NAME OR NUMBER (AS IT APPEARS ON LABEL) 62511 4-BAR COMPOUND KIT	EMERGENCY TELEPHONE NO. 313-921-7030
MANUFACTURER'S NAME FORMAX MANUFACTURING CORPORATION	APPROVED BY
ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE) 3178 BELLEVUE, DETROIT, MICHIGAN 48207	MANUFACTURER'S D.U.N.S. NO. 00-535-4238
PROPER SHIPPING NAME NMFC-48580 SCOURING COMPOUND (CAKE, PASTE OR LIQUID FORM N.O.I.)	
ADDITIONAL HAZARD CLASSES (AS APPLICABLE) NOT REGULATED BY D.O.T.	
CHEMICAL FAMILY ORGANIC/INORGANIC	FORMULA ABRASIVE/GREASE MIXTURE

SECTION II COMPOSITION

CHEMICAL NAME	PERCENTAGE RANGE	COMMON NAME	REG. (Y/N)	CAS #	OSHA PERMISSIVE EXPOSURE LIMIT	ACGIH TLV	CARCINOGEN (Y/N)
BINDERS			Y		15mg/M ³	10mg/M ³	
ANIMAL FATS	32/26			61789-97-7	(Total Dust)		N
MINERAL GREASE				8002-74-2			N
ABRASIVES							
BLACK EMERY	58			1349-28-1/1332-57-7			N
BROWN TRIPOLI	72			7631-86-9			N
WHITE ROUGE	73			1349-28-1			N
RED ROUGE	74			1349-28-1/409-21-2			N

*Materials are regulated by OSHA 29 CFR 1910.1200, Hazard Communication Standard, and/or the Michigan, Right To Know Regulations

SECTION III PHYSICAL AND CHEMICAL DATA

BOILING POINT OVER 250°F	MELTING POINT 125°/140°F	SPECIFIC GRAVITY 1.5/1.7
VAPOR PRESSURE N/A	PERCENT VOLATILE BY VOL -0-	VAPOR DENSITY N/A
EVAPORATION RATE NONE	SOLUBILITY IN WATER NEGLIGIBLE	SOLUBILITY IN ALCOHOL PARTIALLY
SOLUBILITY IN OTHER SOLVENT ALKALINE SOAP CLEANERS OR CHLORINATED SOLUTIONS	APPEARANCE AND ODOR	CAKE FORM/TALLOW ODOR

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT OVER 300°F (METHOD USED) C.O.C.	FLAMMABLE LIMITS LEL NAIFUEL
EXTINGUISHING MEDIA C.O. ₂ , DRY CHEMICAL OR FOAM	
SPECIAL FIRE FIGHTING PROCEDURES TREAT BUFFING DUST, DIRT AND DEBRIS AS AN OIL FIRE	
EXPLOSION POTENTIAL NONE	

SECTION VI REACTIVITY DATA

STABILITY: UNSTABLE STABLE	CONDITIONS TO AVOID: NAIF
INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZERS OR REDUCING AGENTS	
HAZARDOUS DECOMPOSITION PRODUCTS: ON COMBUSTION HYDROCARBONS MAY FORM TO PRODUCE SMOKE, CARBON MONOXIDE, CARBON DIOXIDE.	
HAZARDOUS POLYMERIZATION	MAY OCCUR WILL NOT OCCUR
CONDITIONS TO AVOID: USING UNDER CONDITION OF INSUFFICIENT DUST COLLECTING SYSTEM.	

SECTION V HEALTH, FIRST AID AND MEDICAL DATA

PRIMARY ROUTE(S) OF ENTRY	ACUTE AND CHRONIC HEALTH EFFECTS AND EFFECTS OF OVEREXPOSURE	FIRST AID AND MEDICAL INFORMATION
INHALATION (DURING USE)	ACUTE - MAY CAUSE COUGHING, SHORTNESS (DUST) OF BREATH CHRONIC - MAY AFFECT BREATHING CAPACITY (DUST)	REMOVE TO FRESH AIR APPLY ARTIFICIAL RESPIRATION AS NEEDED. OBTAIN FIRST AID OR MEDICAL ASSISTANCE
INGESTION	NO KNOWN ADVERSE EFFECTS, BUT INGESTION NOT RECOMMENDED	OBTAIN FIRST AID OR MEDICAL ASSISTANCE, IF NEEDED
SKIN CONTACT & ABSORPTION	IRRITATION OF THE SKIN MAY OCCUR DUE TO MECHANICAL/CHEMICAL ACTION	OBTAIN FIRST AID OR MEDICAL ASSISTANCE, IF NEEDED
EYE	DUST MAY IRRITATE EYES	WASH WITH LARGE AMOUNTS OF WATER OBTAIN FIRST AID OR MEDICAL ASSISTANCE, IF NEEDED
OTHER POTENTIAL HEALTH RISKS (PROLONGED INHALATION OF DUST PARTICLES MAY RESULT IN DISABLING PULMONARY FIBROSIS.)	SYMPTOMS MIGHT INCLUDE DEPOSITS OF MATERIALS IN EYES, EARS, NASAL PASSAGES, IRRITATION OF MUCUS MEMBRANES. WARNING: DO NOT BREATHE DUST OF COMPOUNDS CONTAINING ABRASIVE MATERIALS WITHOUT FOLLOWING OSHA SAFETY AND HEALTH STANDARDS FOR DUST ACCUMULATION COLLECTION.	OBTAIN MEDICAL ASSISTANCE

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SWEEP INTO CONTAINERS. STORAGE OF BUFFING WHEEL AND COMPOUND DEBRIS MAY CONTAIN COMBUSTIBLE LINT.	
WASTE DISPOSAL METHOD: INCINERATE OR DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.	
CERCLA (SUPERFUND) REPORTABLE QUANTITY (IN LBS.)	N/A
RCRA HAZARDOUS WASTE NO. (40 CFR 261.33)	N/A
VOLATILE ORGANIC COMPOUND (VOC) (AS PACKAGED, MINUS WATER)	N/A
<input type="checkbox"/> THEORETICAL _____ lb/gal	<input type="checkbox"/> ANALYTICAL <u>14</u> lb/gal

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): OSHA 24 CFR/134 NIOSH/MSHA APPROVED RESPIRATORS FOR PARTICULATES FROM BUFFING DEBRIS.
VENTILATION: LOCAL EXHAUST: _____ MECHANICAL (GENERAL): _____ GENERAL ROOM VENTILATION RECOMMEND VENTING TO DUST COLLECTORS
PROTECTIVE GLOVES: AS DESIRED BY USER.
EYE PROTECTION: OSHA 29 CFR 1910.122 SAFETY GLASSES
OTHER PROTECTIVE EQUIPMENT: PROTECTIVE WORK CLOTHING, BODY APRON OR BELLY PADS, SAFETY SHOES, AS NEEDED.
HEARING PROTECTION: OSHA 29 CFR 1910.215 (HEARING PROTECTION)

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: HANDLE WITH ADEQUATE VENTILATION FOR NUISANCE DUST WHEN USING. SEE OSHA 29 CFR 1910.24 (VENTILATION) AND 29 CFR 1910.1000 (AIR CONTAMINANTS). OTHER PRECAUTIONS: KEEP LIQUIDS FROM FREEZING. STORE AWAY FROM EXCESSIVE HEAT.

The information and recommendations set forth herein are taken from sources believed to be accurate as of the date hereof; however, Formax Mfg. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.