

H3788-89

Material Safety Data Sheet

HMIS: H1 F4 RO PB

Complies with OSHA HAZARD Communication NFPA: H1 F4 RO P-

Standard 29 CFR 1910.1200

Identity: #1055(A, B, P) G96 Gun Treatment

Code:

G96 PRODUCTS CO., Inc.

Emergency Telephone No : (760)602-8888

85 5th Avenue, Bldg. #6

Tel. # for Information: (973)684-4050

Paterson, NJ 07544

Date Prepared: JUNE 2001

Signature of Preparer (optional): Goldman

SECTION II HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components (Specific Chemical Identity)	OSHA CAS	ACGIH OTHER LIMITS Percentage	
		REL-TWA	TLV-TWA Recommended (Optional)
PROPANE	CAS (74-98-6)	300	10-35%
		150	BUTANE CAS (75-28-5)
		300	5-25%
PETROLEUM DISTILLATES	CAS (64742-47-8)	300	15-30%
MINERAL OIL	CAS (8042-47-5)		10-35%
DIMETHYL POLYSILOXANE	CAS (63148-62-7)		1-5%

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICSBoiling Point: (N/A) Specific Gravity (H₂O=1): N/A

Vapor Pressure AEROSOL CAN: Less than 140 F PSIG 130 F Melting Point: N/A

Vapor Density (Air=1): HEAVIER Evaporation Rate: Heavier than air.

Solubility in Water: NIL. (Butyl Acetate = 1)

Appearance & Odor: CHARACTERISTIC PERFUMED OIL

SECTION IV FIRE & EXPLOSION HAZARD DATAFlash Point (-20 F): TCC Flammability Limit: LEL 1.5 UEL 9Extinguishing Media: STANDARD FOAM, CO₂, DRY CHEMICAL

Special Firefighting Procedures: SAME AS FOR PETROLEUM FIRES.

Unusual Fire & Explosion Hazards: Aerosols are under pressure.

Exposure in excess of 140 F may cause bursting of can.

SECTION V REACTIVITY DATA

Stability: Stable; Hazardous Polymerization: Will not occur

Conditions to Avoid: HEAT, FLAME, SPARKS

Incompatibility (Material to avoid): NOT DETERMINED

Hazardous Decomposition or Byproducts: NOT DETERMINED

PAGE 2 MSDS - (#1055(A,B,P) G96 GUN TREATMENT

SECTION VI HEALTH HAZARD DATA

Route(s) of Entry: **Inhalations?** Yes **Skin?** Yes **Ingestion?** Yes
Health Hazards (Acute & Chronic): Can cause irritation, to Eyes: upon direct contact REDNESS & BLURRED VISION. Inhaling high concentration of the vapor IRRITATION, DIZZINESS, HEADACHE OR ASPHYSIATION. SKIN: contact can cause irritation.
Carcinogenity: NTP? No IARC Monographs? No OSHA Regulated? No
Signs & Symptoms of Exposure: Frequent or prolonged contact may cause skin irritation. Exposure to high concentration of the vapor may cause dizziness or in Extreme case, Absence of Oxygen could produce NORCOSIS. If UNCONSCIOUS remove person to fresh air & call Physician.

Medical Conditions generally aggravated by exposure: If swallowed, do not induce vomiting. If sprayed into eyes flush immediately w/large quantities of water and call Physician.
Emergency & First Aid Procedures: Remove patient to fresh air. Call a Physician(see above).

SECTION VII PRECAUTIONS FOR SAFE HANDLING & USE

Steps to be Taken in Case Material is Released or Spilled: Use Absorbents to pick up small Quantities of liquid.
Waste Disposal Method: Do Not puncture or incinerate, dispose in accordance with Federal, state and local regulations.
Precautions to be Taken in Handling & Storage: Do not store above 120 F Contents under pressure. Wear protective clothing e.g. Gloves & Goggles. Keep from all sources of heat, flames and sparks(see Above).

SECTION VIII CONTROL MEASURES

Respiratory Protection: Ventilated area if Possible

Ventilation: local Exhaust: Yes Special: none

Mechanical (general):

Protective Gloves: Polyethylene Gloves.

Eye Protection: Safety glasses or goggles or face shield.

Other Protective Clothing or Equipment: Plastic apron, DO NOT WEAR CLOTHING IF SOAKED BY SPRAY.

Work/Hygienic Practices: Wash thoroughly with soap and water after handle.