

Grizzly Industrial®

CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1123

July, 2019

Introducing the Grizzly Model G0885 5" Portable Metal Cutting Bandsaw

New!

At just 44 lbs. yet packed with features, this Metal-Cutting Bandsaw is perfect for any benchtop, small shop, or job site!

MADE IN TAIWAN



MACHINE HIGHLIGHTS (see Machine Data Sheet for full specifications)

- ½ HP, 120V, 5A, single-phase, universal motor with variable-speed control.
- Maximum workpiece capacity is 4¾" diameter and 4¾" x 5" rectangular.
- 100–260 FPM variable-speed blade.
- Headstock pivots to cut miters from 0–60°.
- Features an adjustable workstop for repeat cuts, a headstock-mounted trigger switch for added control, and ball-bearing blade guides.
- Weighs approximately 44 lbs.

The Model G0885 is available for \$395 and is covered by a one-year warranty. For more information call **1-800-523-4777** or visit **www.grizzly.com**.

Due to rapidly changing market conditions our prices may be increased at any time without prior notice. Our website is updated with any changes as they occur.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0885 5" PORTABLE METAL CUTTING BANDSAW

Product Dimensions:

Weight..... 44 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 27 x 25 x 26 in.
Footprint (Length x Width)..... 12-1/2 x 16 in.

Shipping Dimensions:

Type..... Cardboard Box
Content..... Machine
Weight..... 51 lbs.
Length x Width x Height..... 29 x 15 x 18 in.
Must Ship Upright..... Yes

Electrical:

Power Requirement..... 120V, Single-Phase, 60 Hz
Full-Load Current Rating..... 5A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 6 ft.
Power Cord Gauge..... 18 AWG
Included Plug Type..... 5-15
Switch Type..... On/Off Push Button

Motors:

Main

Horsepower..... 1/2 HP
Phase..... Single-Phase
Amps..... 5A
Speed..... 2000 - 4200 RPM
Type..... Universal
Power Transfer..... Direct
Bearings..... Shielded & Permanently Lubricated

Main Specifications:

Operation Info

Blade Speeds..... 100 - 260 FPM
Std. Blade Length..... 56-1/2 in.
Blade Length Range..... 1/2 in.

Cutting Capacities

Angle Cuts..... 0 - 60 deg.
Vise Jaw Depth..... 5 in.
Vise Jaw Height..... 2-3/4 in.
Max. Capacity Rectangular Height at 90 Deg..... 4-3/4 in.
Max. Capacity Rectangular Width at 90 Deg..... 5 in.
Max. Capacity Round at 90 Deg..... 4-3/4 in.

Construction

Table..... Cast Iron
Upper Wheel..... Cast Iron
Lower Wheel..... Cast Iron
Body..... Aluminum
Base..... Steel
Wheel Cover..... Steel
Paint Type/Finish..... Powder Coated

Other

Blade Guides..... Ball Bearing

Other Specifications:

Country of Origin Taiwan
Warranty 1 Year
Approximate Assembly & Setup Time 15 Minutes
Serial Number Location Machine ID Label
ISO 9001 Factory No
Certified by a Nationally Recognized Testing Laboratory (NRTL) No

Features:

Variable-Speed Control
Built-In Vise
Handle with ON/OFF Trigger
0-60 Degree Angle Cuts