

Grizzly Industrial®

CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1123

January, 2020

Introducing the Grizzly Model G0901 28" Portable Sawmill



MACHINE HIGHLIGHTS (see Machine Data Sheet for full specifications)

- Powered by a 13½ HP Briggs and Stratton® gas engine.
- Mill logs up to 28" diameter x 22" wide, with a maximum cut thickness of 6".
- Features a modular track system for varying length requirements, leveling feet for stabilizing the saw mill on uneven ground, and adjustable work stops and clamp for securing logs during cuts.
- Equipped with a locking hand crank with detents for quickly setting cut thickness in 1/16" increments, a hand throttle for easy blade speed control during the cut, and an onboard coolant reservoir with drip nozzle for blade lubrication.
- Weighs approximately 838 lbs.

The Model G0901 is available for \$5500 and is covered by a one-year warranty. For more information call **1-800-523-4777** or visit **www.grizzly.com**.

Due to rapidly changing market conditions our prices may be increased at any time without prior notice. Our website is updated with any changes as they occur.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0901 28" PORTABLE SAWMILL

Product Dimensions:

Weight 838 lbs.
Width (side-to-side) x Depth (front-to-back) x Height 75 x 144 x 56 in.
Footprint (Length x Width) 144 x 35 in.

Shipping Dimensions:

Type Wood Slat Crate
Content Machine and Toolbox
Weight 993 lbs.
Length x Width x Height 87 x 45 x 50 in.
Must Ship Upright Yes

Engine:

Main

Manufacturer Briggs & Stratton
Horsepower 13.5 HP
Displacement 420 cc
Oil Capacity 39 oz.
Starter Manual

Main Specifications:

Cutting Capacity

Max. Log Length (with included track sections) 9 ft. 3 in.
Min. Log Length 30 in.
Max. Log Diameter 28 in.
Max. Width of Cut 22 in.
Max. Depth of Cut 6 in.
Min. Height Above Bed 1-3/16 in.
Track Length 12 ft. (6 ft. Track Sections)
Track Width 35 in.

Blade Information

Blade Speeds 4825 FPM
Blade Length 144 in.
Blade Width 1 in.
Blade Thickness 0.035 in.
Blade Guides Roller

Operation

Feed System Manual
Lift System Manual
Clutch Centrifugal
Log Supports 2 Supports & Log Clamp

Construction

Track..... Electroplated Steel
Frame Steel
Body Steel
Wheels..... Cast Iron
Paint Powder Coated & Epoxy

Additional Information

Wheel Size 19 in.
Blade Lubrication (type) Water or Water w/Soap
Lubrication Reservoir (capacity)..... 1-1/4 gal.
Track Extensions 6 ft. Sections
Track Leveling 4 Adjustable Feet per Section

Other Specifications:

Country of Origin..... Taiwan
Warranty..... 1 Year
Sound Rating 90 - 92 dB
Approximate Assembly & Setup Time 1 Hr.
Serial Number Location ID Label

Features:

- 13.5 HP Briggs & Stratton Engine
- Manual Lift System Raises 1" per Revolution with 1/16 in. Stop Increments
- Easy-Set Blade Tensioning
- Low-to-the-Ground Bed
- Adjustable Log Supports and Log Clamp
- Blade Lubrication System
- Easy Shipping and Assembly