



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0426 OSCILLATING EDGE BELT AND SPINDLE SANDER - LOWES

Product Dimensions:

Weight..... 29 in.
Width (side-to-side) x Depth (front-to-back) x Height..... 17 x 18 x 18-1/2 in.
Footprint (Length x Width)..... 18 x 16 in.

Shipping Dimensions:

Type..... Cardboard Box
Content..... Machine
Weight..... 34 lbs.
Length x Width x Height..... 21 x 19 x 19 in.
Must Ship Upright..... Yes

Electrical:

Power Requirement..... 120V, Single-Phase, 60 Hz
Full-Load Current Rating..... 4A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 72 in.
Power Cord Gauge..... 18 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Switch Type..... Toggle ON/OFF w/Disabling Key

Motors:

Main

Horsepower..... 1/2 HP
Phase..... Single-Phase
Amps..... 4A
Speed..... 10,000 RPM
Type..... Universal
Power Transfer Belt
Bearings..... Shielded & Permanently Lubricated

Main Specifications:

Belt Sander Info

Sanding Belt Width.....	4 in.
Sanding Belt Length.....	24 in.
Sanding Belt Speed.....	1575 FPM
Table Length.....	15-3/4 in.
Table Width.....	16 in.
Table Thickness.....	1/8 in.
Table Tilt.....	0 - 45 deg.
Table-to-Floor Height.....	13-1/4 in.
Drive Wheel Diameter.....	3 in.
Drive Wheel Width.....	4 in.
Belt Tension Release Type.....	Quick-Release Lever
Platen Type.....	Steel
Platen Length.....	6-7/8 in.
Platen Width.....	4 in.
Idler Wheel Diameter.....	1-1/2 in.
Idler Wheel Width.....	4 in.

Spindle Sander Info

Sanding Drum Diameters.....	3/4, 1, 1-1/2, 2 in.
Sanding Drum Length.....	4-1/2 in.
Spindle Speed.....	2000 RPM
Spindle Oscillation.....	58 OPM
Stroke Length.....	5/8 in.
Spindle Shaft Diameter.....	1/2 in.
Number of Table Inserts.....	5
Included Sanding Sleeve Grit Size.....	80
Table Tilt.....	0 - 45 deg.

Construction Materials

Base.....	Plastic
Table.....	Cast Aluminum
Miter Gauge.....	Plastic

Other Related Info

Miter Gauge Slot Width.....	5/8 in.
Miter Gauge Slot Height.....	1/4 in.
Number of Dust Ports.....	1
Dust Port Size.....	1-1/2 in.

Other Specifications:

Country of Origin	China
Warranty	1 Year
Approximate Assembly & Setup Time	15 Minutes
Serial Number Location	Machine ID Label
ISO 9001 Factory	Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL)	Yes

Features:

Combines Advantages of Edge Sander and Spindler Sander in One Machine
Quickly Converts Between Setups w/Included Wrench
Tilting Table w/Detents at 0, 15, 22.5, 30, and 45 Degrees
Four Sanding Drums: 3/4", 1", 1-1/2", and 2"
Five 80-Grit Sanding Sleeves Included w/Matching Table Inserts: 1/2", 3/4", 1", 1-1/2", and 2"
80-Grit Sanding Belt Included
Included Miter Gauge and Backstop
On-Board Storage Included for All Accessories