



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0438RLX 10" 2 HP 220V CONTRACTOR LEFT-TILT TABLE SAW

Product Dimensions:

Weight..... 300 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 59-1/2 x 47 x 36 in.
Footprint (Length x Width)..... 31-1/2 x 25-3/4 in.

Shipping Dimensions:

Carton #1

Type..... Cardboard Box
Content..... Machine
Weight..... 273 lbs.
Length x Width x Height..... 23 x 36 x 18 in.

Carton #2

Type..... Cardboard Box
Content..... Fence & Rails
Weight..... 55 lbs.
Length x Width x Height..... 18 x 62 x 7 in.

Electrical:

Power Requirement..... 115V or 230V, Single-Phase, 60 Hz
Prewired Voltage..... 230V
Full-Load Current Rating..... 18A at 115V, 9A at 230V
Minimum Circuit Size..... 20A at 115V, 15A at 230V
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 7-1/2 ft.
Power Cord Gauge..... 12 AWG
Plug Included..... No
Recommended Plug Type..... 6-15 for 230V, L5-30 for 115V
Switch Type..... Rail-Mounted Star/Stop Push Button

Motors:

Main

Horsepower..... 2 HP
Phase..... Single-Phase
Amps..... 18A/9A
Speed..... 3450 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Belt Drive
Bearings..... Sealed & Permanently Lubricated

Main Specifications:

Main Information

Table Saw Type.....	Contractor
Maximum Standard Blade Diameter.....	10 in.
Arbor Size.....	5/8 in.
Arbor Speed.....	4200 RPM
Maximum Width of Dado.....	13/16 in.
Blade Tilt Direction.....	Left
Max Blade Tilt.....	45 deg.
Maximum Depth of Cut At 90 Degrees.....	3 in.
Maximum Depth of Cut At 45 Degrees.....	2 in.
Max Rip Right of Blade w/Included Fence & Rails.....	30 in.
Max Rip Left of Blade w/Included Fence & Rails.....	8 in.

Additional Blade Information

Rim Speed at Max Blade Diameter.....	11,000 FPM
--------------------------------------	------------

Table Information

Floor to Table Height.....	36 in.
Table Size with Extension Wings Width.....	39-5/8 in.
Table Size with Extension Wings Depth.....	27 in.
Distance Front of Table to Center of Blade.....	14-11/16 in.
Distance Front of Table to Blade At Maximum Cut.....	10 in.
Main Table Size Thickness.....	1-1/2 in.

Fence Information

Fence Type.....	Camlock T-Shape w/Aluminum Face (Shop Fox Aluma-Classic)
Fence Size Length.....	41 in. (w/o Handle)
Fence Size Width.....	3-15/16 in.
Fence Size Height.....	2-7/16 in.
Fence Rail Type.....	Square Steel Tubing/Angle Iron
Fence Rail Length.....	57-1/4 in.
Fence Rail Width.....	2-3/8 in.
Fence Rail Height.....	1-9/16 in.

Miter Gauge Information

Miter Gauge Slot Type.....	T-Slot
Miter Gauge Slot Size Width.....	3/4 in.
Miter Gauge Slot Size Height.....	3/8 in.

Construction

Table.....	Precision-Ground Cast Iron
Wings.....	Precision-Ground Cast Iron
Cabinet.....	Steel
Trunnions.....	Cast Iron
Fence Assembly.....	Steel with Aluminum Side Plates
Rails.....	Steel
Miter Gauge Construction.....	Cast Iron with Steel Bar
Guard.....	Steel and Clear Plastic
Body/Cabinet Paint Type/Finish.....	Powder Coated
Arbor Bearings.....	Sealed & Permanently Lubricated

Other Related Information

Number of Dust Ports.....	1
Dust Port Size.....	4 in.
Optional Long Rails.....	H5744
Max Rip Right of Blade w/Optional Long Rails.....	50 in.
Compatible Mobile Base.....	D2057A

Other Specifications:

Country of Origin Taiwan
Warranty 1 Year
Approximate Assembly & Setup Time 2 Hours
Serial Number Location ID Label on Center of the Stand
ISO 9001 Factory Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) No

Features:

- Quick release splitter guard
- Riving knife
- Aluma-Classic fence
- Extension rails available to rip 50 in. wide
- Includes regular as well as dado blade table inserts
- Precision-ground cast-iron table with beveled edge
- Precision-machined cast-iron motor pulley for reduced vibration
- All Machined Cast-Iron Internal Structure
- Inboard and outboard arbor bearings
- Powder coated paint