



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0486 43" 25 HP 3-PHASE DOUBLE WIDE-BELT SANDER

Product Dimensions:

Weight..... 3456 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 63 x 59-1/2 x 79 in.
Footprint (Length x Width)..... 61 x 31 in.

Shipping Dimensions:

Type..... Wood Slat Crate
Content..... Machine
Weight..... 3545 lbs.
Length x Width x Height..... 66 x 63 x 86 in.
Must Ship Upright..... Yes

Electrical:

Power Requirement..... 220V or 440V, 3-Phase, 60 Hz
Prewired Voltage..... 220V
Full-Load Current Rating..... 72.1A at 220V, 36.1A at 440V
Minimum Circuit Size..... 90A at 220V, 50A at 440V
Connection Type..... Permanent (Hardwire to Shutoff Switch)
Switch Type..... Control Panel w/Magnetic Switch Protection
Voltage Conversion Kit..... G440VG0486 for 440V

Motors:

Main

Horsepower..... 25 HP
Phase..... 3-Phase
Amps..... 64.9A/32.5A
Speed..... 1765 RPM
Type..... TEFC Induction
Power Transfer Front: Twin V-Belt, Rear: Triple V-Belt
Bearings..... Sealed & Permanently Lubricated
Centrifugal Switch/Contacts Type..... N/A

Feed

Horsepower..... 2 HP
Phase..... 3-Phase
Amps..... 6A/3A
Speed..... 1710 RPM
Type..... TEFC Induction
Power Transfer V-Belt Drive
Bearings..... Sealed & Permanently Lubricated
Centrifugal Switch/Contacts Type..... N/A

Table Elevation

Horsepower.....	1/4 HP
Phase.....	3-Phase
Amps.....	1.2A/0.6A
Speed.....	1650 RPM
Type.....	TEFC Induction
Power Transfer	V-Belt Drive
Bearings.....	Sealed & Permanently Lubricated
Centrifugal Switch/Contacts Type.....	N/A

Main Specifications:

Operation Information

Number of Sanding Heads.....	2
Maximum Board Width.....	43 in.
Minimum Board Width.....	2 in.
Maximum Board Thickness.....	6 in.
Minimum Board Thickness.....	3/16 in.
Minimum Board Length.....	11 in.
Sandpaper Speed.....	Front 3500, Rear 2600 FPM
Sanding Belt Oscillations.....	5/8 – 3/4 in.
Conveyor Feed Rate.....	14 – 60 FPM
Sandpaper Length.....	75 in.
Sandpaper Width.....	43 in.

Drum Information

Infeed Sanding Drum Type.....	Spiral Grooved Rubber
Infeed Sanding Drum Size.....	Front 8, Rear 4 in.
Outfeed Sanding Drum Type.....	Steel
Outfeed Sanding Drum Size.....	3 in.
Shore Hardness (Durometer).....	65 Shore

Platen Information

Platen Type.....	Adjustable
Platen Length.....	44-1/4 in.
Platen Width.....	2-1/4 in.
Platen Travel.....	0 – 2 mm

Construction

Conveyor Belt.....	Rubber
Body.....	Steel
Paint Type/Finish.....	Powder Coated

Other Related Information

Floor To Table Height.....	32 in.
Belt Tracking.....	Pneumatic
Sanding Belt Tension.....	Pneumatic
Number of Pressure Rollers.....	3
Pressure Roller Type.....	Rubber
Pressure Roller Size.....	1.57 in.
Conveyor Belt Length.....	102-1/4 in.
Conveyor Belt Width.....	43-1/4 in.
Belt Roller Size.....	Front 4, Rear 5 in.
Number of Dust Ports.....	10
Dust Port Size.....	4 in.
Air Requirement.....	75 PSI

Other Specifications:

Country of Origin Taiwan
Warranty 1 Year
Approximate Assembly & Setup Time 1 Hour
Serial Number Location ID Label Below Grizzly Nameplate
ISO 9001 Factory Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) Yes

Features:

Pneumatic Belt Tensioning
Industrial-Duty Rubber Conveyor Belt
Ten 4" Dust Ports
Variable-Speed Feed Conveyor
Amp/Load Meter
Built-In Air Regulator/Water Separator
Independent Motor Controls for Sanding Drums, Table Elevation and Conveyor
Disc Brake
Emergency Stop Bar
Adjustable Sanding Belt Oscillation Speed
Micro-Adjustable Graphite/Felt Platen (Rear Drum)
Rubber Infeed and Outfeed Pressure Rollers
Sturdy 4-Column Table Lifting and Lowering System
Powered Table Elevation with Keypad for Typing/Storing Exact Measurements
Digital Readout Displays Table Height in Increments of 0.005" for Super-Accurate Results
Hard Rubber Infeed Drum