



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0524 STRAIGHT LINE RIP SAW

Product Dimensions:

Weight..... 1980 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 43-1/2 x 61-1/4 x 80-1/2 in.
Footprint (Length x Width)..... 35 x 35 in.

Shipping Dimensions:

Type..... Wood Crate
Content..... Machine
Weight..... 2243 lbs.
Length x Width x Height..... 59 x 46 x 64 in.
Must Ship Upright..... Yes

Electrical:

Power Requirement..... 220V or 440V, 3-Phase, 60 Hz
Prewired Voltage..... 220V
Full-Load Current Rating..... 50A at 220V, 25A at 440V
Minimum Circuit Size..... 70A at 220V, 35A at 440V
Connection Type..... Permanent (Hardwire to Shutoff Switch)
Switch Type..... Control Panel w/Magnetic Switch Protection
Voltage Conversion Kit..... P0524067 for 440V
Recommended Phase Converter..... G7979

Motors:

Feed

Type..... TEFC Induction
Horsepower..... 2 HP
Phase..... 3-Phase
Amps..... 6A/3A
Speed..... 1720 RPM
Power Transfer V-Belt Drive
Bearings..... Shielded & Permanently Lubricated

Main

Type..... TEFC Induction
Horsepower..... 15 HP
Phase..... 3-Phase
Amps..... 44A/22A
Speed..... 1720 RPM
Power Transfer V-Belt Drive
Bearings..... Shielded & Permanently Lubricated

Other Specifications:

Country of Origin Taiwan
Warranty 1 Year
Approximate Assembly & Setup Time 15 Minutes
Serial Number Location ID Label on Front Cover
ISO 9001 Factory No
Certified by a Nationally Recognized Testing Laboratory (NRTL) No

Features:

- Extra Long Infeed Table and Rip Fence for Handling Large Workpieces
- Includes Auxiliary Hold-Down Roller Kit
- Variable Feed Conveyor
- 4 Heavy-Duty Pressure Rollers
- Adjustable Automatic Conveyor Track Lubrication System
- Convenient and Easy-To-Reach Control Panel
- Double Row of Anti-Kickback Fingers
- Dual Bearing Driveline for Conveyor Table
- Dual Spindle Elevation Lock
- Exclusive 6" Wide Chain Feeding Conveyor Table for Smooth Operation