



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0555 THE ULTIMATE 14" BANDSAW

Product Dimensions:

Weight..... 167 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 26-3/8 x 30-1/4 x 66-1/2 in.
Footprint (Length x Width)..... 24-1/2 x 17-1/2 in.

Shipping Dimensions:

Type..... Cardboard Box
Content..... Machine
Weight..... 199 lbs.
Length x Width x Height..... 44 x 21 x 20 in.
Must Ship Upright..... No

Electrical:

Power Requirement..... 110V or 220V, Single-Phase, 60 Hz
Prewired Voltage..... 110V
Full-Load Current Rating..... 11A at 110V, 5.5A at 220V
Minimum Circuit Size..... 15A at 110V, 15A at 220V
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 6 ft.
Power Cord Gauge..... 16 AWG
Plug Included..... Yes
Included Plug Type..... 5-15 for 110V
Recommended Plug Type..... 6-15 for 220V
Switch Type..... ON/OFF Push Button Switch

Motors:

Main

Horsepower..... 1 HP
Phase..... Single-Phase
Amps..... 11A/5.5A
Speed..... 1725 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Belt Drive
Bearings..... Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type..... External

Main Specifications:

Main Specifications

Bandsaw Size..... 14 in.
Max Cutting Width (Left of Blade)..... 13-1/2 in.
Max Cutting Width (Left of Blade) w/Fence..... 11-7/8 in.
Max Cutting Height (Resaw Height)..... 6 in.
Blade Speeds..... 1500, 3200 FPM

Blade Information

Standard Blade Length..... 93-1/2 in.
Blade Length Range..... 92-1/2 – 93-1/2 in.
Blade Width Range..... 1/8 – 3/4 in.
Type of Blade Guides..... Ball Bearing
Guide Post Adjustment Type..... Manual
Has Quick-Release..... Yes

Table Information

Table Length..... 14 in.
Table Width..... 14 in.
Table Thickness..... 1-1/2 in.
Table Tilt..... Left 15, Right 45 deg.
Table Tilt Adjustment Type..... Manual
Floor-to-Table Height..... 43-5/16 in.
Fence Locking Position..... Front
Fence is Adjustable for Blade Lead..... Yes
Resaw Fence Attachment Included..... No
Miter Gauge Included..... Yes

Construction Materials

Table..... Precision Ground Cast Iron
Trunnion..... Aluminum
Fence..... Deluxe Extruded Aluminum
Base/Stand..... Pre-Formed Steel
Frame/Body..... Cast Iron
Wheels..... Computer-Balanced Cast Aluminum
Tire..... Rubber
Wheel Cover Pre-Formed Steel
Paint Type/Finish..... Powder Coating & Ure

Other Related Information

Wheel Diameter..... 13-3/4 in.
Wheel Width..... 1-3/16 in.
Number of Dust Ports..... 1
Dust Port Size..... 4 in.
Compatible Mobile Base..... D2057A

Other Specifications:

Country of Origin Taiwan
Warranty 1 Year
Approximate Assembly & Setup Time 1 Hour
Serial Number Location ID Label on Top Cover
ISO 9001 Factory Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) Yes
Awards Popular Woodworking Best New Tool 2003

Features:

- Upper and Lower Ball Bearing Blade Guides
- Green and Putty Powder-Coat Paint
- Deluxe Heavy-Duty Stand
- Cast-Iron Frame
- Quick Release Blade Tension
- Magnifying Window Over Fence Scale
- Deluxe Extruded Aluminum Rip Fence
- 4" Dust Port
- Hinged Wheel Covers
- Included 3/8" Blade
- Included Miter Gauge
- Maximum Cutting Height 12" With Optional Riser Block Installed
- Computer Balanced Cast Aluminum Wheels with Rubber Tires
- All Ball Bearing Construction