



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0555 THE CLASSIC 14" BANDSAW

### Product Dimensions:

Weight..... 167 lbs.  
Width (side-to-side) x Depth (front-to-back) x Height..... 26-3/8 x 30-1/4 x 66-1/2 in.  
Footprint (Length x Width)..... 24-1/2 x 17-1/2 in.

### Shipping Dimensions:

Type..... Cardboard Box  
Content..... Machine  
Weight..... 199 lbs.  
Length x Width x Height..... 44 x 21 x 20 in.  
Must Ship Upright..... No

### Electrical:

Power Requirement..... 110V or 220V, Single-Phase, 60 Hz  
Prewired Voltage..... 110V  
Full-Load Current Rating..... 11A at 110V, 5.5A at 220V  
Minimum Circuit Size..... 15A at 110V, 15A at 220V  
Connection Type..... Cord & Plug  
Power Cord Included..... Yes  
Power Cord Length..... 6 ft.  
Power Cord Gauge..... 16 AWG  
Plug Included..... Yes  
Included Plug Type..... 5-15 for 110V  
Recommended Plug Type..... 6-15 for 220V  
Switch Type..... ON/OFF Push Button Switch

### Motors:

#### Main

Horsepower..... 1 HP  
Phase..... Single-Phase  
Amps..... 11A/5.5A  
Speed..... 1725 RPM  
Type..... TEFC Capacitor-Start Induction  
Power Transfer ..... Belt Drive  
Bearings..... Shielded & Permanently Lubricated  
Centrifugal Switch/Contacts Type..... External

### Main Specifications:

#### Main Specifications

Bandsaw Size..... 14 in.  
Max Cutting Width (Left of Blade)..... 13-1/2 in.  
Max Cutting Width (Left of Blade) w/Fence..... 11-7/8 in.  
Max Cutting Height (Resaw Height)..... 6 in.  
Blade Speeds..... 1500, 3200 FPM

**Blade Information**

Standard Blade Length..... 93-1/2 in.  
Blade Length Range..... 92-1/2 – 93-1/2 in.  
Blade Width Range..... 1/8 – 3/4 in.  
Type of Blade Guides..... Ball Bearing  
Guide Post Adjustment Type..... Manual  
Has Quick-Release..... Yes

**Table Information**

Table Length..... 14 in.  
Table Width..... 14 in.  
Table Thickness..... 1-1/2 in.  
Table Tilt..... Left 15, Right 45 deg.  
Table Tilt Adjustment Type..... Manual  
Floor-to-Table Height..... 43-5/16 in.  
Fence Locking Position..... Front  
Fence is Adjustable for Blade Lead..... Yes  
Resaw Fence Attachment Included..... No  
Miter Gauge Included..... Yes

**Construction Materials**

Table..... Precision Ground Cast Iron  
Trunnion..... Aluminum  
Fence..... Deluxe Extruded Aluminum  
Base/Stand..... Pre-Formed Steel  
Frame/Body..... Cast Iron  
Wheels..... Computer-Balanced Cast Aluminum  
Tire..... Rubber  
Wheel Cover ..... Pre-Formed Steel  
Paint Type/Finish..... Powder Coating & Ure

**Other Related Information**

Wheel Diameter..... 13-3/4 in.  
Wheel Width..... 1-3/16 in.  
Number of Dust Ports..... 1  
Dust Port Size..... 4 in.  
Compatible Mobile Base..... D2057A

**Other Specifications:**

Country of Origin ..... Taiwan  
Warranty ..... 1 Year  
Approximate Assembly & Setup Time ..... 1 Hour  
Serial Number Location ..... ID Label on Top Cover  
ISO 9001 Factory ..... Yes  
Certified by a Nationally Recognized Testing Laboratory (NRTL) ..... Yes  
Awards ..... Popular Woodworking Best New Tool 2003

**Features:**

- Upper and Lower Ball Bearing Blade Guides
- Green and Putty Powder-Coat Paint
- Deluxe Heavy-Duty Stand
- Cast-Iron Frame
- Quick Release Blade Tension
- Magnifying Window Over Fence Scale
- Deluxe Extruded Aluminum Rip Fence
- 4" Dust Port
- Hinged Wheel Covers
- Included 3/8" Blade
- Included Miter Gauge
- Maximum Cutting Height 12" With Optional Riser Block Installed
- Computer Balanced Cast Aluminum Wheels with Rubber Tires
- All Ball Bearing Construction