



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0555LA35 14" 1 HP DELUXE BANDSAW - 35TH ANNIVERSARY EDITION

### Product Dimensions:

Weight..... 229 lbs.  
Width (side-to-side) x Depth (front-to-back) x Height..... 27 x 30 x 67-1/2 in.  
Footprint (Length x Width)..... 23-1/2 x 16-1/2 in.

### Shipping Dimensions:

#### Carton #1

Type..... Cardboard Box  
Content..... Machine  
Weight..... 205 lbs.  
Length x Width x Height..... 46 x 22 x 19 in.

#### Carton #2

Type..... Cardboard Box  
Content..... Stand  
Weight..... 42 lbs.  
Length x Width x Height..... 29 x 24 x 9 in.

### Electrical:

Power Requirement..... 110V or 220V, Single-Phase, 60 Hz  
Prewired Voltage..... 110V  
Full-Load Current Rating..... 11A at 110V, 5.5A at 220V  
Minimum Circuit Size..... 15A  
Power Cord Included..... Yes  
Power Cord Length..... 10 ft.  
Power Cord Gauge..... 16 AWG  
Plug Included..... Yes  
Included Plug Type..... 5-15  
Recommended Plug Type..... 6-15 for 220V  
Switch Type..... ON/OFF Push-Button Switch w/Padlock

### Motors:

#### Main

Horsepower..... 1 HP  
Phase..... Single-Phase  
Amps..... 11A/5.5A  
Speed..... 1725 RPM  
Type..... TEFC Capacitor-Start Induction  
Power Transfer ..... Belt Drive  
Bearings..... Shielded & Permanently Lubricated  
Centrifugal Switch/Contacts Type..... External

**Main Specifications:**

**Main Specifications**

Bandsaw Size.....	14 in.
Max Cutting Width (Left of Blade).....	13-1/2 in.
Max Cutting Width (Left of Blade) w/Fence.....	11-7/8 in.
Max Cutting Height (Resaw Height).....	6 in.
Blade Speeds.....	1800, 3100 FPM

**Blade Information**

Standard Blade Length.....	93-1/2 in.
Blade Length Range.....	92-1/2 - 93-1/2 in.
Blade Width Range.....	1/8 - 3/4 in.
Type of Blade Guides.....	Ball Bearing
Guide Post Adjustment Type.....	Rack and Pinion
Has Quick-Release.....	Yes

**Table Information**

Table Length.....	14 in.
Table Width.....	14 in.
Table Thickness.....	1-1/2 in.
Table Tilt.....	Left 10, Right 45 Deg.
Table Tilt Adjustment Type.....	Manual
Floor-to-Table Height.....	43 in.
Fence Locking Position.....	Front
Fence is Adjustable for Blade Lead.....	Yes
Resaw Fence Attachment Included.....	No
Miter Gauge Included.....	Yes

**Construction Materials**

Table.....	Precision Ground Cast Iron
Trunnion.....	Aluminum
Fence.....	Deluxe Extruded Aluminum
Base/Stand.....	Pre-Formed Steel
Frame/Body.....	Cast Iron
Wheels.....	Computer-Balanced Cast Iron
Tire.....	Rubber
Wheel Cover .....	Pre-Formed Steel
Paint Type/Finish.....	Powder Coating

**Other Related Information**

Wheel Diameter.....	13-3/4 in.
Wheel Width.....	1-3/16 in.
Number of Dust Ports.....	1
Dust Port Size.....	4 in.
Compatible Mobile Base.....	D3757

**Other Specifications:**

Country of Origin .....	Taiwan
Warranty .....	1 Year
Approximate Assembly & Setup Time .....	1-1/2 Hours
Serial Number Location .....	Machine ID Label
ISO 9001 Factory .....	No
Certified by a Nationally Recognized Testing Laboratory (NRTL) .....	Yes

**Features:**

- Deluxe Heavy-Duty Stand
- Upper & Lower Ball-Bearing Blade Guides
- All Ball-Bearing Construction
- 4" Dust Port
- Includes 3/8" Blade
- Includes Fence and Miter Gauge
- Quick-Release Blade Tension Lever
- Fence Scale with Magnifying Window