



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0555LANV 14" DELUXE BANDSAW - ANNIVERSARY EDITION

Product Dimensions:

Weight..... 229 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 27 x 30 x 67-1/2 in.
Footprint (Length x Width)..... 23-1/2 x 16-1/2 in.

Shipping Dimensions:

Carton #1

Type..... Cardboard Box
Content..... Machine
Weight..... 205 lbs.
Length x Width x Height..... 46 x 22 x 19 in.

Carton #2

Type..... Cardboard Box
Content..... Stand
Weight..... 42 lbs.
Length x Width x Height..... 29 x 24 x 9 in.

Electrical:

Power Requirement..... 110V or 220V, Single-Phase, 60 Hz
Prewired Voltage..... 110V
Full-Load Current Rating..... 11A at 110V, 5.5A at 220V
Minimum Circuit Size..... 15A
Power Cord Included..... Yes
Power Cord Length..... 10 ft.
Power Cord Gauge..... 16 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Recommended Plug Type..... 6-15 for 220V
Switch Type..... ON/OFF Push-Button Switch w/Padlock

Motors:

Main

Horsepower..... 1 HP
Phase..... Single-Phase
Amps..... 11A/5.5A
Speed..... 1725 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Belt Drive
Bearings..... Shielded & Permanently Sealed
Centrifugal Switch/Contacts Type..... External

Main Specifications:

Main Specifications

| | |
|--|----------------|
| Bandsaw Size..... | 14 in. |
| Max Cutting Width (Left of Blade)..... | 13-1/2 in. |
| Max Cutting Width (Left of Blade) w/Fence..... | 11-7/8 in. |
| Max Cutting Height (Resaw Height)..... | 6 in. |
| Blade Speeds..... | 1800, 3100 FPM |

Blade Information

| | |
|---------------------------------|---------------------|
| Standard Blade Length..... | 93-1/2 in. |
| Blade Length Range..... | 92-1/2 – 93-1/2 in. |
| Blade Width Range..... | 1/8 – 3/4 in. |
| Type of Blade Guides..... | Ball Bearing |
| Guide Post Adjustment Type..... | Manual |
| Has Quick-Release..... | Yes |

Table Information

| | |
|---|------------------------|
| Table Length..... | 14 in. |
| Table Width..... | 14 in. |
| Table Thickness..... | 1-1/2 in. |
| Table Tilt..... | Left 10, Right 45 deg. |
| Table Tilt Adjustment Type..... | Manual |
| Floor-to-Table Height..... | 43 in. |
| Fence Locking Position..... | Front |
| Fence is Adjustable for Blade Lead..... | Yes |
| Resaw Fence Attachment Included..... | No |
| Miter Gauge Included..... | Yes |

Construction Materials

| | |
|------------------------|-----------------------------|
| Table..... | Precision Ground Cast Iron |
| Trunnion..... | Aluminum |
| Fence..... | Deluxe Extruded Aluminum |
| Base/Stand..... | Pre-Formed Steel |
| Frame/Body..... | Cast Iron |
| Wheels..... | Computer-Balanced Cast Iron |
| Tire..... | Rubber |
| Wheel Cover | Pre-Formed Steel |
| Paint Type/Finish..... | Powder Coating & Ure |

Other Related Information

| | |
|-----------------------------|------------|
| Wheel Diameter..... | 13-3/4 in. |
| Wheel Width..... | 1-3/16 in. |
| Number of Dust Ports..... | 1 |
| Dust Port Size..... | 4 in. |
| Compatible Mobile Base..... | D3757 |

Other Specifications:

| | |
|--|-----------------------|
| Country of Origin | Taiwan |
| Warranty | 1 Year |
| Approximate Assembly & Setup Time | 1-1/2 Hours |
| Serial Number Location | ID Label on Top Cover |
| ISO 9001 Factory | No |
| Certified by a Nationally Recognized Testing Laboratory (NRTL) | Yes |

Features:

- Deluxe Heavy-Duty Stand
- Upper & Lower Ball-Bearing Blade Guides
- All Ball-Bearing Construction
- 4" Dust Port
- Includes 3/8" Blade
- Includes Fence and Miter Gauge
- Quick-Release Blade Tension Lever
- Fence Scale With Magnifying Window