



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0555X 14" 1-1/2 HP EXTREME SERIES BANDSAW

### Product Dimensions:

Weight..... 236 lbs.  
Width (side-to-side) x Depth (front-to-back) x Height..... 30 x 26 x 67-1/4 in.  
Footprint (Length x Width)..... 17-1/4 x 16 in.

### Shipping Dimensions:

#### Carton #1

Type..... Cardboard Box  
Content..... Machine  
Weight..... 199 Lbs.  
Length x Width x Height..... 21 x 41 x 20 in.  
Must Ship Upright..... No

#### Carton #2

Type..... Cardboard Box  
Content..... Stand  
Weight..... 60 Lbs.  
Length x Width x Height..... 17 x 18 x 26 in.  
Must Ship Upright..... No

### Electrical:

Power Requirement..... 110V or 220V, Single-Phase, 60 Hz  
Prewired Voltage..... 110V  
Full-Load Current Rating..... 15A at 110V, 7.5A at 220V  
Minimum Circuit Size..... 20A at 110V, 15A at 220V  
Connection Type..... Cord & Plug  
Power Cord Included..... Yes  
Power Cord Length..... 6 ft.  
Power Cord Gauge..... 14 AWG  
Plug Included..... Yes  
Included Plug Type..... 5-15 for 110V  
Recommended Plug Type..... 6-15 for 220V  
Switch Type..... ON/OFF Push Button Switch

### Motors:

#### Main

Horsepower..... 1.5 HP  
Phase..... Single-Phase  
Amps..... 15A/7.5A  
Speed..... 1725 RPM  
Type..... TEFC Capacitor-Start Induction  
Power Transfer ..... Belt Drive  
Bearings..... Shielded & Permanently Lubricated  
Centrifugal Switch/Contacts Type..... External

**Main Specifications:**

**Main Specifications**

Bandsaw Size.....	14 in.
Max Cutting Width (Left of Blade).....	13-1/2 in.
Max Cutting Width (Left of Blade) w/Fence.....	12-1/4 in.
Max Cutting Height (Resaw Height).....	6 in.
Blade Speeds.....	3000 FPM

**Blade Information**

Standard Blade Length.....	93-1/2 in.
Blade Length Range.....	92-1/2 – 93-1/2 in.
Blade Width Range.....	1/8 – 3/4 in.
Type of Blade Guides.....	Ball Bearing
Guide Post Adjustment Type.....	Manual
Has Quick-Release.....	Yes

**Table Information**

Table Length.....	14 in.
Table Width.....	20-1/2 in.
Table Thickness.....	1-1/2 in.
Table Tilt.....	Left 15, Right 45 deg.
Table Tilt Adjustment Type.....	Manual
Floor-to-Table Height.....	44 in.
Fence Locking Position.....	Front
Fence is Adjustable for Blade Lead.....	Yes
Resaw Fence Attachment Included.....	Yes
Miter Gauge Included.....	Yes

**Construction Materials**

Table.....	Precision Ground Cast Iron
Trunnion.....	Aluminum
Fence.....	Extruded Aluminum and Cast Iron
Base/Stand.....	Pre-Formed Steel
Frame/Body.....	Cast Iron
Wheels.....	Computer-Balanced Cast Iron
Tire.....	Rubber
Wheel Cover .....	Pre-Formed Steel
Paint Type/Finish.....	Powder Coating

**Other Related Information**

Wheel Diameter.....	13-3/4 in.
Wheel Width.....	1-3/16 in.
Number of Dust Ports.....	1
Dust Port Size.....	4 in.
Compatible Mobile Base.....	D2260A

**Other Specifications:**

Country of Origin .....	Taiwan
Warranty .....	1 Year
Approximate Assembly & Setup Time .....	1-1/2 Hours
Serial Number Location .....	ID Label on Top Cover
ISO 9001 Factory .....	Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) .....	Yes
Awards .....	Popular Woodworking Best New Tool 2003

**Features:**

- Upper and Lower Ball Bearing Blade Guides
- Green and Putty Powder Coat
- Deluxe Heavy-Duty Cabinet w/Storage Shelves
- Cast-Iron Frame
- Quick Release Blade Tension
- Magnifying Window Over Fence Scale
- Cast-Iron Rip Fence
- 4" Dust Port
- Hinged Wheel Covers
- Included 3/8" Blade
- Included Miter Gauge
- Maximum Cutting Height 12" With Optional Riser Block Installed
- Computer Balanced Cast-Iron Wheels with Rubber Tires
- Extruded Aluminum Resaw Fence Attachment Included
- Work Light
- Lower Wheel Brush