



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0555XH 14" 1-3/4 HP EXTREME SERIES RESAW BANDSAW

Product Dimensions:

Weight..... 276 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 26 x 31 x 78 in.
Footprint (Length x Width)..... 16 x 18 in.

Shipping Dimensions:

Type..... Wood Crate
Content..... Machine
Weight..... 337 lbs.
Length x Width x Height..... 22 x 23 x 80 in.
Must Ship Upright..... Yes

Electrical:

Power Requirement..... 110V or 220V, Single-Phase, 60 Hz
Prewired Voltage..... 110V
Full-Load Current Rating..... 15A at 110V, 7.5A at 220V
Minimum Circuit Size..... 20A at 110V, 15A at 220V
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 6 ft.
Power Cord Gauge..... 14 AWG
Plug Included..... Yes
Included Plug Type..... 5-15 for 110V
Recommended Plug Type..... 6-15 for 220V
Switch Type..... ON/OFF Push Button Switch

Motors:

Main

Horsepower..... 1.75 HP
Phase..... Single-Phase
Amps..... 15A/7.5A
Speed..... 1720 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Belt Drive
Bearings..... Shielded & Permanently Lubricated

Main Specifications:

Main Specifications

Bandsaw Size..... 14 in.
Max Cutting Width (Left of Blade)..... 13-1/2 in.
Max Cutting Width (Left of Blade) w/Fence..... 12 in.
Max Cutting Height (Resaw Height)..... 12 in.
Blade Speeds..... 3000 FPM

Blade Information

Standard Blade Length..... 105 in.
Blade Length Range..... 104 - 105 in.
Blade Width Range..... 1/8 - 3/4 in.
Type of Blade Guides..... Ball Bearing
Guide Post Adjustment Type..... Rack & Pinion
Has Quick-Release..... Yes

Table Information

Table Length..... 16-1/8 in.
Table Width..... 21-3/4 in.
Table Thickness..... 1-1/2 in.
Table Tilt..... Left 5, Right 45 deg.
Table Tilt Adjustment Type..... Manual
Floor-to-Table Height..... 44-5/8 in.
Fence Locking Position..... Front
Fence is Adjustable for Blade Lead..... Yes
Resaw Fence Attachment Included..... Yes
Miter Gauge Included..... Yes

Construction Materials

Table..... Precision-Ground Cast Iron
Trunnion..... Cast Aluminum
Fence..... Extruded Aluminum and Cast Iron
Base/Stand..... Pre-Formed Steel
Frame/Body..... Cast Iron
Wheels..... Computer-Balanced Cast Iron
Tire..... Polyurethane
Wheel Cover Pre-Formed Steel
Paint Type/Finish..... Powder Coated

Other Related Information

Wheel Diameter..... 14 in.
Wheel Width..... 1-3/16 in.
Number of Dust Ports..... 1
Dust Port Size..... 4 in.
Compatible Mobile Base..... D2260A

Other Specifications:

Country of Origin Taiwan
Warranty 1 Year
Approximate Assembly & Setup Time 30 Minutes
Serial Number Location ID Label on Top Cover
ISO 9001 Factory Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) Yes

Features:

- Upper and Lower Ball Bearing Blade Guides
- Green and Putty Powder-Coat Finish
- Deluxe Heavy-Duty Cabinet w/Storage Shelves
- Cast-Iron Frame
- Quick-Release Blade Tension
- Magnifying Window Over Fence Scale
- 4" Dust Port
- Hinged Wheel Covers
- Included 3/8" Blade
- Included Miter Gauge
- Maximum Cutting Height 12-1/4"
- Computer Balanced Cast-Iron Wheels with Rubber Tires
- Extruded-Aluminum Resaw Fence Included
- Work Light
- Lower Wheel Brush