



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0574 GUITAR FRETBOARD RADIUSING SANDER

Product Dimensions:

Weight..... 172 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 42-1/2 x 32 x 74 in.
Footprint (Length x Width)..... 21-3/4 x 14-3/4 in.

Shipping Dimensions:

Carton #1

Type..... Cardboard Box
Content..... Machine
Weight..... 190 lbs.
Length x Width x Height..... 46 x 45 x 16 in.
Must Ship Upright..... Yes

Carton #2

Type..... Cardboard Box
Content..... Attachment
Weight..... 62 lbs.
Length x Width x Height..... 39 x 18 x 11 in.
Must Ship Upright..... No

Electrical:

Power Requirement..... 110V or 220V, Single-Phase, 60 Hz
Prewired Voltage..... 220V
Full-Load Current Rating..... 20A at 110V, 10A at 220V
Minimum Circuit Size..... 30A at 110V, 15A at 220V
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 10 ft.
Power Cord Gauge..... 16 AWG
Plug Included..... No
Recommended Plug Type..... L5-30 for 110V, 6-15 for 220V
Switch Type..... Paddle Safety Switch w/Removable Key

Motors:

Main

Horsepower..... 1.5 HP
Phase..... Single-Phase
Amps..... 20A/10A
Speed..... 1725 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer..... Direct Drive
Bearings..... Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type..... External

Main Specifications:

Operation Information

Sanding Belt Speed..... 1800 FPM
Sanding Belt Length..... 80 in.
Sanding Belt Width..... 6 in.

Platen Information

Platen Type..... Graphite Coated
Platen Length..... 29-3/4 in.
Platen Width..... 6-3/4 in.

Construction

Frame..... Steel
Base..... Steel
Drive Roller..... Aluminum
Idler Roller..... Rubber
Paint Type/Finish..... Powder Coated

Other Related Information

Number of Dust Ports..... 1
Dust Port Size..... 4 in.
Belt Release..... Quick Release
Drive Roller Size..... 4-1/4 in.
Idler Roller Size..... 3-1/2 in.
Mobile Base..... D2260A

Other Specifications:

Country of Origin Taiwan
Warranty 1 Year
Approximate Assembly & Setup Time 30 Minutes
Serial Number Location ID Label on Stand
ISO 9001 Factory No
Certified by a Nationally Recognized Testing Laboratory (NRTL) No

Features:

Quick Belt Release
Micro Adjustment Knob for Sanding Height
30" Maximum Workpiece Length
15"-5 1/2" Maximum Workpiece Thickness
10"-16" Fretboard Radius