



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0636X 17" 5 HP ULTIMATE BANDSAW

### Product Dimensions:

Weight..... 620 lbs.  
Width (side-to-side) x Depth (front-to-back) x Height..... 35-1/4 x 33-3/4 x 78-1/2 in.  
Footprint (Length x Width)..... 29-1/2 x 23-1/2 in.

### Shipping Dimensions:

Type..... Wood Slat Crate  
Content..... Machine  
Weight..... 784 lbs.  
Length x Width x Height..... 36 x 28 x 88 in.  
Must Ship Upright..... Yes

### Electrical:

Power Requirement..... 230V, Single-Phase, 60 Hz  
Full-Load Current Rating..... 22A  
Minimum Circuit Size..... 30A  
Connection Type..... Cord & Plug  
Power Cord Included..... No  
Recommended Power Cord..... "S"-Type, 3-Wire, 10 AWG, 300 VAC for 220V  
Plug Included..... No  
Recommended Plug Type..... L6-30  
Switch Type..... Control Panel w/Magnetic Switch Protection & Lockout Key

### Motors:

#### Main

Horsepower..... 5 HP  
Phase..... Single-Phase  
Amps..... 22A  
Speed..... 1725 RPM  
Type..... TEFC Capacitor-Start Induction  
Power Transfer ..... Belt Drive  
Bearings..... Shielded & Permanently Lubricated  
Centrifugal Switch/Contacts Type..... External

### Main Specifications:

#### Main Specifications

Bandsaw Size..... 17 in.  
Max Cutting Width (Left of Blade)..... 16-1/2 in.  
Max Cutting Width (Left of Blade) w/Fence..... 15-1/4 in.  
Max Cutting Height (Resaw Height)..... 16 in.  
Blade Speeds..... 4500 FPM

#### Blade Information

Standard Blade Length..... 162 in.  
Blade Length Range..... 160 – 162 in.  
Blade Width Range..... 1/8 – 1-3/8 in.  
Type of Blade Guides..... Double Ball Bearing  
Guide Post Adjustment Type..... Rack & Pinion  
Has Quick-Release..... Yes

**Table Information**

Table Length.....	21"
Table Width.....	25-1/2"
Table Thickness.....	2"
Table Tilt.....	Left 5°, Right 45°
Table Tilt Adjustment Type.....	Rack & Pinion
Floor-to-Table Height.....	35-1/2 in.
Fence Locking Position.....	Front
Fence is Adjustable for Blade Lead.....	Yes
Resaw Fence Attachment Included.....	Yes
Miter Gauge Included.....	Yes

**Construction Materials**

Table.....	Precision Ground Cast Iron
Trunnion.....	Cast Iron
Fence.....	Deluxe Extruded Aluminum
Base/Stand.....	Pre-Formed Steel
Frame/Body.....	Pre-Formed Steel
Wheels.....	Computer-Balanced Cast Iron
Tire.....	Rubber
Wheel Cover .....	Pre-Formed Steel
Paint Type/Finish.....	Powder Coated

**Other Related Information**

Wheel Diameter.....	17 in.
Wheel Width.....	1-3/4 in.
Number of Dust Ports.....	2
Dust Port Size.....	4 in.
Compatible Mobile Base.....	D2058A

**Other Specifications:**

Country of Origin .....	Taiwan
Warranty .....	1 Year
Approximate Assembly & Setup Time .....	1 Hour
Serial Number Location .....	ID Label on Upper Wheel Cover
ISO 9001 Factory .....	Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) .....	Yes

**Features:**

- Ball Bearing Blade Guides
- Green and Putty Powder-Coat Paint
- Blade Tension Indicator
- Blade Tracking Window
- Quick Change Blade Release/Tensioning
- Fence Includes Adjustable Pointer
- Two 4" Dust Ports
- Hinged Wheel Covers
- Micro-Adjusting Rack & Pinion Table Tilt
- Height Scale Measurement
- Includes 1" Blade
- Included Miter Gauge
- Cast-Iron Table Trunnion
- Heavy-Duty Quick-Lock Cast-Iron Fence with Removable Resaw Fence
- Computer Balanced Cast-Iron Wheels with Grizzly Bear Head Cut-Outs
- Rack and Pinion Upper Guide Adjustment
- Foot Brake Stop
- Optional Extension Table with Support